Printing date 04/04/2023 Reviewed on 04/04/2023

1 Identification

· Product identifier

· Trade name: Sodium Acetate / Toluene Solution

· Article number: ERL081

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 1 H370 Causes damage to the central nervous system and

the visual organs.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Toxicity - Oral 4 H302 Harmful if swallowed.

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled. Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3

H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / **Toluene Solution**

(Contd. of page 1)

· Hazard pictograms







GHS02

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Methanol

Toluene

Isopropanol

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system and the visual organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-88-3	Toluene	51.287%
CAS: 67-56-1	Methanol	23.166%
CAS: 67-63-0	Isopropanol	22.976%
· Table of Nonhazardous Ingredients		
CAS: 7732-18-3	5 Water	1.754%
CAS: 6131-90-4	Sodium Acetate Trihydrate	0.817%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:			
CAS: 108-88-3	Toluene	67 pp	m
CAS: 67-56-1	Methanol	530 p	рт
CAS: 67-63-0	Isopropanol	400 p	рт
CAS: 6131-90-4	Sodium Acetate Trihydrate	11 m _ξ	g/m³
· PAC-2:			
CAS: 108-88-3	Toluene	560 ppi	m
CAS: 67-56-1	Methanol	2,100 p	рт
CAS: 67-63-0	Isopropanol	2000* j	ррт
CAS: 6131-90-4	Sodium Acetate Trihydrate	120 mg	ζ/m³
· PAC-3:			
CAS: 108-88-3	Toluene	3700* ppi	m
CAS: 67-56-1	Methanol	7200* ppi	m
CAS: 67-63-0	Isopropanol	12000**;	ррт
CAS: 6131-90-4	Sodium Acetate Trihydrate	690 mg/m	i^3

-US

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 4)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- $\cdot \textit{Control parameters}$
- · Components with limit values that require monitoring at the workplace:

CAS: 108-88-3 Toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

BEI, OTO, A4

CAS: 67-56-1 Methanol

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm

Long-term value: 260 mg/m³, 200 ppm

Skin

TLV Short-term value: 250 ppm

Long-term value: 200 ppm

Skin: BEI

CAS: 67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 400 ppm Long-term value: 200 ppm

BEI, A4

(Contd. on page 6)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 5)

· Ingredients with biological limit values:

CAS: 108-88-3 Toluene

BEI 0.02 mg/L

LD50 Intraperitoneal: blood

Time: prior to last shift of workweek

LD50: Toluene

 $0.03 \, mg/L$

LD50 Intraperitoneal: urine

Time: end of shift LD50: Toluene

0.3 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: o-Cresol with hydrolysis (background)

CAS: 67-56-1 Methanol

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 6)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

· Information on basic physical and c	hemical properties
· General Information · Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Organic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
· Flash point:	4 °C (39.2 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap-mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F):	$0.83279 \ g/cm^3 \ (6.94963 \ lbs/gal)$
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	

(Contd. on page 8)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

	(Contd. of pag
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	97.4 %
Water:	1.8 %
VOC content:	97.43 %
	811.4 g/l / 6.77 lb/gal
Solids content:	0.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· <i>LD/LC50</i> 1	· LD/LC50 values that are relevant for classification:		
ATE (Acut	ATE (Acute Toxicity Estimate)		
Oral	LD50	432 mg/kg	
Dermal	LD50	1,295 mg/kg	
Inhalative	LC50/4h	· ·	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Irritant

· Carcinogenic categories

· IARC (Internat	ional Agency for Research on Cancer)	
CAS: 108-88-3	Toluene	3
CAS: 67-63-0	Isopropanol	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 9)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 8)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1993

· UN proper shipping name

 $\cdot DOT$

Flammable liquids, n.o.s. (Toluene, Methanol, Isopropanol

· IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (Toluene, Methanol, Isopropanol

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

(Contd. on page 10)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

	(Contd. of page
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code)	
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	В
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
-	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUEN)
	METHANOL, ISOPROPANOL
), 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

•	an nyomanon avanaore.
· Sara	
· Section 355 (ex	tremely hazardous substances):
None of the ing	redients is listed.
· Section 313 (Sp	pecific toxic chemical listings):
CAS: 108-88-3	Toluene
CAS: 67-56-1	Methanol
CAS: 67-63-0	Isopropanol
· TSCA (Toxic S	ubstances Control Act):
Toluene	ACTIVE
	(Contd. on page 11)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

		(Contd. of page
Methanol		ACTIV
Isopropanol		ACTIV
Water		ACTIV
Hazardous Air P	Pollutants	
CAS: 108-88-3	Toluene	
CAS: 67-56-1	Methanol	
Proposition 65		
Chemicals know	n to cause cancer:	
None of the ingre	edients is listed.	
Chemicals know	n to cause reproductive toxicity for females:	
None of the ingre	edients is listed.	
Chemicals know	n to cause reproductive toxicity for males:	
None of the ingre	edients is listed.	
Chemicals know	n to cause developmental toxicity:	
CAS: 108-88-3	Toluene Toluene	
CAS: 67-56-1	Methanol	
Carcinogenic ca	tegories	
EPA (Environme	ental Protection Agency)	
CAS: 108-88-3	Toluene	
TLV (Threshold	Limit Value)	
CAS: 108-88-3	Toluene	F
CAS: 67-63-0	sopropanol	
NIOSH-Ca (Nat	ional Institute for Occupational Safety and Health)	
None of the ingre		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

2 GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Methanol

Toluene

Isopropanol

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system and the visual organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 12)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 11)

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 1.0 03/31/2023 Reviewed SDS for accuracy. STN

Creation date for SDS 11-12-2014. STN

04/04/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 13)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Sodium Acetate / Toluene Solution

(Contd. of page 12)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard - Category 1

· * Data compared to the previous version altered.

HIC