Printing date 12/10/2021

Reviewed on 12/10/2021

7 7 7		<b>(**</b>	. •
1 Id	entri	тса	10N
	energ		

- · Product identifier
- · Trade name: Nitrogen Standard 30.0 ug/ml in Toluene
- Article number: AM334
- · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

- · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number: Chemtrec: 800-424-9300
- Canutec: 613-996-6666

# **2** Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child. Repr. 2

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: Toluene

(Contd. on page 2)

US

Reviewed on 12/10/2021

# Safety Data Sheet acc. to OSHA HCS

Printing date 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene

	(Contd. of page 1)
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/show	wer.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	tions
Dispose of contents/container in accordance with local/regional/national/international regula • Classification system:	uons.
· <i>Classification system:</i> · <i>NFPA ratings (scale 0 - 4)</i>	
A TITA Tulings (scale 0 - 4)	
$\begin{array}{c} Health = 1\\ Fire = 3 \end{array}$	
Tue = 3	
1  0  Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
<b>HEALTH</b> 2 $Health = 2$	
FIRE 3 Fire = 3 $P_{\text{restrict}} = 0$	
<b>REACTIVITY</b> $0$ Reactivity = 0	

- Other hazards
- Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

(Contd. on page 3)

US

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene

(Contd. of page 2)

99.958%

0.042%

#### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-88-3 Toluene

· Table of Nonhazardous Ingredients

CAS: 86-74-8 Carbazole, 96%

#### 4 First-aid measures

· Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

# 6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

• *Reference to other sections* See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

US

Printing date 12/10/2021

Reviewed on 12/10/2021

#### Trade name: Nitrogen Standard 30.0 ug/ml in Toluene

	for disposal information.	(Contd. of page 3)
· Protective Action	on Criteria for Chemicals	
· PAC-1:		
CAS: 108-88-3	Toluene	67 ppm
CAS: 86-74-8	Carbazole, 96%	0.66 mg/m <sup>3</sup>
· PAC-2:		
CAS: 108-88-3	Toluene	560 ppm
CAS: 86-74-8	Carbazole, 96%	7.2 $mg/m^3$
· PAC-3:		
CAS: 108-88-3	Toluene	3700* ppm
CAS: 86-74-8	Carbazole, 96%	43 mg/m <sup>3</sup>

# 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

CAS:	: 108-88-3 Toluene	
PEL	Long-term value: 200 ppm	
	Ceiling limit value: 300; 500* ppm	
	*10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m³, 150 ppm	
	Long-term value: 375 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm	
	BEI, OTO, A4	
		(Contd. on pa

Printing date 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene Reviewed on 12/10/2021

(Contd. of page 4)

(Contd. on page 6)

US

	: 108-88-3 Toluene
BEI	0.02 mg/L
	LD50 Intraperitoneal: blood
	Time: prior to last shift of workweek
	LD50: Toluene
	0.03 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Toluene
	0.3 mg/g creatinine
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: o-Cresol with hydrolysis (background)
Add	<i>tional information:</i> The lists that were valid during the creation were used as basis.
-	osure controls
	onal protective equipment:
	eral protective and hygienic measures:
	o away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	e protective clothing separately.
	d contact with the skin.
	d contact with the eyes and skin.
	uthing equipment:
	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure
	iratory protective device that is independent of circulating air. <b>ection of hands:</b>
1101	ection of nanas.
<i>Vn</i> ,	Protective gloves
The	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	to missing tests no recommendation to the glove material can be given for the product the preparation/
	nical mixture.
Sele	ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	erial of gloves
	selection of the suitable gloves does not only depend on the material, but also on further marks of quality of
varie	es from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance
	vove material can not be calculated in advance and has therefore to be checked prior to the application.
	etration time of glove material
	exact break through time has to be found out by the manufacturer of the protective gloves and has to
	rved.
<b>F</b>	protection:
Eye	
Eye	

Printing date 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene

· Body protection: Protective work clothing

(Contd. of page 5)

Information on basic physical and ch	emical properties
General Information	
Appearance:	<b>7</b> · · · <b>1</b>
Form: Color:	Liquid Clear
Color: Odor:	Toluene
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	110 °C (230 °F)
Flash point:	4 °C (39.2 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	535 °C (995 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapor pressure at 20 $\cdot$ C (68 $\cdot$ F):	29 hPa (21.8 mm Hg)
Density at 20 °C (68 °F):	0.8669 g/cm <sup>3</sup> (7.23428 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 15 °C (59 °F):	0.5 g/l
Partition coefficient (n-octanol/water	): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	99.96 % 866.5 g/l / 7.23 lb/gal
Solids content:	0.0 %

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard

30.0 ug/ml in Toluene

(Contd. of page 6)

• Other information

No further relevant information available.

### **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11** Toxicological information

· Information on toxicological effects

- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Internat	tional Agency for Research on Cancer)	
CAS: 108-88-3	Toluene	3
CAS: 86-74-8	Carbazole, 96%	2B
· NTP (National	Toxicology Program)	
None of the ing	redients is listed.	

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# **12** Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

US

Printing date 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene

(Contd. of page 7)

Reviewed on 12/10/2021

•	Results	of PBT	and	vPvB	assessment
---	---------	--------	-----	------	------------

· **PBT:** Not applicable.

· vPvB: Not applicable.

• Other adverse effects No further relevant information available.

# **13 Disposal considerations**

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1993	
UN proper shipping name		
DOT	Flammable liquids, n.o.s. (Toluene)	
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Toluene)	
Transport hazard class(es)		
DOT		
PLAMABLE LODO		
3		
Class	3 Flammable liquids	
Label	3	
IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, IMDG, IATA	II	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Hazard identification number (Kemler code):		
EMS Number:	<i>F-E,<u>S-E</u></i>	
Stowage Category	В	

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene

	(Contd. of page a
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE), 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
CAS: 108-88-3 Toluene	
TSCA (Toxic Substances Control Act):	
Toluene	ACTIV
Carbazole, 96%	ACTIV
Hazardous Air Pollutants	
CAS: 108-88-3 Toluene	
Proposition 65	
Chemicals known to cause cancer:	
CAS: 86-74-8 Carbazole, 96%	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
CAS: 108-88-3 Toluene	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
CAS: 108-88-3 Toluene	
TLV (Threshold Limit Value)	
CAS: 108-88-3 Toluene	A
	(Contd. on page

Printing date 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene Reviewed on 12/10/2021

(Contd. of page 9)

# ·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: Toluene
Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

*Call a poison center/doctor if you feel unwell.* 

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 30.0 ug/ml in Toluene

(Contd. of page 10)

This information is based o	n our present knowledge. However, this shall not constitute a guarantee for
	shall not establish a legally valid contractual relationship.
• Denartment issuing SDS: En	vironment protection department.
Contact:	
Date of preparation / last rev	igion
	odated sections 1, 2 and 15 to meet Fanns new requirements
<i>Revision 1.0, 11-16-2021: Up</i>	odated product information. STN
12/10/2021 / -	
Abbreviations and acronyms	:
IMDG: International Maritime Code	
DOT: US Department of Transporta	
IATA: International Air Transport A	ssociation
	isting Commercial Chemical Substances
ELINCS: European List of Notified	Chemical Substances
CAS: Chemical Abstracts Service (d	ivision of the American Chemical Society)
NFPA: National Fire Protection Ass	
HMIS: Hazardous Materials Identifi	
VOC: Volatile Organic Compounds	
PBT: Persistent, Bioaccumulative an	
vPvB: very Persistent and very Bioa	
NIOSH: National Institute for Occup	
OSHA: Occupational Safety & Heal	th
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit BEI: Biological Exposure Limit	
Flam. Liq. 2: Flammable liquids – C	atagam ?
Skin Irrit. 2: Skin corrosion/irritatio	
<i>Repr. 2: Reproductive toxicity – Cat</i>	
	xicity (single exposure) – Category 3
STOT RE 2: Specific target organ to	