Printing date 06/02/2021 Reviewed on 06/02/2021

1 Identification

· Product identifier

· Trade name: Chloroform/Toluene/

Methanol Solution

· Article number: CHV106

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.

STOT RE 1 H372 Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

on page 2

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 1)

· Hazard pictograms







GHS02

2 GHS07

GHS0

· Signal word Danger

· Hazard-determining components of labeling:

Chloroform

Toluene

Methanol (Methyl Alcohol)

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system and the visual organs.

Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:					
CAS: 67-66-3	Chloroform	80.245%			
CAS: 67-56-1	Methanol (Methyl Alcohol)	11.922%			
CAS: 108-88-3	Toluene	7.834%			

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- $\cdot \textit{After skin contact:} \ \textit{Immediately wash with water and soap and rinse thoroughly}.$
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 3)

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:				
CAS: 67-66-3	Chloroform	2 ppm		
CAS: 67-56-1	Methanol (Methyl Alcohol)	530 ppm		
CAS: 108-88-3	Toluene	67 ppm		
· PAC-2:				
CAS: 67-66-3	Chloroform	64 ppm		
CAS: 67-56-1	Methanol (Methyl Alcohol)	2,100 ppm		
CAS: 108-88-3	Toluene	560 ppm		
· PAC-3:				
CAS: 67-66-3	Chloroform	3,200 ppm		
CAS: 67-56-1	Methanol (Methyl Alcohol)	7200* ppm		
CAS: 108-88-3	Toluene	3700* ppm		

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 5)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 4)

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with	limit values	that require	monitoring	at the workplace:
-------------------	--------------	--------------	------------	-------------------

CAS: 67-66-3 Chloroform

PEL Ceiling limit value: 240 mg/m³, 50 ppm

REL Short-term value: 9.78* mg/m³, 2* ppm

*60-min; See Pocket Guide App. A

TLV Long-term value: 49 mg/m³, 10 ppm

CAS: 67-56-1 Methanol (Methyl Alcohol)

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm

Long-term value: 260 mg/m³, 200 ppm

Skin

TLV Short-term value: 328 mg/m³, 250 ppm

Long-term value: 262 mg/m³, 200 ppm

Skin; BEI

CAS: 108-88-3 Toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

BEI, NIC-OTO

· Ingredients with biological limit values:

CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

(Contd. on page 6)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 5)

CAS: 108-88-3 Toluene

BEI 0.02 mg/L

LD50 Intraperitoneal: blood

Time: prior to last shift of workweek

LD50: Toluene

 $0.03 \, mg/L$

LD50 Intraperitoneal: urine

Time: end of shift LD50: Toluene

0.3 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

· Body protection: Protective work clothing

(Contd. of page 6)

Information on basic physical and c	chemical properties
General Information	menteut properties
Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	0 °C (32 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	210 hPa (157.5 mm Hg)
Density at 20 °C (68 °F):	1.27676 g/cm³ (10.65456 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	19.8 %
VOC content:	19.76 %
	252.2 g/l / 2.10 lb/gal
Solids content:	0.0 %

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 7)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

120000	new toxicity.				
· LD/LC50 1	· LD/LC50 values that are relevant for classification:				
ATE (Acut	ATE (Acute Toxicity Estimate)				
Oral	LD50	586-607 mg/kg			
Inhalative	LC50/4h	1,075 mg/l (rat)			
CAS: 67-6	CAS: 67-66-3 Chloroform				
Oral	LD50	500 mg/kg (ATE)			
Inhalative	LC50/4h	3 mg/l (ATE)			
CAS: 67-5	CAS: 67-56-1 Methanol (Methyl Alcohol)				
Oral	LD50	100 mg/kg (ATE)			
Dermal	<i>LD50</i>	300 mg/kg (ATE)			
Inhalative	LC50/4h	3 mg/l (ATE)			

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)					
CAS: 67-66-3	Chloroform	2B			
CAS: 108-88-3	Toluene	3			
· NTP (National Toxicology Program)					
CAS: 67-66-3	Chloroform	R			
		(Contd on mage 0)			

(Contd. on page 9)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 8)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

•	UN	-N	uml	ber
---	----	----	-----	-----

· DOT, IMDG, IATA

UN2929

· UN proper shipping name

 $\cdot DOT$

Toxic liquids, flammable, organic, n.o.s. (Chloroform, Methanol, Toluene)

· IMDG, IATA

TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S.

(CHLOROFORM, METHANOL, TOLUENE)

- · Transport hazard class(es)
- $\cdot DOT$





· Class 3 Flammable liquids

(Contd. on page 10)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

	(Contd. of page
· Label	6.1, 3
· IMDG	
· Class	3 Flammable liquids
· Label	6.1/3
· IATA	
· Class	3 Flammable liquids
· Label	6.1 (3)
· Packing group	77
· DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups 	Warning: Flammable liquids
· Stowage Category · Stowage Code	B SW2 Clear of living quarters.
	Sw2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot DOT$	
· Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	IL .
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2929 TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O. (CHLOROFORM, METHANOL, TOLUENE), 6.1 (3), II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 11)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

· Sara		(Contd. of page 10)
~	ctremely hazardous substances):	
CAS: 67-66-3	•	
	pecific toxic chemical listings):	
All ingredients	<u> </u>	
TSCA (Toxic S	ubstances Control Act):	
Chloroform		ACTIVE
Methanol (Meth	hyl Alcohol)	ACTIVE
Toluene		ACTIVE
Hazardous Air	Pollutants	
All ingredients	are listed.	
Proposition 65		
Chemicals know	wn to cause cancer:	
CAS: 67-66-3	Chloroform	
Chemicals kno	wn to cause reproductive toxicity for females:	
None of the ing	redients is listed.	
Chemicals kno	wn to cause reproductive toxicity for males:	
None of the ing	redients is listed.	
Chemicals know	wn to cause developmental toxicity:	
All ingredients	are listed.	
Carcinogenic c	atagorias	
Ü	nental Protection Agency)	
CAS: 67-66-3	Chloroform	B2, L, NL
CAS: 108-88-3		II

 • TLV (Threshold Limit Value)

 CAS: 67-66-3
 Chloroform
 A3

 CAS: 108-88-3
 Toluene
 A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 67-66-3 Chloroform

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Chloroform

Toluene

Methanol (Methyl Alcohol)

· Hazard statements

 $Highly\,flammable\;liquid\;and\;vapor.$

Harmful if swallowed.

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 11)

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system and the visual organs.

Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Creation date for SDS 10-05-2015 STN

Revision 1.0 05-07-2021: updated hazard information. STN 06/02/2021 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 13)

Printing date 06/02/2021 Reviewed on 06/02/2021

Trade name: Chloroform/Toluene/ Methanol Solution

(Contd. of page 12)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

- US