

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

1 Identification

- **Product identifier**
- **Trade name:** Mixed Indicator Solution
ASTM D 4047-13
- **Article number:** 5914
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT SE 2 H371 May cause damage to organs.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Isopropanol
Methanol (Methyl Alcohol)
- **Hazard statements**
Highly flammable liquid and vapor.
May cause damage to organs.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: Mixed Indicator Solution
ASTM D 4047-13

(Contd. of page 1)

Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Call a POISON CENTER/doctor.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	89.898%
CAS: 67-56-1	Methanol (Methyl Alcohol)	5.008%
CAS: 67-63-0	Isopropanol	4.967%

· **Table of Nonhazardous Ingredients**

CAS: 76-61-9	Thymol Blue	0.076%
CAS: 77-09-8	Phenolphthalein	0.051%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: Mixed Indicator Solution
ASTM D 4047-13

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	530 ppm
CAS: 67-63-0	Isopropanol	400 ppm
CAS: 76-61-9	Thymol Blue	30 mg/m ³
CAS: 77-09-8	Phenolphthalein	4 mg/m ³

· PAC-2:

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	2,100 ppm
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 76-61-9	Thymol Blue	330 mg/m ³
CAS: 77-09-8	Phenolphthalein	44 mg/m ³

· PAC-3:

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	7200* ppm
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 76-61-9	Thymol Blue	2,000 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: Mixed Indicator Solution
ASTM D 4047-13

CAS: 77-09-8 Phenolphthalein

(Contd. of page 3)

260 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm

CAS: 67-56-1 Methanol (Methyl Alcohol)

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm

Long-term value: 260 mg/m³, 200 ppm
 Skin

TLV Short-term value: 328 mg/m³, 250 ppm

Long-term value: 262 mg/m³, 200 ppm
 Skin; BEI

CAS: 67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm

Long-term value: 492 mg/m³, 200 ppm
 BEI

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: Mixed Indicator Solution
ASTM D 4047-13

(Contd. of page 4)

· **Ingredients with biological limit values:**

CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L
 LD50 Intraperitoneal: urine
 Time: end of shift
 LD50: Methanol (background, nonspecific)

CAS: 67-63-0 Isopropanol

BEI 40 mg/L
 LD50 Intraperitoneal: urine
 Time: end of shift at end of workweek
 LD50: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Wash hands before breaks and at the end of work.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid
Color: Dark red

· **Odor:** Alcohol

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: *Mixed Indicator Solution*
ASTM D 4047-13

(Contd. of page 5)

· Change in condition	
Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>64 °C (147 °F)</i>
· Flash point:	<i>11 °C (52 °F)</i>
· Flammability (solid, gaseous):	<i>Not applicable.</i>
· Ignition temperature:	<i>425 °C (797 °F)</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/vapor mixtures are possible.</i>
· Explosion limits:	
Lower:	<i>3.5 Vol %</i>
Upper:	<i>19.0 Vol %</i>
· Vapor pressure at 20 °C (68 °F):	<i>59 hPa (44 mm Hg)</i>
· Density at 20 °C (68 °F):	<i>0.78938 g/cm³ (6.587 lbs/gal)</i>
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Not miscible or difficult to mix.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
Organic solvents:	<i>99.9 %</i>
VOC content:	<i>99.9 %</i>
	<i>788.4 g/l / 6.58 lb/gl</i>
Solids content:	<i>0.1 %</i>
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: Mixed Indicator Solution
ASTM D 4047-13

(Contd. of page 6)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4 h	54.5 mg/l
------------	----------	-----------

CAS: 67-56-1 Methanol (Methyl Alcohol)

Oral	LD50	5628 mg/kg (rat)
Dermal	LD50	15800 mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/l (ATE)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 67-63-0	Isopropanol	3
CAS: 77-09-8	Phenolphthalein	2B

· NTP (National Toxicology Program)

CAS: 77-09-8	Phenolphthalein	R
--------------	-----------------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information:
- General notes:
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017



Trade name: *Mixed Indicator Solution*
ASTM D 4047-13

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1993
· UN proper shipping name	
· DOT	Flammable liquids, n.o.s. (Ethanol, Methanol, Isopropanol)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ETHANOL, METHANOL, Isopropanol)
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: Mixed Indicator Solution
ASTM D 4047-13

(Contd. of page 8)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ETHANOL, METHANOL, ISOPROPANOL), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 67-56-1 Methanol (Methyl Alcohol)

CAS: 67-63-0 Isopropanol

CAS: 77-09-8 Phenolphthalein

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

CAS: 77-09-8 Phenolphthalein

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

CAS: 67-56-1 Methanol (Methyl Alcohol)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

A3

CAS: 67-63-0 Isopropanol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: *Mixed Indicator Solution*
ASTM D 4047-13

(Contd. of page 9)

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
Isopropanol
Methanol (Methyl Alcohol)
- **Hazard statements**
Highly flammable liquid and vapor.
May cause damage to organs.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF exposed or concerned: Call a POISON CENTER/doctor.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
- **Date of preparation / last revision**
09-07-2017: review SDS for accuracy. STN
Creation date for SDS 01-20-2015. STN
09/07/2017 / -
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/07/2017

Reviewed on 09/07/2017

Trade name: Mixed Indicator Solution
ASTM D 4047-13

(Contd. of page 10)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
STOT SE 2: Specific target organ toxicity (single exposure) – Category 2

US