Printing date 01/10/2018 Reviewed on 01/10/2018

1 Identification

· Product identifier

· Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

· Article number: THE343

• CAS Number: 71-43-2 • EC number: 200-753-7

• Index number: 601-020-00-8

800-256-2586

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300

Canutec: 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 1 H310 Fatal in contact with skin.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

(Contd. on page 2)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 1)

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS06

GHS07

GHS0

- · Signal word Danger
- · Hazard-determining components of labeling:

Benzene

· Hazard statements

Highly flammable liquid and vapor.

Fatal in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Do NOT induce vomiting.

 ${\it If skin irritation occurs: Get medical advice/attention.}$

If eye irritation persists: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Substances

· CAS No. Description 71-43-2 Benzene

· Identification number(s) · EC number: 200-753-7

· Index number: 601-020-00-8

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 3)

- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

52 ppm

· PAC-2:

800 ppm

· PAC-3:

4000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

US

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 71-43-2 Benzene

PEL Short-term value: 15* mg/m³, 5* ppm Long-term value: 3* mg/m³, 1* ppm

*table Z-2 for exclusions in 29CFR1910.1028(d)

REL Short-term value: 1 ppm

Long-term value: 0.1 ppm See Pocket Guide App. A

TLV Short-term value: 8 mg/m³, 2.5 ppm Long-term value: 1.6 mg/m³, 0.5 ppm

Skin; BEI

· Ingredients with biological limit values:

CAS: 71-43-2 Benzene

BEI 25 ug/g creatinine

LD50 Intraperitoneal: urine Time: end of shift Parameter

LD50: S-Phenylmercapturic acid (background

500 μg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: t,t-Muconic acid (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 6)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 5)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9	Physic Physic	al and	chemical	propert	ties

· Information on basic physical and c	hemical properties				
· General Information					
· Appearance:	EL.: J				
Form: Color:	Fluid Colorless				
· Odor:	Aromatic				
· Odor threshold:	Not determined.				
	Not determined.				
· pH-value:	Not determined.				
· Change in condition					
Melting point/Melting range:	6 °C (42.8 °F)				
Boiling point/Boiling range:	80 °C (176 °F)				
· Flash point:	-11 °C (12.2 °F)				
· Flammability (solid, gaseous):	Not applicable.				
· Ignition temperature:	555 °C (1,031 °F)				
· Decomposition temperature:	Not determined.				
· Auto igniting:	Not determined.				
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.				
· Explosion limits:					
Lower:	1.2 Vol %				
Upper:	8 Vol %				
· Vapor pressure at 20 °C (68 °F):	100 hPa (75 mm Hg)				
· Density at 20 °C (68 °F):	0.874 g/cm³ (7.29353 lbs/gal)				
· Relative density	Not determined.				
· Vapor density	Not determined.				
· Evaporation rate	Not determined.				
· Solubility in / Miscibility with					
Water at 20 °C (68 °F):	0.7 g/l				
· Partition coefficient (n-octanol/water): Not determined.					

(Contd. on page 7)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 6)

· Viscosity:

Dynamic at 20 °C (68 °F): 0.66 mPas
Kinematic: Not determined.
Organic solvents: 100.0 %
VOC content: 100.00 %

100.00 % 874.0 g/l / 7.29 lb/gl

8/4.0 g/t / /.29 ti

Solids content: 0.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 v	alues the	it are re	elevant for	r classi	fication:
-------------	-----------	-----------	-------------	----------	-----------

ATE (Acute Toxicity Estimate)

 Oral
 LD50
 4,894 mg/kg (rat)

 Dermal
 LD50
 48 mg/kg (mouse)

CAS: 71-43-2 Benzene

Dermal LD50 5 mg/kg (ATE)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information: Danger through skin absorption.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

1

· NTP (National Toxicology Program)

K

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is listed.

US

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Assessment by list): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA UN1114
- · UN proper shipping name
- · DOT Benzene · IMDG, IATA BENZENE
- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· Label

(Contd. on page 9)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 8)

· IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler): 33
EMS Number: 3-03
Stowage Category B

· Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot DOT$

• Quantity limitations On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· Hazardous substance: 10 lbs, 4.54 kg

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 IL
 Code: I

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1114 BENZENE, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is listed.

· TSCA (Toxic Substances Control Act):

Benzene

- · Proposition 65
- · Chemicals known to cause cancer:

Substance is listed.

(Contd. on page 10)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 9)

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is listed.

· Chemicals known to cause developmental toxicity:

Substance is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

A, K/L

· TLV (Threshold Limit Value established by ACGIH)

A1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is listed.

- GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS06

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Benzene

· Hazard statements

Highly flammable liquid and vapor.

Fatal in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

(Contd. on page 11)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 10)

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group I (extremely dangerous).

Carcinogenic hazardous material group II (very dangerous).

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

01-10-2018: review SDS for accuracy. STN

Creation date for SDS 10-15-2015. STN

01/10/2018 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 $IATA: International\ Air\ Transport\ Association$

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

(Contd. on page 12)

Printing date 01/10/2018 Reviewed on 01/10/2018

Trade name: Sulfur 0.00 ppm w/w in

Benzene Soln, (S Source: Butyl Sulfide)

(Contd. of page 11)

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 1: Acute toxicity – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1A: Carcinogenicity - Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1