Printing date 11/29/2017 Reviewed on 11/29/2017

#### 1 Identification

· Product identifier

· Trade name: Bromine Index Number

**Titration Solvent** 

· Article number: LY001A

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300

Canutec: 613-996-6666



#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

  (Contd. on page 2)



Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number **Titration Solvent** 

(Contd. of page 1)

#### · Hazard pictograms









GHS02

GHS05 GHS07

#### · Signal word Danger

#### · Hazard-determining components of labeling:

Acetic Acid

*Dichloromethane* (*Methylene Chloride*)

Methanol (Methyl Alcohol)

**Toluene** 

Sulfuric Acid 96 - 98%

Mercuric Chloride

#### · Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

*Obtain special instructions before use.* 

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Immediately call a poison center/doctor.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

*Take off contaminated clothing and wash it before reuse.* 

Wash contaminated clothing before reuse.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 2Reactivity = 1

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous comp  | oonents:                             |         |
|-------------------|--------------------------------------|---------|
| CAS: 64-19-7      | Acetic Acid                          | 64.423% |
| CAS: 75-09-2      | Dichloromethane (Methylene Chloride) | 15.53%  |
| CAS: 67-56-1      | Methanol (Methyl Alcohol)            | 10.355% |
| CAS: 108-88-3     | Toluene                              | 8.365%  |
| CAS: 7664-93-9    | Sulfuric Acid 96 - 98%               | 0.475%  |
| CAS: 7487-94-7    | Mercuric Chloride                    | 0.156%  |
| · Table of Nonhaz | ardous Ingredients                   |         |
| CAS: 7758-02-3    | Potassium Bromide                    | 0.261%  |
| CAS: 7732-18-5    | Water                                | 0.436%  |

### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| CAS: 64-19-7   | Acetic Acid                          | <i>5 ppm</i>           |
|----------------|--------------------------------------|------------------------|
| CAS: 75-09-2   | Dichloromethane (Methylene Chloride) | 200 ppm                |
| CAS: 67-56-1   | Methanol (Methyl Alcohol)            | 530 ppm                |
| CAS: 108-88-3  | Toluene                              | 67 ppm                 |
| CAS: 7664-93-9 | Sulfuric Acid 96 - 98%               | 0.20 mg/m <sup>2</sup> |
| CAS: 7758-02-3 | Potassium Bromide                    | 9.2 mg/m³              |
| CAS: 7487-94-7 | Mercuric Chloride                    | 0.1 mg/m³              |
| PAC-2:         |                                      |                        |
| CAS: 64-19-7   | Acetic Acid                          | 35 ppm                 |
| CAS: 75-09-2   | Dichloromethane (Methylene Chloride) | 560 ppm                |
| CAS: 67-56-1   | Methanol (Methyl Alcohol)            | 2,100 ppm              |
| CAS: 108-88-3  | Toluene                              | 560 ppm                |
| CAS: 7664-93-9 | Sulfuric Acid 96 - 98%               | 8.7 mg/m <sup>3</sup>  |
| CAS: 7758-02-3 | Potassium Bromide                    | $100 \text{ mg/m}^3$   |
| CAS: 7487-94-7 | Mercuric Chloride                    | 0.14 mg/m <sup>2</sup> |
| <i>PAC-3:</i>  |                                      | ·                      |
| CAS: 64-19-7   | Acetic Acid                          | 250 ppm                |

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

|                |                                      | (Contd. of page 4) |
|----------------|--------------------------------------|--------------------|
| CAS: 75-09-2   | Dichloromethane (Methylene Chloride) | 6,900 ppm          |
| CAS: 67-56-1   | Methanol (Methyl Alcohol)            | 7200* ppm          |
| CAS: 108-88-3  |                                      | 3700* ppm          |
|                | Sulfuric Acid 96 - 98%               | 160 mg/m³          |
|                | Potassium Bromide                    | 610 mg/m³          |
| CAS: 7487-94-7 | Mercuric Chloride                    | 38 mg/m³           |

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

PEL Long-term value: 260 mg/m³, 200 ppm

· Additional information about design of technical systems: No further data; see item 7.

| Additional information about design of technical systems. 140 jurner data, see tiem 7. |
|--|
| · Control parameters   |
| · Components with limit values that require monitoring at the workplace:               |
| CAS: 64-19-7 Acetic Acid   |
| PEL Long-term value: 25 mg/m³, 10 ppm  |
| REL Short-term value: 37 mg/m³, 15 ppm<br>Long-term value: 25 mg/m³, 10 ppm            |
| TLV Short-term value: 37 mg/m³, 15 ppm<br>Long-term value: 25 mg/m³, 10 ppm            |
| CAS: 75-09-2 Dichloromethane (Methylene Chloride)                                      |
| PEL Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052             |
| REL See Pocket Guide App. A  |
| TLV Long-term value: 174 mg/m³, 50 ppm<br>BEI  |
| CAS: 67-56-1 Methanol (Methyl Alcohol)   |

(Contd. on page 6)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

| TLV She Lo Ski  CAS: 10  PEL Lo Ce *10  REL She Lo BE  CAS: 76  PEL Lo REL Lo TLV Lo *a.  CAS: 74 | hort-term value: 325 mg/m³, 250 ppm ong-term value: 260 mg/m³, 200 ppm kin hort-term value: 328 mg/m³, 250 ppm ong-term value: 262 mg/m³, 200 ppm kin; BEI  08-88-3 Toluene ong-term value: 200 ppm Ceiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm |
|---|---|
| TLV She Lo Ski  CAS: 10  PEL Lo Ce *10  REL She Lo BE  CAS: 76  PEL Lo REL Lo TLV Lo *a.  CAS: 74 | kin hort-term value: 328 mg/m³, 250 ppm ong-term value: 262 mg/m³, 200 ppm kin; BEI  08-88-3 Toluene ong-term value: 200 ppm eiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm   |
| REL She Lo BE Lo TLV Lo REL Lo TLV Lo REL Lo TLV Lo REL Lo TLV Lo *a.                             | ong-term value: 262 mg/m³, 200 ppm kin; BEI  08-88-3 Toluene ong-term value: 200 ppm Seiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm  |
| REL She Lo REL Lo REL Lo REL Lo REL Lo CAS: 76  | ong-term value: 262 mg/m³, 200 ppm kin; BEI  08-88-3 Toluene ong-term value: 200 ppm Seiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm  |
| CAS: 10 PEL Lo Ce *10 REL Sh Lo TLV Lo BE CAS: 76 PEL Lo TLV Lo *a.  CAS: 74                      | O8-88-3 Toluene  ong-term value: 200 ppm  Eviling limit value: 300; 500* ppm  10-min peak per 8-hr shift  hort-term value: 560 mg/m³, 150 ppm  ong-term value: 375 mg/m³, 100 ppm  ong-term value: 75 mg/m³, 20 ppm   |
| PEL Lo Ce *10 REL Sh Lo TLV Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a.  CAS: 74                       | ong-term value: 200 ppm<br>Ceiling limit value: 300; 500* ppm<br>10-min peak per 8-hr shift<br>hort-term value: 560 mg/m³, 150 ppm<br>ong-term value: 375 mg/m³, 100 ppm<br>ong-term value: 75 mg/m³, 20 ppm  |
| REL Sha<br>Lo<br>TLV Lo<br>BE<br>CAS: 76<br>PEL Lo<br>REL Lo<br>TLV Lo<br>*a.                     | Ceiling limit value: 300; 500* ppm  10-min peak per 8-hr shift  hort-term value: 560 mg/m³, 150 ppm  ong-term value: 375 mg/m³, 100 ppm  ong-term value: 75 mg/m³, 20 ppm  EEI  |
| REL Sh. Lo TLV Lo BE  CAS: 76  PEL Lo TLV Lo *a.  CAS: 74   | 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm EEI  |
| REL She Lo TLV Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a.  CAS: 74                                    | hort-term value: 560 mg/m³, 150 ppm<br>ong-term value: 375 mg/m³, 100 ppm<br>ong-term value: 75 mg/m³, 20 ppm<br>EEI  |
| TLV Lo BE  CAS: 76  PEL Lo REL Lo TLV Lo *a.  CAS: 74   | ong-term value: 375 mg/m³, 100 ppm<br>ong-term value: 75 mg/m³, 20 ppm<br>EI  |
| TLV Lo BE  CAS: 76  PEL Lo REL Lo TLV Lo *a.  CAS: 74   | ong-term value: 75 mg/m³, 20 ppm<br>EI  |
| CAS: 76 PEL Lo REL Lo TLV Lo *a.  CAS: 74   | PEI   |
| CAS: 76 PEL Lo REL Lo TLV Lo *a.  CAS: 74   |   |
| PEL Lo REL Lo TLV Lo *a.  CAS: 74   | 7664-93-9 Sulfuric Acid 96 - 98%  |
| REL Lo TLV Lo *a.  CAS: 74  | ·   |
| TLV Lo.<br>*a.<br>CAS: 74   | ong-term value: 1 mg/m³   |
| *a.  CAS: 74  | ong-term value: 1 mg/m³   |
| CAS: 74   | ong-term value: 0.2* mg/m³  |
|   | as thoracic fraction  |
| PFI Lo  | 1487-94-7 Mercuric Chloride   |
|   | ong-term value: 0.1 mg/m³   |
| as  | s Hg; see OSHA standard interpretation memo   |
|   | ong-term value: 0.05* mg/m³   |
|   | Ceiling limit value: 0.1 mg/m³  |
| as  | s Hg; *Vapor; Skin  |
| TLV Lo  | ong-term value: 0.025 mg/m³   |
| as  | s Hg; Skin; BEI   |
| · Ingredie  | ients with biological limit values:   |
| CAS: 75   | 75-09-2 Dichloromethane (Methylene Chloride)  |
| BEI 0.3   | 3 mg/L  |
| LD  | D50 Intraperitoneal: urine  |
|   | ime: end of shift   |
|   | D50: Dichloromethane (semi-quantitative)  |
|   | 7-56-1 Methanol (Methyl Alcohol)  |
| BEI 15  |   |
|   | D50 Intraperitoneal: urine  |
|   | ime: end of shift   |
| LD  | D50: Methanol (background, nonspecific)   |

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 6)

#### CAS: 108-88-3 Toluene

#### BEI 0.02 mg/L

LD50 Intraperitoneal: blood

*Time: prior to last shift of workweek* 

LD50: Toluene

 $0.03 \, mg/L$ 

LD50 Intraperitoneal: urine

Time: end of shift LD50: Toluene

0.3 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: o-Cresol with hydrolysis (background)

#### CAS: 7487-94-7 Mercuric Chloride

#### BEI 35 μg/L

LD50 Intraperitoneal: urine

Time: prior to shift

LD50: Total inorganic mercury (background)

15 µg/L

LD50 Intraperitoneal: blood

Time: end of shift at end of workweek

LD50: Total inorganic mercury (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

 ${\it Keep \ away \ from \ foodstuffs, \ beverages \ and \ feed.}$ 

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 7)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Dynamic:



Tightly sealed goggles

· Body protection: Protective work clothing

| Information on basic physical and c | hemical properties  |
|-------------------------------------|---|
| General Information                 |   |
| Appearance: Form:                   | I :! I  |
| r orm:<br>Color:                    | Liquid<br>Clear   |
| · Odor:                             | Organic   |
| Odor threshold:                     | Not determined.   |
| pH-value:                           | Not determined.   |
| Change in condition                 |   |
| Melting point/Melting range:        | Undetermined.   |
| Boiling point/Boiling range:        | 64 °C (147.2 °F)  |
| Flash point:                        | 4 °C (39.2 °F)  |
| Flammability (solid, gaseous):      | Not applicable.   |
| Ignition temperature:               | 455 °C (851 °F)   |
| Decomposition temperature:          | Not determined.   |
| Auto igniting:                      | Product is not selfigniting.  |
| Danger of explosion:                | Product is not explosive. However, formation of explosive air/vape mixtures are possible. |
| Explosion limits:                   |   |
| Lower:                              | 4 Vol %   |
| Upper:                              | 44 Vol %  |
| Vapor pressure at 20 °C (68 °F):    | 453 hPa (339.8 mm Hg)   |
| Density at 20 °C (68 °F):           | 1.03629 g/cm³ (8.64784 lbs/gal)   |
| Relative density                    | Not determined.   |
| Vapor density                       | Not determined.   |
| Evaporation rate                    | Not determined.   |
| Solubility in / Miscibility with    |   |
| Water:                              | Not miscible or difficult to mix.   |

Not determined.

(Contd. on page 9)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number **Titration Solvent** 

| (Conta. | ΟI | page | 8) |
|---------|----|------|----|
|         |    |      |    |

|                     | (Col                                       | itu. oi page o |
|---------------------|--|----------------|
| Kinematic:          | Not determined.                            |                |
| · Solvent content:  |  |                |
| Organic solvents:   | 98.7 %                                     |                |
| Water:              | 0.4 %                                      |                |
| VOC content:        | 83.14 %                                    |                |
|                     | 861.6 g/l / 7.19 lb/gl                     |                |
| Solids content:     | 0.4 %                                      |                |
| · Other information | No further relevant information available. |                |

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

| Acute toxicity:    | oxicological effects          |                          |
|--------------------|-------------------------------|--------------------------|
| LD/LC50 values     | that are relevant for classij | fication:                |
| ATE (Acute Toxi    | icity Estimate)               |                          |
| Oral               | LD50                          | >511-524 mg/kg (rat)     |
| Dermal             | LD50                          | >1,382 mg/kg             |
| Inhalative         | LC50/4 h                      | 1,238 mg/l (rat)         |
| CAS: 64-19-7 Ac    | etic Acid                     |                          |
| Oral               | LD50                          | 3,310 mg/kg (rat)        |
| Dermal             | LD50                          | 1,060 mg/kg (rabbit)     |
| CAS: 75-09-2 Di    | chloromethane (Methylene      | c Chloride)              |
| Oral               | LD50                          | 1,600 mg/kg (rat)        |
| Dermal             | LD50                          | >2,000 mg/kg (rat)       |
| Inhalative         | LC50/4 h                      | 52,000 mg/l (rat)        |
| Irritation of skin | Skin Corrosion/Irritation     | (rabbit) (Draize)        |
| Irritation of eyes | Eye damage/eye irritation     | (rabbit)                 |
| CAS: 67-56-1 M     | ethanol (Methyl Alcohol)      |                          |
| Oral               | LD50                          | >1,187-2,769 mg/kg (rat) |
| Dermal             | LD50                          | 17,100 mg/kg (rabbit)    |
| Inhalative         | LC50/4 h                      | 128.2 mg/l (rat)         |
| CAS: 108-88-3 T    | oluene                        |                          |
| Oral               | LD50                          | 5,000 mg/kg (rat)        |

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number **Titration Solvent** 

|                |                   | (Contd. of page 9)    |
|----------------|-------------------|-----------------------|
| Dermal         | LD50              | 12,124 mg/kg (rabbit) |
| Inhalative     | LC50/4 h          | 5,320 mg/l (mouse)    |
| CAS: 7487-94-7 | Mercuric Chloride |                       |
| Oral           | LD50              | 1 mg/kg (rat)         |
| Dermal         | LD50              | 41 mg/kg (rat)        |

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

| · IARC (Internat | tional Agency for Research on Cancer)      |    |
|------------------|--|----|
| CAS: 75-09-2     | Dichloromethane (Methylene Chloride)       | 2A |
| CAS: 108-88-3    | Toluene                                    | 3  |
| CAS: 7664-93-9   | 9 Sulfuric Acid 96 - 98%                   | 1  |
| CAS: 7487-94-7   | 7 Mercuric Chloride                        | 3  |
| · NTP (National  | Toxicology Program)                        |    |
| CAS: 75-09-2     | Dichloromethane (Methylene Chloride)       | R  |
| CAS: 7664-93-9   | 9 Sulfuric Acid 96 - 98%                   | K  |
| · OSHA-Ca (Occ   | cupational Safety & Health Administration) |    |
| CAS: 75-09-2     | Dichloromethane (Methylene Chloride)       |    |

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 11)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 10)

 $\cdot \textit{Other adverse effects} \ \textit{No further relevant information available}.$ 

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| UN-Number                  |   |
|----------------------------|---|
| DOT, IMDG, IATA            | UN2924  |
| UN proper shipping name    |   |
| DOT                        | Flammable liquids, corrosive, n.o.s. (Acetic acid, glacial, Metha<br>Toluene) |
| IMDG, IATA                 | FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ACETIC AC                                |
| 2,122                      | GLACIAL, METHANOL, TOLUENE)   |
| Transport hazard class(es) |   |
| DOT                        |   |
| -<br>•                     |   |
| Framable Loud              |   |
| CORROSIVE                  |   |
| · Class                    | 2 Flammabla liquida   |
| · Cass<br>· Label          | 3 Flammable liquids<br>3, 8   |
| IMDG                       |   |
|                            |   |
|                            |   |
|                            |   |
| <b>V</b>                   |   |
| · Class<br>· Label         | 3 Flammable liquids<br>3/8  |
|                            | 3/0   |
| IATA                       |   |
|                            |   |
|                            |   |
| 3                          |   |
|                            | 3 Flammable liquids   |
| Class<br>Label             | 3 (8)   |

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

|  | (Contd. of page                                    |  |
|--|--|--|
| Environmental hazards:                 |  |  |
| Marine pollutant:                      | No   |  |
| Special precautions for user           | Warning: Flammable liquids                         |  |
| Danger code (Kemler):                  | 338  |  |
| EMS Number:                            | F- $E$ , $S$ - $C$                                 |  |
| Segregation groups                     | Acids  |  |
| Stowage Category                       | B  |  |
| Stowage Code                           | SW2 Clear of living quarters.                      |  |
| Transport in bulk according to Annex   | II of  |  |
| MARPOL73/78 and the IBC Code           | Not applicable.                                    |  |
| Transport/Additional information:      |  |  |
| DOT                                    |  |  |
| Quantity limitations                   | On passenger aircraft/rail: 1 L                    |  |
| 2                                      | On cargo aircraft only: 5 L                        |  |
| · IMDG                                 |  |  |
| Limited quantities (LQ)                | 1L   |  |
| Excepted quantities $(\widetilde{EQ})$ | Code: E2   |  |
| ( Z)                                   | Maximum net quantity per inner packaging: 30 ml    |  |
|  | Maximum net quantity per outer packaging: 500 ml   |  |
| UN "Model Regulation":                 | UN 2924 FLAMMABLE LIQUIDS, CORROSIVE, N.O.S. (ACET |  |
| <u> </u>                               | ACID, GLACIAL, METHANOL, TOLUENE), 3 (8), II       |  |

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

| · Section 355 (extremely hazardous substances): |                                      |
|---|--------------------------------------|
| ,   | Sulfuric Acid 96 - 98%               |
| CAS: 7487-94-7                                  | Mercuric Chloride                    |
| · Section 313 (Spe                              | ccific toxic chemical listings):     |
| CAS: 75-09-2                                    | Dichloromethane (Methylene Chloride) |
| CAS: 67-56-1                                    | Methanol (Methyl Alcohol)            |
| CAS: 108-88-3                                   | Toluene                              |
| CAS: 7664-93-9                                  | Sulfuric Acid 96 - 98%               |
| CAS: 7487-94-7                                  | Mercuric Chloride                    |
| · TSCA (Toxic Su                                | bstances Control Act):               |
| Acetic Acid                                     |                                      |
| Dichloromethane (Methylene Chloride)            |                                      |
| Methanol (Methyl Alcohol)                       |                                      |
| Toluene   |                                      |
| Sulfuric Acid 96                                | - 98%                                |
| Potassium Brom                                  | ide                                  |
| Mercuric Chloric                                | de                                   |
|   | (Contd. on page 1)                   |

(Contd. on page 13)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

Water

Proposition 65

Chemicals known to cause cancer:

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol (Methyl Alcohol)

CAS: 108-88-3 Toluene

#### · Carcinogenic categories

CAS: 7487-94-7 Mercuric Chloride

| · EPA (Environmental Protection Agency)                            |                                      |    |  |
|--|--------------------------------------|----|--|
| CAS: 75-09-2   | Dichloromethane (Methylene Chloride) | L  |  |
| CAS: 108-88-3  | Toluene                              | II |  |
| CAS: 7487-94-7   | Mercuric Chloride                    | C  |  |
| · TLV (Threshold Limit Value established by ACGIH)                 |                                      |    |  |
| CAS: 75-09-2   | Dichloromethane (Methylene Chloride) | A3 |  |
| CAS: 108-88-3  | Toluene                              | A4 |  |
| CAS: 7664-93-9   | Sulfuric Acid 96 - 98%               | A2 |  |
| CAS: 7487-94-7   | Mercuric Chloride                    | A4 |  |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) |                                      |    |  |
| CAS: 75-09-2 D   | ichloromethane (Methylene Chloride)  |    |  |

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02 GHS05

GHS07

GHS08

· Signal word Danger

#### · Hazard-determining components of labeling:

Acetic Acid

Dichloromethane (Methylene Chloride)

Methanol (Methyl Alcohol)

Toluene

Sulfuric Acid 96 - 98%

Mercuric Chloride

#### · Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause cancer.

Suspected of damaging fertility or the unborn child.

(Contd. on page 14)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number
Titration Solvent

(Contd. of page 13)

Causes damage to organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Immediately call a poison center/doctor.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

11-29-2017: review SDS for accuracy. STN

Creation date for SDS 01-08-2015. STN

11/29/2017 / -

(Contd. on page 15)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number
Titration Solvent

(Contd. of page 14)

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Carc. 1A: Carcinogenicity - Category 1A

Repr. 2: Reproductive toxicity - Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

-US