Printing date 04/04/2023 Reviewed on 04/04/2023

1 Identification

· Product identifier

· Trade name: Smoke Point Reference
Blend B, ASTM D 1322-08

· Article number: ERL178

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 1)

· Hazard-determining components of labeling:

2,2,4-Trimethylpentane (Iso-Octane)

Toluene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 2)

· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	81.868%		
CAS: 108-88-3	Toluene	18.132%		

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

. Components with limit values that require monitoring at the workpla	ts with limit values that require monitoring at the wo	rknlace
---	--	---------

CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

PEL Long-term value: 2350 mg/m³, 500 ppm

n-Octane only

TLV Long-term value: 1401 mg/m³, 300 ppm

CAS: 108-88-3 Toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

(Contd. on page 5)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 4)

· Ingredients with biological limit values:

CAS: 108-88-3 Toluene

BEI 0.02 mg/L

LD50 Intraperitoneal: blood

Time: prior to last shift of workweek

LD50: Toluene

0.03 mg/L

LD50 Intraperitoneal: urine

Time: end of shift LD50: Toluene

0.3 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

Information on basic physical and o	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Organic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	99 °C (210.2 °F)
Flash point:	-12 °C (10.4 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	410 °C (770 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
Vapor pressure at 20 °C (68 °F):	29 hPa (21.8 mm Hg)
Density at 20 °C (68 °F):	0.692 g/cm³ (5.77474 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

		(Contd. of page 6)
VOC content:	100.0 % 692.0 g/l / 5.78 lb/gl	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
CAS: 108-88-3 Toluene			
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5320 mg/l (mouse)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
CAS: 108-88-3 Toluene	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 8)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 7)

- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

7 4 7	1 A		C	7 ·
	TOTAC	nort in	TOWN	ntion
		port in	4	шили

· UN-Number · DOT, IMDG, IATA	UN1993
· UN proper shipping name	
$\cdot DOT$	Flammable liquids, n.o.s. (Octanes, Toluene)
· IMDG	FLAMMABLE LIQUID, N.O.S. (OCTANES, TOLUENE),
	MARINE POLLUTANT
\cdot IATA	FLAMMABLE LIQUID, N.O.S. (OCTANES, TOLUENE)

- · Transport hazard class(es)
- $\cdot DOT$



ClassLabel3 Flammable liquids3

· IMDG





· Class 3 Flammable liquids

(Contd. on page 9)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

	(Contd. of page		
· Label	3		
· IATA			
· Class	3 Flammable liquids		
· Label	3		
· Packing group · DOT, IMDG, IATA	II		
Environmental hazards:	Product contains environmentally hazardous substances: Octane		
· Marine pollutant:	Yes		
	Symbol (fish and tree)		
· Special precautions for user	Warning: Flammable liquids		
· Hazard identification number (Kemler code).			
· EMS Number:	<i>F-E,<u>S-E</u></i>		
Transport in bulk according to Annex II of			
MARPOL73/78 and the IBC Code	Not applicable.		
Transport/Additional information:			
· DOT			
· Quantity limitations	On passenger aircraft/rail: 5 L		
	On cargo aircraft only: 60 L		
· IMDG			
· Limited quantities (LQ)	1L		
· Excepted quantities (EQ)	Code: E2		
	Maximum net quantity per inner packaging: 30 ml		
	Maximum net quantity per outer packaging: 500 ml		
· UN ''Model Regulation'':	UN1993, Flammable liquids, n.o.s. (Octanes, Toluene		
	ENVIRONMENTALLY HAZARDOUS, 3, II		

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355	(extremely	hazardous	substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 108-88-3 Toluene

· TSCA (Toxic Substances Control Act):

2,2,4-Trimethylpentane (Iso-Octane)

Toluene

(Contd. on page 10)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 9)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

CAS: 108-88-3 Toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 108-88-3 Toluene

· Carcinogenic categories

· EPA (Environmental Protection Agency)

All components have the value II.

· TLV (Threshold Limit Value)

CAS: 108-88-3 Toluene

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHSC

- · Signal word Danger
- · Hazard-determining components of labeling:

2,2,4-Trimethylpentane (Iso-Octane)

Toluene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

(Contd. on page 11)

Printing date 04/04/2023 Reviewed on 04/04/2023

Trade name: Smoke Point Reference Blend B, ASTM D 1322-08

(Contd. of page 10)

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 1.0 03/31/2023 Reviewed SDS for accuracy. STN

Creation date for SDS 08-06-2014. STN

04/04/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 ${\it IATA: International Air Transport Association}$

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatila Organic Compounds (USA FII)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1