Printing date 11/01/2017 Reviewed on 11/01/2017

### 1 Identification

· Product identifier

· Trade name: Isooctane-Butanol

**Mix Solution** 

· Article number: DC927-277

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 1)

### · Hazard pictograms











GHS02

GHS05

GHS06

GHS07

011502 01150

· Signal word Danger

### · Hazard-determining components of labeling:

2,2,4-Trimethylpentane (Iso-Octane)

n-Butyl Alcohol

### · Hazard statements

Highly flammable liquid and vapor.

Toxic if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 3Reactivity = 0

(Contd. on page 3)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	90.205%	
CAS: 71-36-3	n-Butyl Alcohol	9.795%	

### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

JS -

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 3)

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:					
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	230 ppm			
CAS: 71-36-3	n-Butyl Alcohol	60 ppm			
· PAC-2:					
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	830 ppm			
CAS: 71-36-3	n-Butyl Alcohol	800 ppm			
· PAC-3:					
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	5000* ppm			
CAS: 71-36-3	n-Butyl Alcohol	8000** ppm			

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 4)

### · Control parameters

	· · · · · · · · · · · · · · · · · · ·				
· Com	· Components with limit values that require monitoring at the workplace:				
CAS:	CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)				
	Long-term value: 2350 mg/m³, 500 ppm				
	n-Octane only				
TLV	Long-term value: 1401 mg/m³, 300 ppm				
CAS:	71-36-3 n-Butyl Alcohol				
PEL	Long-term value: 300 mg/m³, 100 ppm				
REL	Ceiling limit value: 150 mg/m³, 50 ppm				
	Skin				

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

TLV Long-term value: 61 mg/m<sup>3</sup>, 20 ppm

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 6)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

· Body protection: Protective work clothing

(Contd. of page 5)

. Information on basic physical and	phomical properties			
· Information on basic physical and chemical properties · General Information				
· Appearance:				
Form:	Liquid			
Color:	Clear			
· Odor:	Characteristic			
· Odor threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	98 °C (208.4 °F)			
Flash point:	-12 °C (10.4 °F)			
Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	340 °C (644 °F)			
Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
Danger of explosion:	Product is not explosive. However, formation of explosive air/vaper mixtures are possible.			
· Explosion limits:				
Lower:	1.1 Vol %			
Upper:	6 Vol %			
· Vapor pressure at 20 °C (68 °F):	15 hPa (11.3 mm Hg)			
Density at 20 °C (68 °F):	0.70175 g/cm³ (5.8561 lbs/gal)			
· Relative density	Not determined.			
· Vapor density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with	Not missible on difficult to mix			
Water:	Not miscible or difficult to mix.			
Partition coefficient (n-octanol/wate	er); woi determined.			
· Viscosity:	Not determined.			
Dynamic: Kinematic:	Not determined.			
	то инстинси.			
· Solvent content:	100.0.07			
Organic solvents:	100.0 %			
VOC content:	100.00 % 701.7 g/l / 5.86 lb/gl			
	101.1 8111 0.00 10181			

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 6)

· Other information

No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	LD/LC50 values that are relevant for classification:			
ATE (Acu	ATE (Acute Toxicity Estimate)			
Oral	LD50	8,065 mg/kg (rat)		

Oral	LD50	8,065 mg/kg (rat)
Dermal	LD50	≤2,084 mg/kg
Inhalative		4.43-37.2 mg/l (rat)

### CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

		≤> 2,000 mg/kg (rat)
Inhalative	LC50/4 h	≤4->33.52 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 7)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

•	UN-	Numl	ber
---	-----	------	-----

· **DOT**, **IMDG**, **IATA** UN1993

· UN proper shipping name

· **DOT** Flammable liquids, n.o.s. (Octanes, Butanols)

· IMDG FLAMMABLE LIQUID, N.O.S. (OCTANES, BUTANOLS), MARINE

**POLLUTANT** 

· IATA FLAMMABLE LIQUID, N.O.S. (OCTANES, BUTANOLS)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· Label

· IMDG





· Class 3 Flammable liquids

(Contd. on page 9)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

	(Contd. of page
· Label	3
· IATA	
3	
· Class	3 Flammable liquids
· Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances: 2,2,
	Trimethylpentane (Iso-Octane)
· Marine pollutant:	Yes
	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	В
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
~ '	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (OCTANE
-	BUTANOLS), 3, II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 71-36-3 n-Butyl Alcohol

- · TSCA (Toxic Substances Control Act):
- 2,2,4-Trimethylpentane (Iso-Octane)

n-Butyl Alcohol

(Contd. on page 10)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 9)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (	· EPA (Environmental Protection Agency)		
CAS:	540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	II
CAS:	71-36-3	n-Butyl Alcohol	D

### · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms











011502

GHS05

GHS06

GHS07 GHS08

· **Signal word** Danger

### · Hazard-determining components of labeling:

2,2,4-Trimethylpentane (Iso-Octane)

n-Butyl Alcohol

### · Hazard statements

Highly flammable liquid and vapor.

Toxic if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 11)

Printing date 11/01/2017 Reviewed on 11/01/2017

Trade name: Isooctane-Butanol Mix Solution

(Contd. of page 10)

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

11-01-2017: review SDS for accuracy. STN

Creation date for SDS 12-23-2014. STN

11/01/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

 $Flam.\ Liq.\ 2: Flammable\ liquids-Category\ 2$ 

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1