Printing date 01/08/2018

Reviewed on 01/08/2018

Identification	
Product identifier	
Trade name: Total Acid Number	
Solution	
Article number: STA025B	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	AQUA
Aqua Solutions, Inc. 6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536	
USA	
800-256-2586	
Information department:	
Technical Coordinator Sherman Nelson sherman@aquasolutions.org	
Emergency telephone number:	
Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
Hazard(s) identification	
Classification of the substance or mixture	
GHS02 Flame	
GHS02 Fiame	
Flow Lie 2 11225 Highly flower all lists if and some on	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
GHS08 Health hazard	
Repr. 2 H361 Suspected of damaging fertility or the unborn	
STOT RE 2 H373 May cause damage to organs through prolong	
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.	•
\wedge	
GHS07	
Skin Irrit. 2 H315 Causes skin irritation.	
Eye Irrit. 2A H319 Causes serious eye irritation.	
STOT SE 3 H336 May cause drowsiness or dizziness.	
Label elements	
GHS label elements The product is classified and labeled accordi.	ng to the Globally Harmonized System (GHS)
Hazard pictograms	
$ \land \land \land \land $	
GHS02 GHS07 GHS08	
Signal word Danger	

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number Solution

	(Contd. of page 1)
Hazard-determining components of labeling:	
Toluene	
Isopropanol	
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present a	nd easy to do.
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
Take off contaminated clothing and wash it before reuse.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = 3	
$\frac{2}{0} Reactivity = 0$	
HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 3 Fire = 3	
REACTIVITY \bigcirc Reactivity = 0	

(Contd. on page 3)

US

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number

Solution

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous com	ponents:	
CAS: 108-88-3	Toluene	52.102%
CAS: 67-63-0	Isopropanol	46.92%
· Table of Nonha	zardous Ingredients	
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	0.352%
CAS: 67-56-1	Methanol (Methyl Alcohol)	0.0196%
CAS: 77-09-8	Phenolphthalein	0.005%
CAS: 1310-58-3	Potassium Hydroxide	0.0002%
CAS: 7732-18-5	Water	0.6011%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

· Information for doctor:

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number

Solution

(Contd. of page 3)

. Personal precau	tions, protective equipment and emergency procedures	
	equipment. Keep unprotected persons away.	
• Environmental p		
Dilute with plent		
	enter sewers/ surface or ground water.	
	t terial for containment and cleaning up: id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
	nated material as waste according to item 13.	
Ensure adequate		
· Reference to oth		
	information on safe handling.	
	information on personal protection equipment. or disposal information.	
	a Criteria for Chemicals	
• PAC-1:		
CAS: 108-88-3	Toluene	67 ppm
CAS: 67-63-0	Isopropanol	400 ppm
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	530 ppm
CAS: 77-09-8	Phenolphthalein	4 mg/m ³
CAS: 1310-58-3	Potassium Hydroxide	0.18 mg/m
• PAC-2:		
CAS: 108-88-3	Toluene	560 ppm
CAS: 67-63-0	Isopropanol	2000* ppn
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppn
CAS: 67-56-1	Methanol (Methyl Alcohol)	2,100 ppm
CAS: 77-09-8	Phenolphthalein	44 mg/m ³
CAS: 1310-58-3	Potassium Hydroxide	$2 mg/m^3$
• PAC-3:		
CAS: 108-88-3	Toluene	3700* ppm
CAS: 67-63-0	Isopropanol	12000** ppn
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	7200* ppm
CAS: 77-09-8	Phenolphthalein	260 mg/m ³
CAS: 1310-58-3	Potassium Hydroxide	54 mg/m^3

7 Handling and storage

· Handling:

• Precautions for safe handling No special precautions are necessary if used correctly.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 5)

US

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number Solution

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- *Specific end use(s)* No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

Com	ponents with limit values that require monitoring at the workplace:
CAS	: 108-88-3 Toluene
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV	Long-term value: 75 mg/m³, 20 ppm BEI
CAS	: 67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI
Ingr	edients with biological limit values:
CAS	: 108-88-3 Toluene
	0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene
	0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene
	0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background)
	(Contd. on pag

US –

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number

Solution

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physic	cal and chemical properties	
• General Information		
Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Organic	
• Odor threshold:	Not determined.	

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number Solution

	(Contd. of page 6
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C (179.6 °F)
· Flash point:	4 °C (39.2 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	12 Vol %
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
• Density at 20 °C (68 °F):	0.82841 g/cm ³ (6.91308 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.4 %
Water:	0.6 %
VOC content:	99.39 %
	823.4 g/l / 6.87 lb/gl
Solids content:	0.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 8)

US

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number Solution

(Contd. of page 7)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

 Oral
 LD50
 9,597 mg/kg (rat)

Inhalative LC50/4 h 63.9 mg/l (rat)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Internat	tional Agency for Research on Cancer)	
CAS: 108-88-3	Toluene	3
CAS: 67-63-0	Isopropanol	3
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 77-09-8	Phenolphthalein	2B
· NTP (National	Toxicology Program)	
CAS: 77-09-8	Phenolphthalein	R
· OSHA-Ca (Occ	cupational Safety & Health Administration)	
None of the ing	redients is listed.	

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

(Contd. on page 9)

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number Solution

(Contd. of page 8)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*
- Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG, IATA	Flammable liquids, n.o.s. (Toluene, Isopropanol) FLAMMABLE LIQUID, N.O.S. (TOLUENE, Isopropanol)
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
Class Label	3 Flammable liquids 3
	5
Packing group DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	В
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	II of Not applicable.

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number Solution

	(Contd. of page 9)
· Transport/Additional information:	
• DOT • Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (TOLUENE, ISOPROPANOL), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

None of the ing	edients is listed.	
	ecific toxic chemical listings):	
CAS: 108-88-3		
CAS: 67-63-0	Isopropanol	
CAS: 67-56-1	Methanol (Methyl Alcohol)	
CAS: 77-09-8	Phenolphthalein	
TSCA (Toxic Si	bstances Control Act):	
Toluene		
Isopropanol		
Ethyl Alcohol, A	bsolute 200 Proof	
Methanol (Meth	yl Alcohol)	
Phenolphthaleir		
Potassium Hydr	oxide	
Water		
	Century Act) (Substances not listed)	
Proposition 65		
	n to cause cancer:	
CAS: 77-09-8 Phenolphthalein		
	n to cause reproductive toxicity for females:	
None of the ing	edients is listed.	
Chemicals know	on to cause reproductive toxicity for males:	
None of the ing	edients is listed.	
Chemicals know	n to cause developmental toxicity:	
CAS: 108-88-3	Toluene	
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	
		(Contd. on pag

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number

Solution

CAS: 67-56-1	Methanol (Methyl Alcohol)	(Contd. of page
Carcinogenic c	-	
	nental Protection Agency)	
CAS: 108-88-3	Toluene	1
TLV (Threshol	d Limit Value established by ACGIH)	
CAS: 108-88-3	Toluene	A
CAS: 67-63-0	Isopropanol	A
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	A
NIOSH-Ca (Na	tional Institute for Occupational Safety and Health)	I
None of the ing	redients is listed.	
GHS02 GH	507 GHS08	
Signal word Da	nger	
0		
Hazara-aeterm Toluene	ining components of labeling:	
Isopropanol		
Hazard stateme	nts	
	ole liquid and vapor.	
Causes skin irri	tation.	
Causes serious		
	maging fertility or the unborn child.	
-	vsiness or dizziness.	
	age to organs through prolonged or repeated exposure.	
	swallowed and enters airways.	
Precautionary	statements instructions before use.	
	instructions before use. Intil all safety precautions have been read and understood.	
	<i>i heat/sparks/open flames/hot surfaces No smoking.</i>	
	ontainer and receiving equipment.	
	proof electrical/ventilating/lighting/equipment.	
Use only non-sp	parking tools.	
	nary measures against static discharge.	
	dust/fume/gas/mist/vapors/spray.	
	ly after handling.	
	ors or in a well-ventilated area.	
	gloves/protective clothing/eye protection/face protection. nmediately call a poison center/doctor.	
	imediately can a poison center/aocior. iir): Take off immediately all contaminated clothing. Rinse skin with water/s.	hower
	Remove person to fresh air and keep comfortable for breathing.	nower.
	e cautiously with water for several minutes. Remove contact lenses, if p.	resent and easy to
Continue rinsin		
	oncerned: Get medical advice/attention.	
Call a poison co	enter/doctor if you feel unwell.	
		(Contd. on page

Printing date 01/08/2018

Reviewed on 01/08/2018

Trade name: Total Acid Number Solution

(Contd. of page 11)

Get medical advice/attention if you feel unwell. Specific treatment (see on this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

• Date of preparation / last revision 01-08-2018: review SDS for accuracy. STN Creation date for SDS 01-30-2015. STN 01/08/2018 / -

• Abbreviations and acronyms: ADR: Accord européen sur le transport des m

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

US -