Printing date 12/08/2017

Reviewed on 12/08/2017

nting date 12/08/2017	
Identification	
Product identifier	
Trade name: <u>Nitrogen Standard</u> 30.0 ppm w/v in Toluene	
Article number: MOT128A	
Details of the supplier of the safety data sheet Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	AQUA SOLUTIONS
Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	
Hazard(s) identification	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
\mathbf{v}	hild
<i>Repr.</i> 2 H361 Suspected of damaging fertility or the unborn of	
Repr. 2H361 Suspected of damaging fertility or the unborn ofSTOT RE 2H373 May cause damage to organs through prolonge	
STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.	
STOT RE 2 H373 May cause damage to organs through prolonge	
STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irrit. 2 H315 Causes skin irritation.	
 STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. 	
STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irrit. 2 H315 Causes skin irritation.	d or repeated exposure.
 STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled according Hazard pictograms 	d or repeated exposure.
STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled according	d or repeated exposure.
 STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled according Hazard pictograms 	d or repeated exposure.
STOT RE 2 H373 May cause damage to organs through prolonge Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled according Hazard pictograms GHS02 GHS07 GHS08	d or repeated exposure.

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard 30.0 ppm w/v in Toluene

	(Contd. of page 1)
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
<i>IF INHALED: Remove person to fresh air and keep comfortable for breathing.</i>	
<i>IF exposed or concerned: Get medical advice/attention.</i>	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If skin irritation occurs: Get medical advice/attention.	
Take off contaminated clothing and wash it before reuse.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations	s
Classification system:	•
NFPA ratings (scale 0 - 4)	
Health = 1	
$\frac{1}{3}$ Fire = 3	
1 0 Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
$\begin{array}{c c} \text{HEALTH} & 2 \\ \hline \end{array} \\ Health = 2 \\ \hline \end{array}$	
FIRE 3 $Fire = 3$	
REACTIVITY 0 <i>Reactivity</i> = 0	
Other hazanda	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	

(Contd. on page 3)

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard

30.0 ppm w/v in Toluene

(Contd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-88-3 Toluene

· Table of Nonhazardous Ingredients

CAS: 110-86-1 Pyridine

99.981%

0.0195%

4 First-aid measures

· Description of first aid measures

- General information:
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- **Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 4)

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard 30.0 ppm w/v in Toluene

· Protective Action Criteria for Chemicals	(Contd. of page 3)
• PAC-1:	
CAS: 108-88-3 Toluene	67 ppm
CAS: 110-86-1 Pyridine	3 ppm
· PAC-2:	
CAS: 108-88-3 Toluene	560 ppm
CAS: 110-86-1 Pyridine	19 ppm
· PAC-3:	
CAS: 108-88-3 Toluene	3700* ppm
CAS: 110-86-1 Pyridine	3600* ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:		
CAS: 108-88-3 Toluene		
	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV	Long-term value: 75 mg/m³, 20 ppm BEI	
	(Contd. on page 5)	

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard 30.0 ppm w/v in Toluene

(Contd. of page 4)

CAS	S: 108-88-3 Toluene
BEI	0.02 mg/L
	LD50 Intraperitoneal: blood
	Time: prior to last shift of workweek
	LD50: Toluene
	0.03 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Toluene
	0.3 mg/g creatinine
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: o-Cresol with hydrolysis (background)
Add	itional information: The lists that were valid during the creation were used as basis.
	osure controls
	conal protective equipment:
	eral protective and hygienic measures:
	p away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work. e protective clothing separately.
	id contact with the skin.
	id contact with the eyes and skin.
	athing equipment:
	ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure us
	iratory protective device that is independent of circulating air.
	ection of hands:
111	Protective gloves
The	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ th
	nical mixture.
	ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	erial of gloves
	selection of the suitable gloves does not only depend on the material, but also on further marks of quality an
	es from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance
	glove material can not be calculated in advance and has therefore to be checked prior to the application.
	etration time of glove material
The	exact break through time has to be found out by the manufacturer of the protective gloves and has to l
obse	erved.
Eye	protection:
_	
	Tightly sealed goggles



(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard 30.0 ppm w/v in Toluene

· Body protection: Protective work clothing

9 Physical and chemical properties		
Information on basic physical and chemical properties General Information		
· Appearance: Form:	Liquid	
Color:	Clear	
· Odor:	Odorless	
• Odor threshold:	Not determined.	
· pH-value:	Not determined.	
• Change in condition Melting point/Melting range:	-95 °C (-139 °F)	
Boiling point/Boiling range:	110 °C (230 °F)	
· Flash point:	4 °C (39.2 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	535 °C (995 °F)	
• Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7 Vol %	
· Vapor pressure at 20 °C (68 °F):	29 hPa (21.8 mm Hg)	
• Density at 20 °C (68 °F):	0.86685 g/cm ³ (7.23386 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
 Solubility in / Miscibility with Water at 15 °C (59 °F): 	0.5 g/l	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	99.98 %	
	866.7 g/l / 7.23 lb/gl	
Solids content:	0.0 %	

(Contd. on page 7)

US –

Printing date 12/08/2017

Reviewed on 12/08/2017

(Contd. of page 6)

Trade name: Nitrogen Standard

30.0 ppm w/v in Toluene

• Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 5,001 mg/kg (rat)

CAS: 108-88-3 Toluene

Oral	LD50	5,000 mg/kg (rat)
	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

• Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 108-88-3	Toluene	
CAS: 110-86-1	Pyridine	
· NTP (National Toxicology Program)		

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 8)

3 3

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard 30.0 ppm w/v in Toluene

(Contd. of page 7)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- \cdot Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1993	
UN proper shipping name		
DOT	Flammable liquids, n.o.s. (Toluene)	
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (TOLUENE)	
Transport hazard class(es)		
DOT		
TAMBAGE LOUD		
Class	3 Flammable liquids 3	
Label	3	
IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, IMDG, IATA	II	

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard

30.0 ppm w/v in Toluene

	(Contd. of page
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F- E , S - E
· Stowage Category	B
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
• Quantity limitations	On passenger aircraft/rail: 5 L
~ '	On cargo aircraft only: 60 L
· IMDG	
\cdot Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (TOLUENE), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

• TSCA (Toxic Substances Control Act):

Toluene

Pyridine

· Proposition 65

· Chemicals known to cause cancer:

CAS: 110-86-1 Pyridine

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 108-88-3 Toluene

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 108-88-3 Toluene

(Contd. on page 10)

US

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard

30.0 ppm w/v in Toluene

(Contd. of page 9)

A4

AЗ

CAS: 108-88-3 Toluene

CAS: 110-86-1 Pyridine

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: Toluene · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Specific treatment (see on this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 11)

US

Printing date 12/08/2017

Reviewed on 12/08/2017

Trade name: Nitrogen Standard

30.0 ppm w/v in Toluene

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision 12-08-2017: review SDS for accuracy. STN Creation date for SDS 02-06-2015. STN 12/08/2017 / -· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1