

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

1 Identification

- **Product identifier**
- **Trade name:** Methanol (Low Acetone) HPLC Grade
- **Article number:** M-557
- **CAS Number:**
67-56-1
- **EC number:**
200-659-6
- **Index number:**
603-001-00-X
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

STOT SE 1 H370 Causes damage to organs.

- **Label elements**

- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: **Methanol (Low Acetone) HPLC Grade**

(Contd. of page 1)

· **Hazard pictograms**· **Signal word** *Danger*· **Hazard statements***Highly flammable liquid and vapor.**Toxic if swallowed, in contact with skin or if inhaled.**Causes damage to organs.*· **Precautionary statements***Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wash thoroughly after handling.**Do not eat, drink or smoke when using this product.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Immediately call a poison center/doctor.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**Call a poison center/doctor if you feel unwell.**Specific treatment (see on this label).**Rinse mouth.**Take off immediately all contaminated clothing and wash it before reuse.**In case of fire: Use for extinction: CO₂, powder or water spray.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Classification system:**· **NFPA ratings (scale 0 - 4)***Health = 1**Fire = 3**Reactivity = 0*· **HMIS-ratings (scale 0 - 4)***Health = 3**Fire = 3**Reactivity = 0*· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: Methanol (Low Acetone) HPLC Grade

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
67-56-1 Methanol (Methyl Alcohol)
- **Identification number(s)**
- **EC number:** 200-659-6
- **Index number:** 603-001-00-X

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Remove breathing apparatus only after contaminated clothing have been completely removed.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
Most important symptoms and effects, both acute and delayed No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: Methanol (Low Acetone) HPLC Grade

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:** 530 ppm

· **PAC-2:** 2,100 ppm

· **PAC-3:** 7200* ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 67-56-1 Methanol (Methyl Alcohol)

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm

Long-term value: 260 mg/m³, 200 ppm

Skin

TLV Short-term value: 328 mg/m³, 250 ppm

Long-term value: 262 mg/m³, 200 ppm

Skin; BEI

· **Ingredients with biological limit values:**

CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: **Methanol (Low Acetone) HPLC Grade**

(Contd. of page 4)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid

Color: Colorless

· **Odor:** Alcohol-like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: -97.8 °C (-144 °F)

Boiling point/Boiling range: 64.4 °C (147.9 °F)

· **Flash point:** 11 °C (51.8 °F)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: **Methanol (Low Acetone) HPLC Grade**

(Contd. of page 5)

· Ignition temperature:	455 °C (851 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
· Density at 20 °C (68 °F):	0.7915 g/cm ³ (6.60507 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: Methanol (Low Acetone) HPLC Grade

(Contd. of page 6)

- **Additional toxicological information:**
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)** Substance is not listed.
- **NTP (National Toxicology Program)** Substance is not listed.
- **OSHA-Ca (Occupational Safety & Health Administration)** Substance is not listed.


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Assessment by list): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|---------------------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1230 |
| · UN proper shipping name | |
| · DOT | Methanol |
| · IMDG, IATA | METHANOL |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: Methanol (Low Acetone) HPLC Grade

(Contd. of page 7)

· **Label** 3· **IMDG, IATA**· **Class** 3 Flammable liquids· **Label** 3· **Packing group**· **DOT, IMDG, IATA** II· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user** Warning: Flammable liquids· **Danger code (Kemler):** 336· **EMS Number:** F-E,S-D· **Stowage Category** B· **Stowage Code** SW2 Clear of living quarters.· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.· **Transport/Additional information:**· **DOT**· **Quantity limitations** On passenger aircraft/rail: 1 L

On cargo aircraft only: 60 L

· **Hazardous substance:** 5000 lbs, 2270 kg· **IMDG**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1230 METHANOL, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):** Substance is not listed.· **Section 313 (Specific toxic chemical listings):** Substance is listed.· **TSCA (Toxic Substances Control Act):**

Methanol (Methyl Alcohol)

· **Proposition 65**· **Chemicals known to cause cancer:** Substance is not listed.· **Chemicals known to cause reproductive toxicity for females:** Substance is not listed.· **Chemicals known to cause reproductive toxicity for males:** Substance is not listed.· **Chemicals known to cause developmental toxicity:** Substance is listed.· **Carcinogenic categories**· **EPA (Environmental Protection Agency)** Substance is not listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: **Methanol (Low Acetone) HPLC Grade**

(Contd. of page 8)

- **TLV (Threshold Limit Value established by ACGIH)** Substance is not listed.
- **NIOSH-Ca (National Institute for Occupational Safety and Health)** Substance is not listed.
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS06 GHS08

- **Signal word** *Danger*
- **Hazard statements**
Highly flammable liquid and vapor.
Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to organs.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Rinse mouth.
Take off immediately all contaminated clothing and wash it before reuse.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
- **Date of preparation / last revision**
Revision 0.0, 11-03-2016: creation date for SDS. STN
12-04-2017: review SDS for accuracy. STN
12/04/2017 / -
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/04/2017

Reviewed on 12/04/2017

Trade name: Methanol (Low Acetone) HPLC Grade

(Contd. of page 9)

DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 3: Acute toxicity – Category 3
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

US