Printing date 03/03/2022 Reviewed on 03/03/2022

1 Identification

· Product identifier

· Trade name: Ethyl Alcohol

Denatured, Gov 2-B

· Article number: E2540

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.

Carcinogenicity 1A H350 May cause cancer.

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Benzene

· Hazard statements

Highly flammable liquid and vapor.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

(Contd. on page 2)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 1)

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



 *0 Health = *0

Fire = 3

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	98.892%
CAS: 71-43-2	Benzene	0.558%
CAS: 108-88-3	Toluene	0.55%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

	<u> </u>	
· PAC-1:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 71-43-2	Benzene	52 ppm
CAS: 108-88-3	Toluene	67 ppm
· PAC-2:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 71-43-2	Benzene	800 ppm
CAS: 108-88-3	Toluene	560 ppm
· PAC-3:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 71-43-2	Benzene	4000* ppm
CAS: 108-88-3	Toluene	3700* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 3)

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Com	· Components with limit values that require monitoring at the workplace:	
CAS.	: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	
DEL	1 1 1000 / 3 1000	

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1000 ppm A3

CAS: 71-43-2 Benzene

PEL Short-term value: 15* mg/m³, 5* ppm Long-term value: 3* mg/m³, 1* ppm

*table Z-2 for exclusions in 29CFR1910.1028(d)

REL Short-term value: 1 ppm Long-term value: 0.1 ppm

See Pocket Guide App. A

TLV Short-term value: 2.5 ppm Long-term value: 0.5 ppm

Skin; BEI, A1

CAS: 108-88-3 Toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

BEI, OTO, A4

(Contd. on page 5)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 4)

· Ingredients with biological limit values:

CAS: 71-43-2 Benzene

BEI 25 μg/g creatinine

LD50 Intraperitoneal: urine Time: end of shift Parameter

LD50: S-Phenylmercapturic acid (background

500 μg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: t,t-Muconic acid (background)

CAS: 108-88-3 Toluene

BEI 0.02 mg/L

LD50 Intraperitoneal: blood

Time: prior to last shift of workweek

LD50: Toluene

 $0.03 \, mg/L$

LD50 Intraperitoneal: urine

Time: end of shift LD50: Toluene

0.3 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

 Information on basic physical and chemical properties General Information Appearance: 			
Color:	Clear		
Odor:	Alcohol		
Odor threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/Melting range:	-114 °C (-173.2 °F)		
Boiling point/Boiling range:	78 °C (172.4 °F)		
Flash point:	13 °C (55.4 °F)		
Flammability (solid, gaseous):	Not applicable.		
Ignition temperature:	425 °C (797 °F)		
Decomposition temperature:	Not determined.		
Auto igniting:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.		
Explosion limits:			
Lower:	3.5 Vol %		
Upper:	19 Vol %		
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)		
Density at 20 °C (68 °F):	0.78807 g/cm³ (6.57644 lbs/gal)		
Relative density	Not determined.		
Vapor density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
Water at 20 °C (68 °F):	$1{,}000~g/l$		
Partition coefficient (n-octanol/water): Not determined.			
Viscosity:			
Dynamic:	Not determined.		

(Contd. on page 7)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

		(Contd. of page 6
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	788.1 g/l / 6.58 lb/gal	
Solids content:	98.9 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:	
ATE (Acute Toxicity Estimate)	

Dermal LD50 8,598 mg/kg (mouse)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: The product can cause inheritable damage.

· Carcinogenic categories

	0	
· IARC (Internat	tional Agency for Research on Cancer)	
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 71-43-2	Benzene	1
CAS: 108-88-3	Toluene	3
· NTP (National	Toxicology Program)	
CAS: 71-43-2	Benzene	K
· OSHA-Ca (Occ	cupational Safety & Health Administration)	
CAS: 71-43-2 Benzene		

-US

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

	UN-	Num	ber
--	-----	-----	-----

· **DOT**, **IMDG**, **IATA** UN1992

· UN proper shipping name

· DOT Flammable liquids, toxic, n.o.s. (Ethanol, Benzene)

· IMDG, IATA FLAMMABLE LIQUID, TOXIC, N.O.S. (Ethanol, Benzene)

- · Transport hazard class(es)
- $\cdot DOT$





· Class 3 Flammable liquids

· Label 3, 6.1

(Contd. on page 9)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 8) · IMDG · Class 3 Flammable liquids · Label 3/6.1 \cdot IATA · Class 3 Flammable liquids · Label 3 (6.1) · Packing group · DOT, IMDG, IATA II· Environmental hazards: Not applicable. Warning: Flammable liquids · Special precautions for user · Hazard identification number (Kemler code): 33 F-E,S-D· EMS Number: · Stowage Category В SW2 Clear of living quarters. · Stowage Code · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 1LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHANOL, BENZENE), 3 (6.1), II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 71-43-2 Benzene

(Contd. on page 10)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

CAS: 108-88-3 Toluene	(Contd. of page
· TSCA (Toxic Substances Control Act):	
Ethyl Alcohol, Absolute 200 Proof	ACTIVE
Benzene	ACTIVI
Toluene	ACTIVI
· Hazardous Air Pollutants	
CAS: 71-43-2 Benzene	
CAS: 108-88-3 Toluene	
· Proposition 65	
· Chemicals known to cause cancer:	
CAS: 71-43-2 Benzene	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
CAS: 71-43-2 Benzene	
Chemicals known to cause developmental toxicity:	
All ingredients are listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
CAS: 71-43-2 Benzene	A, K/.
CAS: 108-88-3 Toluene	II
TLV (Threshold Limit Value)	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	A
CAS: 71-43-2 Benzene	A

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms

CAS: 108-88-3 Toluene

CAS: 71-43-2 Benzene





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Benzene

· Hazard statements

Highly flammable liquid and vapor.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

· Precautionary statements

Obtain special instructions before use.

(Contd. on page 11)

A4

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol

Denatured, Gov 2-B

(Contd. of page 10)

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Creation date for SDS 07-28-2016. STN

03/03/2022 / 1.0

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 ${\it IATA: International\ Air\ Transport\ Association}$

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B

Carcinogenicity 1A: Carcinogenicity - Category 1A

Toxic to Reproduction 2: Reproductive toxicity – Category 2

* Data compared to the previous version altered.

US