Printing date 05/12/2021

Reviewed on 05/12/2021

1 Identification

- · Product identifier
- · Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)
- · Article number: 0395
- · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225

DEER PARK, TX 77536 USA 800-256-2586

- · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number:
- Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eve Dam. 1 H318 Causes serious eye damage.

· Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger · Hazard statements Flammable liquid and vapor. Causes severe skin burns and eye damage. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.



Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

(Contd. of page 1) Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 2Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 Health = 3FIRE Fire = 22 **REACTIVITY O** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64-19-7 Acetic Acid 20.		20.0%	
· Table of Nonhazardous Ingredients			
CAS: 7732-18-5	Water	70.0%	
CAS: 631-61-8	Ammonium Acetate	10.0%	

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 3)

US

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

(Contd. of page 2)

- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal preca	utions, protective equipment and emergency procedures	
	bry protective device.	
	e equipment. Keep unprotected persons away.	
· Environmental		
Dilute with plen	•	
	enter sewers/ surface or ground water.	
	aterial for containment and cleaning up:	
	uid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizin		
Dispose contam	inated material as waste according to item 13.	
Ensure adequat	e ventilation.	
· Reference to ot	her sections	
See Section 7 fo	r information on safe handling.	
See Section 8 fo	r information on personal protection equipment.	
See Section 13	for disposal information.	
· Protective Action	on Criteria for Chemicals	
· PAC-1:		
CAS: 64-19-7	Acetic Acid	5 ppm
CAS: 631-61-8	Ammonium Acetate	3.8 mg/m ³
· PAC-2:		
CAS: 64-19-7	Acetic Acid	35 ppm
CAS: 631-61-8	Ammonium Acetate	$42 mg/m^3$
· PAC-3:		
CAS: 64-19-7	Acetic Acid	250 ppm
CAS: 631-61-8	Ammonium Acetate	250 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

(Contd. of page 3)

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges. Keep respiratory protective device available.

heep respiratory protective device dvalable.

 \cdot Conditions for safe storage, including any incompatibilities

• Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

CAS: 64-19-7 Acetic Acid

PEL Long-term value: 25 mg/m³, 10 ppm

REL Short-term value: 37 mg/m³, 15 ppm

Long-term value: 25 mg/m³, 10 ppm

TLV Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

⁻ US

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid *Solution (ASTM E-200, E-394-15)*

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Strong Vinegar
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	40 °C (104 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	485 °C (905 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	4 Vol %
Upper:	17 Vol %
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	1.0176 g/cm ³ (8.49187 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

		(Contd. of page 5)
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	20.0 %	
Water:	70.0 %	
VOC content:	20.00~%	
	203.5 g/l / 1.70 lb/gal	
Solids content:	10.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 5,300 mg/kg (rabbit)

CAS: 64-19-7 Acetic Acid

Dermal LD50 1,100 mg/kg (ATE)

- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- \cdot on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

US

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
DOT, IMDG, IATA	UN3265
· UN proper shipping name	
DOT	Corrosive liquid, acidic, organic, n.o.s. (Acetic acid, glacial)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (ACETI
	ACID, GLACIAL)
Transport hazard class(es)	
DOT	
CORROSIVE 8	
· Class	8 Corrosive substances

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

	(Contd. of page
Label	8
· IMDG, IATA	
A CONTRACTOR	
8	
Class	8 Corrosive substances
· Label	8
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code)	
EMS Number:	F-E,S-C
Segregation groups	Acids
Stowage Category Stowage Code	A SW2 Clear of living quarters.
0	Sw2 Clear of living quarters.
Transport in bulk according to Annex II of	NY . 1º 11
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
	(ACETIC ACID, GLACIAL), 8, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

Section 355 (extremely hazardous substances):
 None of the ingredients is listed.
 Section 313 (Specific toxic chemical listings):
 None of the ingredients is listed.
 TSCA (Toxic Substances Control Act):
 Water
 Acetic Acid
 (Contd. on page 9)
 US

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

(Contd. of page 8) ACTIVE

D

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

Ammonium Acetate

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 631-61-8 Ammonium Acetate

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard statements

Flammable liquid and vapor.

Causes severe skin burns and eye damage.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

 $Use \ explosion-proof \ electrical/ventilating/lighting/equipment.$

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

(Contd. on page 10)

Printing date 05/12/2021

Reviewed on 05/12/2021

Trade name: Ammonium Acetate-Acetic Acid Solution (ASTM E-200, E-394-15)

(Contd. of page 9)

Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of preparation / last revision Revision 1.0, 05-22-19: updated product description. STN 05/12/2021 / 1.0

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Eye Dam. 1: Serious eye damage/eye irritation - Category 1 • * Data compared to the previous version altered.