Printing date 10/03/2017

Reviewed on 10/03/2017

		ne .	•
<u>1 Id</u>	ontit	1001	101
1 10	enn	icui	$\iota o n$

- · Product identifier
- Trade name: <u>Methanol-MTBE 50.0 ppm</u> w/w each in HPLC Hexane
- · Article number: ACB311
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536

USA 800-256-2586

- Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org
 Emergency telephone number: Chemtrec: 800-424-9300
- Canutec: 613-996-6666

2 *Hazard*(*s*) *identification*

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling: Hexane*

(Contd. on page 2)

US

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

Harand statements	(Contd. of page 1)
Hazard statements Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause arowsmess of alguness. May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower	•
<i>IF INHALED: Remove person to fresh air and keep comfortable for breathing.</i>	
IF exposed or concerned: Get medical advice/attention.	
Call a POISON CENTER/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If skin irritation occurs: Get medical advice/attention.	
Take off contaminated clothing and wash it before reuse.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	ıs.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = 3	
2 0 Reactivity = 0	
HMIS-ratings (scale 0 - 4)	

HEALTH ^{*2} Health = *2 FIRE 3 *Fire* = 3 **REACTIVITY O** Reactivity = 0

- Other hazards
- Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

(Contd. on page 3)

US

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

(Contd. of page 2)

99.98%

0.01%

0.01%

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:
-------------	-------------

CAS: 110-54-3 Hexane

• Table of Nonhazardous Ingredients

CAS: 67-56-1 Methanol (Methyl Alcohol)

CAS: 1634-04-4 Methyl Tert-Butyl Ether (MTBE)

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Do not allow product to reach sewage system or any water course.	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
Do not flush with water or aqueous cleansing agents	
· Reference to other sections	
See Section 7 for information on safe handling.	
	(Contd. on page 4)

Reviewed on 10/03/2017

Safety Data Sheet acc. to OSHA HCS

Printing date 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 110-54-3 Hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

- *REL* Long-term value: 180 mg/m³, 50 ppm
- TLV Long-term value: 176 mg/m³, 50 ppm Skin; BEI

· Ingredients with biological limit values:

CAS: 110-54-3 Hexane

BEI 0.4 mg/L

LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: 2.5-Hexanedione without hydrolysis

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 5)

(Contd. of page 3)

US

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

(Contd. of page 4)

- Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and	chemical properties
General Information Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Organic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	$> 68 \ ^{\circ}C \ (> 154 \ ^{\circ}F)$
Flash point:	-23 °C (-9 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

		(Contd. of pag
· Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7.4 Vol %	
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)	
· Density at 20 °C (68 °F):	0.68 g/cm ³ (5.675 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	0.1 g/l	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.0 %	
	680.0 g/l / 5.67 lb/gl	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Irritant
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- CAS: 1634-04-4 Methyl Tert-Butyl Ether (MTBE)

(Contd. on page 7)

3

US –

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Ecotoxical effects:
- Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, IMDG, IATA	UN1208	
· UN proper shipping name		
$\cdot DOT$	Hexanes	
· IMDG	HEXANES, MARINE POLLUTANT	
·IATA	HEXANES	

[·] Uncleaned packagings:

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

	(Contd. of pag
· Transport hazard class(es)	
·DOT	
FLAMMABLE LOUD	
3	
· Class	3 Flammable liquids
· Label	3
·IMDG	
V V	
· Class · Label	3 Flammable liquids
	3
·IATA	
3	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: Hexane
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Transport in bulk according to An	nex II of
	Not applicable.
MARPOL73/78 and the IBC Code	I I I I I I I I I I I I I I I I I I I

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

All ingredients are listed.

(Contd. on page 9)

⁻ US

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

(Contd. of page 8)

Π

A3

• TSCA (Toxic Substances Control Act): All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol (Methyl Alcohol)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 110-54-3 Hexane

· TLV (Threshold Limit Value established by ACGIH)

CAS: 1634-04-4 Methyl Tert-Butyl Ether (MTBE)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Hexane · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

(Contd. on page 10)

US

Printing date 10/03/2017

Reviewed on 10/03/2017

Trade name: Methanol-MTBE 50.0 ppm w/w each in HPLC Hexane

(Contd. of page 9)

Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Specific treatment (see on this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. . 7

· Department issuing SDS: Environment protection department.
· Contact:
· Date of preparation / last revision
10-03-2017: review SDS for accuracy. STN
Creation date for SDS 07-16-2014 LS
10/03/2017 / -
· Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1