Printing date 01/11/2018

Reviewed on 01/11/2018

I Identification	
· Product identifier	
• Trade name: <u>Benzene Standard</u> 25 ppm w/w in Methanol	
• Article number: THE362	
• Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	AQUA
• Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org • Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	
P Hazard(s) identification	
· Classification of the substance or mixture	
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS08 Health hazard	
GHS08 Health hazard	
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs.	
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs. GHS07	to the Globally Harmonized System (GH
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs. GHS07 Acute Tox. 4 H302 Harmful if swallowed. • Label elements • GHS label elements The product is classified and labeled according	to the Globally Harmonized System (GH
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs. GHS07 Acute Tox. 4 H302 Harmful if swallowed. • Label elements • GHS label elements The product is classified and labeled according	to the Globally Harmonized System (GH
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs. GHS07 Acute Tox. 4 H302 Harmful if swallowed. • Label elements • GHS label elements The product is classified and labeled according • Hazard pictograms	to the Globally Harmonized System (GH
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs. Image: GHS07 Acute Tox. 4 H302 Harmful if swallowed. • Label elements • GHS label elements • Hazard pictograms Image: GHS02 GHS07 GHS08 • Signal word Danger • Hazard-determining components of labeling: Methanol (Methyl Alcohol)	to the Globally Harmonized System (GH
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs. Image: Constraint of the state of the s	to the Globally Harmonized System (GH
GHS08 Health hazard STOT SE 1 H370 Causes damage to organs. Image: GHS07 Acute Tox. 4 H302 Harmful if swallowed. • Label elements • GHS label elements • Hazard pictograms Image: GHS02 GHS07 GHS02 GHS07 GHS08 • Signal word Danger • Hazard-determining components of labeling: Methanol (Methyl Alcohol)	to the Globally Harmonized System (GH

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard 25 ppm w/w in Methanol

	(Contd. of page 1)
Causes damage to organs.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Call a poison center/doctor if you feel unwell.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
Specific treatment (see on this label).	
Rinse mouth.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations	
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Fire = 3 Reactivity = 0 • HMIS-ratings (scale 0 - 4) HEALTH 1 Health = *1 FIRE 3 REACTIVITY 0 Reactivity = 0 • Other hazards • Results of PBT and vPvB assessment • PBT: Not applicable.	
· vPvB: Not applicable.	
**	
3 Composition/information on ingredients	
• Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	99.998%
Table of Nonhazardous Ingredients	
CAS: 71.42.2 Demonstrations	0.002501

CAS: 71-43-2 Benzene

(Contd. on page 3)

0.0025%

US

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard

25 ppm w/w in Methanol

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

• PAC-1:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	530 ppm
CAS: 71-43-2 Benzene	52 ppm
• PAC-2:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	2,100 ppm
CAS: 71-43-2 Benzene	800 ppm
• PAC-3:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	7200* ppm
	(Contd. on page 4)

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard

25 ppm w/w in Methanol

CAS: 71-43-2 Benzene

(Contd. of page 3) 4000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 67-56-1 Methanol (Methyl Alcohol)

- PEL Long-term value: 260 mg/m³, 200 ppm
- REL Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
- TLV Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI

· Ingredients with biological limit values:

CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

US ·

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard 25 ppm w/w in Methanol

(Contd. of page 4)

US

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Alcohol
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-97.8 °C (-144 °F)
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F):	0.7915 g/cm ³ (6.60507 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard 25 ppm w/w in Methanol

		(Contd. of page
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	791.5 g/l / 6.61 lb/gl	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- $\cdot \textit{Incompatible materials: } No further relevant information available.$
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 1,187-2,769 mg/kg (rat)

Inhalative LC50/4 h 128 mg/l (rat)

CAS: 67-56-1 Methanol (Methyl Alcohol)

01-101-01-0	• =	
Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

 \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

(Contd. on page 7)

US -

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard

25 ppm w/w in Methanol

(Contd. of page 6)

1

K

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 71-43-2 Benzene

· NTP (National Toxicology Program)

CAS: 71-43-2 Benzene

· OSHA-Ca (Occupational Safety & Health Administration)

CAS: 71-43-2 Benzene

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	UN1993	
UN proper shipping name		
-DOT	Flammable liquids, n.o.s. (Methanol)	
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (METHANOL)	

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard 25 ppm w/w in Methanol

	(Contd. of pag
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
3	
Class Label	3 Flammable liquids 3
	5
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	В
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
2	On cargo aircraft only: 60 L
IMDG	······································
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (METHANOL), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

US

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard

25 ppm w/w in Methanol

Contd. of page 8)

Section 313 (Specific toxic chemical listings):
All ingredients are listed.

TSCA (Toxic Substances Control Act):
Methanol (Methyl Alcohol)
Benzene

Proposition 65

Chemicals known to cause cancer:
CAS: 71-43-2 Benzene

Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:
CAS: 71-43-2 Benzene

CAS: 71-43-2 Benzene

Chemicals known to cause reproductive toxicity for males:
CAS: 71-43-2 Benzene

CAS: 71-43-2 Benzene

All ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 71-43-2 Benzene

A, K/L

A1

· TLV (Threshold Limit Value established by ACGIH)

CAS: 71-43-2 Benzene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 71-43-2 Benzene

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Methanol (Methyl Alcohol) · Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Causes damage to organs. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Printing date 01/11/2018

Reviewed on 01/11/2018

Trade name: Benzene Standard

25 ppm w/w in Methanol

(Contd. of page 9)

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Specific treatment (see on this label). Rinse mouth. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

· Date of preparation / last revision

01-11-2018: review SDS for accuracy. STN Creation date for SDS 03-11-2015. STN 01/11/2018 / -

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity - Category 4 STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

US