Printing date 12/13/2017 Reviewed on 12/13/2017

1 Identification

· Product identifier

· Trade name: Chromium Etchant

· Article number: ND340

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS03 Flame over circle

Ox. Liq. 2 H272 May intensify fire; oxidizer.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS03

GHS05

11303 011303 01

- · Signal word Danger
- · Hazard-determining components of labeling:

Perchloric acid 68 - 70% w/w

· Hazard statements

May intensify fire; oxidizer.

Causes severe skin burns and eye damage.

(Contd. on page 2)

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

(Contd. of page 1)

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat.

Keep/Store away from clothing/combustible materials.

Take any precaution to avoid mixing with combustibles.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 3Reactivity = 0

The substance possesses oxidizing properties.

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous compo	onents:	
CAS: 16774-21-3	Ceric Ammonium Nitrate	8.0%
CAS: 7601-90-3	Perchloric acid 68 - 70% w/w	7.0%

· Table of Nonhazardous Ingredients

CAS: 7732-18-5 | Water

US

85.0%

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

- · · · · · · · · · · · · · · · · · · ·				
· PAC-1:				
CAS: 16774-21-3 Ceric Ammonium Nitrate	1.2 mg/m ³			
CAS: 7601-90-3 Perchloric acid 68 - 70% w/w	0.61 ppm			
· PAC-2:				
CAS: 16774-21-3 Ceric Ammonium Nitrate	13 mg/m³			
CAS: 7601-90-3 Perchloric acid 68 - 70% w/w	6.7 ppm			
· PAC-3:				
CAS: 16774-21-3 Ceric Ammonium Nitrate	79 mg/m³			
	(Contd. on page 4)			

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

CAS: 7601-90-3 | Perchloric acid 68 - 70% w/w | 40 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)


(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

· Eye protection:



· Body protection: Protective work clothing

Physical and chemical properties				
· Information on basic physical and chemical properties · General Information				
· Appearance:				
Form:	Liquid			
Color:	Orange			
· Odor:	Odorless			
· Odor threshold:	Not determined.			
· pH-value at 20 °C (68 °F):	<2			
· Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	100 °C (212 °F)			
· Flash point:	Not applicable.			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:				
Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product does not present an explosion hazard.			
Explosion limits:				
Lower:	Not determined.			
Upper:	Not determined.			
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)			
Density at 20 °C (68 °F):	$1.05288 \ g/cm^3 (8.78628 \ lbs/gal)$			
· Relative density	Not determined.			
· Vapor density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with				
Water:	Fully miscible.			
Partition coefficient (n-octanol/water): Not determined.				
· Viscosity:				
Dynamic:	Not determined.			
Kinematic:	Not determined.			
· Solvent content:				
Water:	85.0 %			
VOC content:	0.00 %			
	0.0 g/l / 0.00 lb/gl			

(Contd. on page 6)

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

(Contd. of page 5)

Solids content: 8.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

.]	LD/LC50	values	that are	relevant	for	classification:

ATE (Acute Toxicity Estimate)

Oral LD50 4,472 mg/kg

CAS: 7601-90-3 Perchloric acid 68 - 70% w/w

Oral LD50 500 mg/kg (ATE)

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 $The \ product \ shows \ the \ following \ dangers \ according \ to \ internally \ approved \ calculation \ methods \ for \ preparations:$

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 7)

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

(Contd. of page 6)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

7 4 7			C	, •
1 4 1	ranc	port in	Orma	TON
	פטוש די	וווו עוועע		uuuuu

· UN-Number	
· DOT, IMDG, IATA	UN3264

· UN proper shipping name

• DOT

Corrosive liquid, acidic, inorganic, n.o.s. (Perchloric acid, Ceric Ammonium Nitrate)
• IMDG. IATA

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

· IMDG, IATA CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (PERCHLORIC ACID, Ceric Ammonium Nitrate)

- · Transport hazard class(es)
- $\cdot DOT$



· Label 8

(Contd. on page 8)

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

rade name: Chromium Etchant	
	(Contd. of page
· IMDG	
8	
· Label	8
· IATA	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler): · EMS Number:	8 F-A,S-B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot DOT$	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L Code: E1
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per utner packaging. 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O
· ·	(PERCHLORIC ACID, CERIC AMMONIUM NITRATE), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 16774-21-3 Ceric Ammonium Nitrate

(Contd. on page 9)

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

(Contd. of page 8)

· TSCA (Toxic Substances Control Act):

Ceric Ammonium Nitrate

Perchloric acid 68 - 70% w/w

Water

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 16774-21-3 | Ceric Ammonium Nitrate

II

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS03

GHS05 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Perchloric acid 68 - 70% w/w

· Hazard statements

May intensify fire; oxidizer.

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat.

Keep/Store away from clothing/combustible materials.

Take any precaution to avoid mixing with combustibles.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

(Contd. on page 10)

Printing date 12/13/2017 Reviewed on 12/13/2017

Trade name: Chromium Etchant

(Contd. of page 9)

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label). Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- Contact:
- · Date of preparation / last revision

12-13-2017: review SDS for accuracy. STN Creation date for SDS 04-21-2014. STN 12/13/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 $HMIS: Hazardous\ Materials\ Identification\ System\ (USA)$

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Ox. Liq. 2: Oxidizing liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

- 115