Printing date 04/04/2023

*

Product identifier	
Trade name: Bromine Number Titration	
Solvent ASTM D1159, D2710	
Article number: ERL078	
Restrictions	
This chemical/product is not and cannot be disti processed (as defined in TSCA section 3(13)) for com	ributed in commerce (as defined in TSCA section 3(5)) of a section (5) of
	SOLUTIONS
Details of the supplier of the safety data sheet Manufacturer/Supplier:	SOLUTIONS
Aqua Solutions, Inc.	
6913 Highway 225	
DEER PARK, TX 77536 USA	
800-256-2586	
Information department:	
Technical Coordinator	
Sherman Nelson shermann@aquasolutions.org Emergency telephone number:	
Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
Hazard(s) identification Classification of the substance or mixture	
Classification of the substance or mixture GHS02 Flame	H225 Highly flammable liquid and vapor.
Classification of the substance or mixture GHS02 Flame	H225 Highly flammable liquid and vapor.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones	
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones	H225 Highly flammable liquid and vapor. H311 Toxic in contact with skin.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 3	
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones	
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 3	H311 Toxic in contact with skin.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 3 GHS08 Health hazard	H311 Toxic in contact with skin. H350 May cause cancer.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A Specific Target Organ Toxicity - Single Exposure 1	H311 Toxic in contact with skin. H350 May cause cancer. H370 Causes damage to the central nervous system an the visual organs.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A Specific Target Organ Toxicity - Single Exposure 1 Specific Target Organ Toxicity - Repeated Exposure	 H311 Toxic in contact with skin. H350 May cause cancer. H370 Causes damage to the central nervous system an the visual organs. 2 H373 May cause damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the system and the system and the visual damage to organs through prolonged or content of the system and th
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A Specific Target Organ Toxicity - Single Exposure 1	 H311 Toxic in contact with skin. H350 May cause cancer. H370 Causes damage to the central nervous system an the visual organs. 2 H373 May cause damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the visual damage to organs through prolonged or content of the system and the system and the system and the visual damage to organs through prolonged or content of the system and th
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A Specific Target Organ Toxicity - Single Exposure 1 Specific Target Organ Toxicity - Repeated Exposure	 H311 Toxic in contact with skin. H350 May cause cancer. H370 Causes damage to the central nervous system an the visual organs. 2 H373 May cause damage to organs through prolonged c

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 1) GHS07 Acute Toxicity - Oral 4 H302 Harmful if swallowed. Sensitization - Skin 1 H317 May cause an allergic skin reaction. · Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS08 GHS02 GHS05 GHS06 GHS07 · Signal word Danger · Hazard-determining components of labeling: Acetic Acid, Glacial Dichloromethane (Methylene Chloride) Methanol Sulfuric Acid 96 - 98% · Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. Causes damage to the central nervous system and the visual organs. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention.

(Contd. on page 3)

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

Specific treatment (see on this label).	(Contd. of page 2)
Get medical advice/attention if you feel unwell.	
Take off immediately all contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	<i>s</i> .
Classification system:	
·NFPA ratings (scale 0 - 4)	
$\begin{array}{c} \textbf{Health} = 3\\ \textbf{Fire} = 3\\ \textbf{Reactivity} = 0 \end{array}$	
· HMIS-ratings (scale 0 - 4)	
HEALTH 3 Health = 3FIRE 2 Fire = 2REACTIVITYReactivity = 1	
• Other hazards	
· Results of PBT and vPvB assessment	
• PBT: Not applicable.	
• vPvB: Not applicable.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-19-7	Acetic Acid, Glacial	71.944%
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	17.045%
CAS: 67-56-1	Methanol	10.185%
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.826%

4 First-aid measures

*

- · Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Immediately call a doctor.

(Contd. on page 4)

US

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 3)

- Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- \cdot For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

	euse meusures	
· Personal precau	tions, protective equipment and emergency procedures	
Mount respirator	y protective device.	
Wear protective e	equipment. Keep unprotected persons away.	
• Environmental p		
Do not allow pro	duct to reach sewage system or any water course.	
Inform respective	e authorities in case of seepage into water course or sewage system.	
	nter sewers/ surface or ground water.	
	terial for containment and cleaning up:	
	id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing		
	nated material as waste according to item 13.	
Ensure adequate		
• Reference to oth		
	information on safe handling.	
	information on personal protection equipment.	
	r disposal information. I Criteria for Chemicals	
	i Crueria for Chemicais	
· PAC-1:		
	Acetic Acid, Glacial	5 ppm
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	200 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	$0.20 \ mg/m^{3}$
· PAC-2:		
CAS: 64-19-7	Acetic Acid, Glacial	35 ppm
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	560 ppm
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	$8.7 mg/m^3$
· PAC-3:		
CAS: 64-19-7	Acetic Acid, Glacial	250 ppm
		(Contd. on page 5)

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

		(Contd. of page 4)
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	6,900 ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	160 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
CAS:	: 64-19-7 Acetic Acid, Glacial
PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm
TLV	Short-term value: 15 ppm Long-term value: 10 ppm
CAS:	75-09-2 Dichloromethane (Methylene Chloride)
PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 50 ppm BEI, A3
CAS:	: 67-56-1 Methanol
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
	(Contd. on page 6)

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

	(C	Contd. of page 5)
TLV	Short-term value: 250 ppm	
	Long-term value: 200 ppm	
	Skin; BEI	
CAS.	S: 7664-93-9 Sulfuric Acid 96 - 98%	
	Long-term value: 1 mg/m ³	
REL	Long-term value: 1 mg/m ³	
TLV	Long-term value: 0.2* mg/m ³	
	*as thoracic fraction, A2	
·Ingro	redients with biological limit values:	
	S: 75-09-2 Dichloromethane (Methylene Chloride)	
	0.3 mg/L	
	LD50 Intraperitoneal: urine	
	Time: end of shift	
	LD50: Dichloromethane (semi-quantitative)	
	S: 67-56-1 Methanol	
	15 mg/L	
	LD50 Intraperitoneal: urine	
	Time: end of shift	
	LD50: Methanol (background, nonspecific)	
· Addi	itional information: The lists that were valid during the creation were used as basis.	
· Expo	osure controls	
· Perse	sonal protective equipment:	
	eral protective and hygienic measures:	
	p away from foodstuffs, beverages and feed.	
	nediately remove all soiled and contaminated clothing.	
	h hands before breaks and at the end of work.	
	e protective clothing separately.	
	id contact with the eyes.	
	id contact with the eyes and skin.	
	athing equipment:	
	ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer biratory protective device that is independent of circulating air.	exposure use
	tection of hands:	
•11016	iection of nunus.	
ſ	μ μ	
1111	Protective gloves	

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

• Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Vinegar
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	118 °C (244.4 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	4 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)
Density at 20 °C (68 °F):	1.06597 g/cm ³ (8.89552 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

US –

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

	(Contd. of pag	ge 7)
 Solvent content: Organic solvents: 	99.2 %	
VOC content:	82.13 % 875.5 g/l / 7.31 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)OralLD50889 mg/kgDermalLD50982 mg/kgInhalativeLC50/4h29.5 mg/l

· Primary irritant effect:

• on the skin: Caustic effect on skin and mucous membranes.

 \cdot on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: Sensitization possible through skin contact.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	2A
CAS: 7664-93-9 Sulfuric Acid 96 - 98%		1
	(Contd. on p	(0 ane

(Contd. on page 9)

US

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 8)

R

K

· NTP (National Toxicology Program)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· OSHA-Ca (Occupational Safety & Health Administration)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

 \cdot Waste treatment methods

· Recommendation:


Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN3286
UN proper shipping name	
DOT	Flammable liquid, toxic, corrosive, n.o.s. (Methanol
	Dichloromethane, Acetic Acid, Glacial
)
IMDG, IATA	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (Methano
, ,	Dichloromethane, Acetic Acid, Glacial
)

Printing date 04/04/2023

Reviewed on 04/04/2023



	(Contd. of pag
• Transport hazard class(es)	
·DOT	
Class Label	3 Flammable liquids 3, 6.1, 8
· IMDG	
· Class	3 Flammable liquids
· Label	3/6.1/8
IATA	
· Class · Label	3 Flammable liquids 3 (6.1, 8)
Packing group	5 (01, 0)
DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
• Hazard identification number (Kemle • EMS Number:	
• EMS Number: • Stowage Category	F-E,S-C B
· Stowage Calegory	SW2 Clear of living quarters.
Segregation Code	SG5 Segregation as for class 3
	SG8 Stow "away from" class 4.1
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	x II of Not applicable.
Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
	(Contd. on page

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 10)

· UN "Model Regulation":

UN 3286 FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (METHANOL, DICHLOROMETHANE, ACETIC ACID, GLACIAL), 3 (6.1+8), II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

• Section 313 (Specific toxic chemical listings):

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 67-56-1 Methanol

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· TSCA (Toxic Substances Control Act):

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

· Hazardous Air Pollutants	
Sulfuric Acid 96 - 98%	ACTIVE
Methanol	ACTIVE
Dichloromethane (Methylene Chloride)	ACTIVE
Acetic Acid, Glacial	ACTIVE

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 67-56-1 Methanol

· Proposition 65

· Chemicals known to cause cancer:

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

· TLV (Threshold Limit Value)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 12)

- US

L

A3 A2

Printing date 04/04/2023

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 11) · Hazard pictograms GHS06 GHS07 GHS02 GHS05 GHS08 · Signal word Danger · Hazard-determining components of labeling: Acetic Acid, Glacial Dichloromethane (Methylene Chloride) Methanol Sulfuric Acid 96 - 98% · Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. Causes damage to the central nervous system and the visual organs. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 13) US

Printing date 04/04/2023

*

Reviewed on 04/04/2023

Trade name: Bromine Number Titration Solvent ASTM D1159, D2710

(Contd. of page 12)

US

Workers are not Exceptions can be	at limitation of use: allowed to be exposed to the hazardous carcinogenic materials contained in this prepara e made by the authorities in certain cases. assessment: A Chemical Safety Assessment has not been carried out.
Other informa	tion
	is based on our present knowledge. However, this shall not constitute a guarantee for eatures and shall not establish a legally valid contractual relationship.
Department issui	ng SDS: Environment protection department.
Contact:	
Date of preparati	
04/04/2023	1/2023 Reviewed SDS for accuracy. STN
Abbreviations an	
	Maritime Code for Dangerous Goods
DOT: US Department	
	ir Transport Association wentory of Existing Commercial Chemical Substances
	ist of Notified Chemical Substances
	acts Service (division of the American Chemical Society)
	Protection Association (USA)
	tterials Identification System (USA)
	ic Compounds (USA, EU)
LC50: Lethal concent	
LD50: Lethal dose, 50	ccumulative and Toxic
· · · · · ·	and very Bioaccumulative
	itute for Occupational Safety
OSHA: Occupational	
TLV: Threshold Limit	
PEL: Permissible Exp	
REL: Recommended	
BEI: Biological Expo	sure Limit · Flammable liquids – Category 2
	4: Acute toxicity – Category 4
	al 3: Acute toxicity – Category 3
	kin corrosion/irritation – Category 1B
	us eye damage/eye irritation – Category 1
	Skin sensitisation – Category 1
	Carcinogenicity – Category 1A
Specific Target Organ	Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1
	a Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2