Printing date 11/29/2017 Reviewed on 11/29/2017

1 Identification

· Product identifier

· Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

· Article number: LEI012

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300

Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Cyclohexanone 99.8% Methyl Ethyl Ketone

· Hazard statements

Flammable liquid and vapor.

Harmful if swallowed or in contact with skin.

(Contd. on page 2)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 1)

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Rinse mouth.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 2

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 108-94-1 Cyclohexanone 99.8%

73.335%

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

CAS: 78-93-3	Methyl Ethyl Ketone	(Contd. of page 2) 26.665%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 108-94-1	Cyclohexanone 99.8%	60 ppm
CAS: 78-93-3	Methyl Ethyl Ketone	200 ppm
	(Cont	d on page 4

Reviewed on 11/29/2017 Printing date 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

(Contd. of page
830 ppm
2700* ppm
Language
5000* ppn 4000* ppn

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
CAS:	108-94-1 Cyclohexanone 99.8%
PEL	Long-term value: 200 mg/m³, 50 ppm
REL	Long-term value: 100 mg/m³, 25 ppm Skin
TLV	Long-term value: 50 mg/m³, 20 ppm Skin
CAS:	78-93-3 Methyl Ethyl Ketone
PEL	Long-term value: 590 mg/m³, 200 ppm
REL	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm
TLV	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm BEI
	(Contd. on page 5)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 4)

· Ingredients with biological limit values:

CAS: 108-94-1 Cyclohexanone 99.8%

BEI 80 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek

LD50: 1.2-Cyclohexanediol with hydrolysis (nonspecific, semi-quantitative)

8 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Cyclohexanol with hydrolysis (nonspecific, semi-quantitative)

CAS: 78-93-3 Methyl Ethyl Ketone

BEI 2 mg/L

LD50 Intraperitoneal: urine

Time: end of shift LD50: MEK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

· Body protection: Protective work clothing

(Contd. of page 5)

1	1
· Information on basic physical and c · General Information	nemical properties
· General Information · Appearance:	
Form:	Liquid
Color:	Colorless
· Odor:	Organic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>34 °C (>93.2 °F)
· Flash point:	<40 °C (<104 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	420 °C (788 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
· Explosion limits:	
Lower:	1.3 Vol %
Upper:	11.5 Vol %
· Vapor pressure at 20 °C (68 °F):	105 hPa (78.8 mm Hg)
· Density at 20 °C (68 °F):	0.9068 g/cm³ (7.56725 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 %
	906.8 g/l / 7.57 lb/gl
Solids content:	0.0 %

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
ATE (Acu	te Toxicity	Estimate)
Oral	LD50	1,790 mg/kg (rat)
Dermal	LD50	1,209 mg/kg (rabbit)

CAS: 108-94-1 Cyclohexanone 99.8%

Oral	LD50	1,535 mg/kg (rat)
Dermal	LD50	948 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research o	on Cancer)	
---	------------	--

CAS: 108-94-1 Cyclohexanone 99.8%

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 7)

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG, IATA	Flammable liquids, n.o.s. (Ethyl methyl ketone, Cyclohexanone) FLAMMABLE LIQUID, N.O.S. (Methyl Ethyl Keton) CYCLOHEXANONE)
Transport hazard class(es)	
DOT	
Class Label	3 Flammable liquids
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

	(Contd. of page
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	30
· EMS Number:	F- E , S - E
· Stowage Category	В
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
~ .	On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
· · · · · · · · · · · · · · · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ETHYL METHY
Ç	KETONE, CYCLOHEXANONE), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 78-93-3 Methyl Ethyl Ketone

· TSCA (Toxic Substances Control Act):

Cyclohexanone 99.8%

Methyl Ethyl Ketone

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 9)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 78-93-3 Methyl Ethyl Ketone

· TLV (Threshold Limit Value established by ACGIH)

CAS: 108-94-1 Cyclohexanone 99.8%

A3

Ι

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Cyclohexanone 99.8% Methyl Ethyl Ketone

· Hazard statements

Flammable liquid and vapor.

Harmful if swallowed or in contact with skin.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

 $Use\ explosion-proof\ electrical/ventilating/lighting/equipment.$

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Rinse mouth.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

(Contd. on page 11)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 10)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

11-29-2017: review SDS for accuracy. STN Creation date for SDS 03-12-2014. STN

11/29/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

 \cdot * Data compared to the previous version altered. Creation date 03/12/14 LS