Printing date 12/10/2021

Reviewed on 12/10/2021

Identification	
Product identifier	
Trade name: Potassium Hydroxide	
9.0 g/L in n-Butanol	
Article number: ANA005	
Details of the supplier of the safety data sheet Manufacturer/Supplier:	
Aqua Solutions, Inc.	
6913 Highway 225 DEER PARK, TX 77536	SOLUTIONS
USA	
800-256-2586	
Information department: Technical Coordinator	
Sherman Nelson shermann@aquasolutions.org	
Emergency telephone number:	
Chemtrec: 800-424-9300 Canutec: 613-996-6666	
Hazard(s) identification	
Classification of the substance or mixture	
GHS02 Flame	
GHS02 Flame	
<i>GHS02 Flame</i> <i>Flam. Liq. 3 H226 Flammable liquid and vapor.</i>	
Flam. Liq. 3 H226 Flammable liquid and vapor.	
Flam. Liq. 3 H226 Flammable liquid and vapor.	
Flam. Liq. 3 H226 Flammable liquid and vapor.	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage.	
Flam. Liq. 3 H226 Flammable liquid and vapor.	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed.	May cause drowsiness or dizziness.
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled and	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation.	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled and	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled and	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled and	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements GHS01 GHS07 GHS02 GHS05 GHS07	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled au Hazard pictograms GHS02 GHS05 GHS07 Signal word Danger	
Flam. Liq. 3 H226 Flammable liquid and vapor. GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. Label elements GHS04 GHS05 GHS07 GHS02 GHS05 GHS07	

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

	(Contd. of page 1)
Hazard statements	
Flammable liquid and vapor.	
Harmful if swallowed.	
Causes skin irritation.	
Causes serious eye damage.	
May cause respiratory irritation. May cause drowsiness or dizziness.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Call a poison center/doctor if you feel unwell.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/show	er.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese	nt and easy to do.
Continue rinsing.	·
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Rinse mouth.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulati	ons
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 3	
Fire = 3	
3 0 Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
HEALTH *3 Health = $*3$	
FIRE 3 $Fire = 3$	
REACTIVITY O $Reactivity = 0$	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	
	110 -

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 2)

98.896%

1.104%

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 71-36-3 n-Butyl Alcohol

CAS: 1310-58-3 Potassium Hydroxide

4 First-aid measures

· Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 4)

US –

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 3)
60 ppm
0.18 mg/m ³
800 ppm
$2 mg/m^3$
8000** ppm
54 mg/m ³

7 Handling and storage

· Handling:

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

Components with	limit values	that require	monitoring a	it the workplace:

CAS: 71-36-3 n-Butyl Alcohol

- PEL Long-term value: 300 mg/m³, 100 ppm
- REL Ceiling limit value: 150 mg/m³, 50 ppm Skin
- TLV Long-term value: 20 ppm

CAS: 1310-58-3 Potassium Hydroxide

- REL Ceiling limit value: 2 mg/m³
- TLV Ceiling limit value: 2 mg/m³

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

US ·

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Colorless	
· Odor:	Alcohol-like	
• Odor threshold:	Not determined.	
• pH-value at 20 •C (68 •F):	7	
Change in condition		
Melting point/Melting range:	-89 °C (-128.2 °F)	
Boiling point/Boiling range:	116 °C (240.8 °F)	
· Flash point:	35 °C (95 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	340 °C (644 °F)	
• Decomposition temperature:	Not determined.	

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

	(Contd. of page 5
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	9.4 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
• Density at 20 •C (68 •F):	0.8154 g/cm ³ (6.80451 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water at 20 °C (68 °F):	77 g/l
· Partition coefficient (n-octanol/wate	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	98.9 %
VOC content:	98.90 %
	806.4 g/l / 6.73 lb/gal
Solids content:	1.1 %
• Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 500 mg/kg

CAS: 71-36-3 n-Butyl Alcohol

Oral LD50 500 mg/kg (ATE)

(Contd. on page 7)

US -

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 6)

CAS: 1310-58-3 Potassium Hydroxide

Oral LD50 500 mg/kg (ATE)

- Primary irritant effect:
- \cdot on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- \cdot Sensitization: No sensitizing effects known.
- \cdot Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 7)

Transport information	
UN-Number	
DOT, IMDG, IATA	UN1120
UN proper shipping name	
DOT	Butanols
IMDG, IATA	BUTANOLS
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	Α
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
2 ·········	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1120 BUTANOLS, 3, III

(Contd. on page 9)

US

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 8)

ACTIVE

ACTIVE

D

15 Regulatory information Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

CAS: 71-36-3 n-Butyl Alcohol

· TSCA (Toxic Substances Control Act):

n-Butyl Alcohol

Potassium Hydroxide

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 71-36-3 n-Butyl Alcohol

• *TLV* (*Threshold Limit Value*) None of the ingredients is listed.

 \cdot NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: n-Butyl Alcohol Potassium Hydroxide
Hazard statements Flammable liquid and vapor. Harmful if swallowed.

US

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 9)
Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation. May cause drowsiness or dizziness.
· Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Rinse mouth.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of preparation / last revision Revision 1.0, 11-16-2021: Updated product information. STN Revision0.0, 09-02-2021: Creation date for SDS. STN 12/10/2021 / Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Potassium Hydroxide 9.0 g/L in n-Butanol

(Contd. of page 10)

US

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3