Printing date 05/18/2023

Reviewed on 05/18/2023

1 Identification

- · Product identifier
- Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L
- Article number: OXY202
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Aqua Solutions, Inc.
 6913 Highway 225 DEER PARK, TX 77536

USA 800-256-2586

- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- *Emergency telephone number:* Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Corrosion 1A H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labeling:
- Sodium Hydroxide • Hazard statements
- Causes severe skin burns and eye damage.
- Precautionary statements
- Do not breathe dusts or mists.
- Wash thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If swallowed: Rinse mouth. Do NOT induce vomiting.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

[–] US

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

(Contd. of page 1)

Lum district soll a science contact de star	(Contd. of page 1)
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Wash contaminated clothing before reuse.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	es.
Classification system:	
NFPA ratings (scale 0 - 4)	
$\begin{array}{c} \textbf{Health} = 3\\ \textbf{Health} = 0\\ Fire = 0\\ Reactivity = 0 \end{array}$	
HMIS-ratings (scale 0 - 4)	
HEALTH 3 $Health = 3$	
FIRE 0 Fire = 0	
REACTIVITY 0 Reactivity = 0	
REACTIVITE Reactivity = 0	
Other hazards	
Results of PBT and vPvB assessment	
• PBT : Not applicable.	
• <i>vPvB</i> : Not applicable.	
W VD. Not applicable.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

• Dangerous comp		
CAS: 1310-73-2	Sodium Hydroxide	15.217%
, v	ardous Ingredients	
CAS: 7732-18-5	Water	75.54%
	Sodium Chloride	9.13%
	Sodium Chlorate	0.109%
CAS: 7758-05-6	Potassium Iodate	0.004%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- \cdot Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- *Environmental precautions:* Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 1310-73-2	Sodium Hydroxide	$0.5 mg/m^3$
CAS: 7775-09-9	Sodium Chlorate	$3.6 mg/m^3$
CAS: 7758-05-6	Potassium Iodate	$0.45 mg/m^3$
· PAC-2:		
CAS: 1310-73-2	Sodium Hydroxide	5 mg/m ³
CAS: 7775-09-9	Sodium Chlorate	40 mg/m ³
CAS: 7758-05-6	Potassium Iodate	$4.9 mg/m^3$
· PAC-3:		
CAS: 1310-73-2	Sodium Hydroxide	50 mg/m ³
CAS: 7775-09-9	Sodium Chlorate	240 mg/m ³
CAS: 7758-05-6	Potassium Iodate	29 mg/m ³

7 Handling and storage

· Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.*
- Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

(Contd. on page 4)

US

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 1310-73-2 Sodium Hydroxide

PEL Long-term value: 2 mg/m³

REL Ceiling limit value: 2 mg/m³

TLV Ceiling limit value: 2 mg/m³

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

US -

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

(Contd. of page 4)

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and che	nical properties	
General Information		
Appearance:	7 · · · 7	
Form:	Liquid	
Color: Odor:	Clear Odorless	
• Odor: • Odor threshold:	Not determined.	
<i>pH-value at 20 °C (68 °F):</i>	>12	
Change in condition Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
0 1 0 0		
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.15001 g/cm³ (9.59683 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/water):	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	75.5 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	

Printing date 05/18/2023

Reviewed on 05/18/2023

(Contd. of page 5)

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

Solids content:

24.5 %

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 13,143 mg/kg (rat)

- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- \cdot on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive
- Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 7)

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

(Contd. of page 6)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, IMDG, IATA	UN1760
· UN proper shipping name · DOT · IMDG, IATA	Corrosive liquids, n.o.s. (Sodium Hydroxide) CORROSIVE LIQUID, N.O.S. (Sodium Hydroxide)
· Transport hazard class(es)	
CORROSIVE 0 • Class	8 Corrosive substances
· Label	8
· IMDG, IATA	
· Class	8 Corrosive substances

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

	(Contd. of page 7
· Label	8
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
 Special precautions for user Hazard identification number (Kemler code): 	Warning: Corrosive substances 80
• EMS Number: • Segregation groups	F-A,S-B (SGG18) Alkalis, (SGG4) chlorates
· Stowage Category · Stowage Code	B SW2 Clear of living quarters.
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
• DOT • Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE), 8, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

Section 355 (extremely hazardous substances):			
None of the ingredients is listed. • Section 313 (Specific toxic chemical listings): None of the ingredients is listed.			
		· TSCA (Toxic Substances Control Act):	
		Water	ACTIVE
Sodium Hydroxide	ACTIVE		
Sodium Chloride	ACTIVE		
Sodium Chlorate	ACTIVE		
Potassium Iodate	ACTIVE		
Hazardous Air Pollutants			
None of the ingredients is listed.			
	(Contd. on page		

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2

NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

(Contd. of page 8)

· Proposition 65

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

 \cdot Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Sodium Hydroxide · Hazard statements Causes severe skin burns and eye damage. · Precautionary statements Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Lachat Calibration Std. Level 2 NaOH 175, NaCl 105, NaClO3 1.25 g/L, NaOCl 50 mg/L

(Contd. of page 9)

	16 Other information
	This information is based on our present knowledge. However, this shall not constitute a guarantee for an specific product features and shall not establish a legally valid contractual relationship.
	· Department issuing SDS: Environment protection department.
• Contact: • Date of preparation / last revision	
	Revision 1.0 01-10-2022, removed fluoride and sulfate from ingredients. STN
	Creation date for SDS 08-27-2014. STN
	05/18/2023
	· Abbreviations and acronyms:
	IMDG: International Maritime Code for Dangerous Goods
	DOT: US Department of Transportation
	IATA: International Air Transport Association
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	NFPA: National Fire Protection Association (USA)
	HMIS: Hazardous Materials Identification System (USA)
	VOC: Volatile Organic Compounds (USA, EU)
	LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	NIOSH: National Institute for Occupational Safety
	OSHA: Occupational Safety & Health
	TLV: Threshold Limit Value
	PEL: Permissible Exposure Limit
	REL: Recommended Exposure Limit
	Skin Corrosion 1A: Skin corrosion/irritation – Category 1A
	Eye Damage 1: Serious eye damage/eye irritation – Category 1
	• * Data compared to the previous version altered.