Printing date 09/07/2017 Reviewed on 09/07/2017

1 Identification

· Product identifier

· Trade name: Molybdate Reagent ASTM D 1091

· Article number: 5956

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number:

Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

Ammonium Hydroxide

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

(Contd. on page 2)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

(Contd. of page 1)

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

17.5 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 3Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|-------------------------------------|---|---------|
| CAS: 12054-85-2 | Ammonium Molybdate Tetrahydrate ACS Grade | 17.507% |
| CAS: 1336-21-6 | Ammonium Hydroxide | 12.465% |
| · Table of Nonhazardous Ingredients | | |
| CAS: 7732-18-5 | Water | 70.028% |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.

(Contd. on page 3)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

(Contd. of page 2)

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| · PAC-1: | | |
|-----------------|---|-----------|
| CAS: 12054-85-2 | Ammonium Molybdate Tetrahydrate ACS Grade | 2.8 mg/m3 |
| CAS: 1336-21-6 | Ammonium Hydroxide | 61 ppm |
| · PAC-2: | | |
| CAS: 12054-85-2 | Ammonium Molybdate Tetrahydrate ACS Grade | 30 mg/m3 |
| CAS: 1336-21-6 | Ammonium Hydroxide | 330 ppm |
| · PAC-3: | | |
| CAS: 12054-85-2 | Ammonium Molybdate Tetrahydrate ACS Grade | 180 mg/m3 |
| CAS: 1336-21-6 | Ammonium Hydroxide | 2,300 ppm |

7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

| CAS: 12054-85-2 Ammonium Molybdate Tetrahydrate ACS Grade | | |
|---|--|--|
| ACGIH | Short-term value: 0.5 mg/m³ Long-term value: 5.0 mg/m³ | |
| NIOSH | Short-term value: 1000 mg/m³ | |
| OSHA-FINAL PEL'S | Short-term value: 5 mg/m³ Long-term value: 5 mg/m³ | |

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

(Contd. of page 4)

| Physical and chemical proper | ties — — — — — — — — — — — — — — — — — — — | |
|--|---|--|
| Information on basic physical and c | chemical properties | |
| General Information | | |
| Appearance: | | |
| Form: | Liquid | |
| Color: | Clear | |
| Odor: | Ammonia | |
| Odor threshold: | Not determined. | |
| pH-value at 20 °C (68 °F): | >12 | |
| Change in condition | | |
| Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | 100 °C (212 °F) | |
| Flash point: | Not applicable. | |
| Flammability (solid, gaseous): | Not applicable. | |
| Ignition temperature: | | |
| Decomposition temperature: | Not determined. | |
| Auto igniting: | Product is not selfigniting. | |
| Danger of explosion: | Product does not present an explosion hazard. | |
| Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Vapor pressure at 20 °C (68 °F): | 23 hPa (17 mm Hg) | |
| Density at 20 °C (68 °F): | 1.1424 g/cm³ (9.533 lbs/gal) | |
| Relative density | Not determined. | |
| Vapor density | Not determined. | |
| Evaporation rate | Not determined. | |
| Solubility in / Miscibility with | | |
| Water: | Fully miscible. | |
| Partition coefficient (n-octanol/water): Not determined. | | |
| Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| Solvent content: | | |
| Organic solvents: | 0.0 % | |
| Water: | 70.0 % | |
| VOC content: | 0.0 g/l / 0.00 lb/gl | |
| Solids content: | 17.5 % | |
| Other information | No further relevant information available. | |

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

(Contd. of page 5)

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

(Contd. on page 7)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent **ASTM D 1091**

(Contd. of page 6)

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

| 14 Transport | tinj | formai | tion |
|--------------|------|--------|------|
|--------------|------|--------|------|

| | UN-Number | |
|--|-----------|--|
|--|-----------|--|

· DOT, IMDG, IATA

UN1760

· UN proper shipping name

 $\cdot DOT$

Corrosive liquids, n.o.s. (Ammonia solution)

· IMDG, IATA CORROSIVE LIQUID, N.O.S. (AMMONIA SOLUTION)

- · Transport hazard class(es)
- $\cdot DOT$



· Class

8 Corrosive substances

· Label

· IMDG, IATA



| • | Class |
|---|-------|
| | Label |

8 Corrosive substances

· Packing group

· DOT, IMDG, IATA

III

· Environmental hazards:

· Marine pollutant:

No

· Special precautions for user

Warning: Corrosive substances

· Danger code (Kemler):

80

· EMS Number: · Segregation groups F-A,S-B

Ammonium compounds

· Stowage Category

(Contd. on page 8)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

| | (Contd. of page |
|---|--|
| · Stowage Code | SW2 Clear of living quarters. |
| · Transport in bulk according to Annex MARPOL73/78 and the IBC Code | II of Not applicable. |
| · Transport/Additional information: | |
| · DOT · Quantity limitations | On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN ''Model Regulation'': | UN 1760 CORROSIVE LIQUIDS, N.O.S. (AMMONIA SOLUTION) 8, III |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 1336-21-6 Ammonium Hydroxide

· TSCA (Toxic Substances Control Act):

CAS: 1336-21-6 Ammonium Hydroxide

CAS: 7732-18-5 Water

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 9)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

(Contd. of page 8)

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

Ammonium Hydroxide

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

09-07-2017: review SDS for accuracy. STN

Creation date for SDS 01-21-2015. STN

09/07/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

(Contd. on page 10)

Printing date 09/07/2017 Reviewed on 09/07/2017

Trade name: Molybdate Reagent ASTM D 1091

(Contd. of page 9)

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

HC