Printing date 11/29/2017 Reviewed on 11/29/2017

1 Identification

· Product identifier

· Trade name: Bromine Index Number

Titration Solvent

· Article number: LY001

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Canutec: 613-996-6666

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)



Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number **Titration Solvent**

(Contd. of page 1)

· Hazard pictograms









GHS02

GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Acetic Acid

Dichloromethane (*Methylene Chloride*)

Methanol (Methyl Alcohol)

Toluene

Sulfuric Acid 96 - 98%

Mercuric Chloride

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Immediately call a poison center/doctor.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 2Reactivity = 1

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous comp	oonents:	
CAS: 64-19-7	Acetic Acid	64.423%
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	15.53%
CAS: 67-56-1	Methanol (Methyl Alcohol)	10.355%
CAS: 108-88-3	Toluene	8.365%
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.475%
CAS: 7487-94-7	Mercuric Chloride	0.156%
· Table of Nonhaz	ardous Ingredients	
CAS: 7758-02-3	Potassium Bromide	0.261%
CAS: 7732-18-5	Water	0.436%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

CAS: 64-19-7	Acetic Acid	<i>5 ppm</i>
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	200 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	530 ppm
CAS: 108-88-3	Toluene	67 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.20 mg/m ²
CAS: 7758-02-3	Potassium Bromide	9.2 mg/m³
CAS: 7487-94-7	Mercuric Chloride	0.1 mg/m³
PAC-2:		
CAS: 64-19-7	Acetic Acid	35 ppm
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	560 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	2,100 ppm
CAS: 108-88-3	Toluene	560 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	8.7 mg/m ³
CAS: 7758-02-3	Potassium Bromide	100 mg/m^3
CAS: 7487-94-7	Mercuric Chloride	0.14 mg/m ²
<i>PAC-3:</i>		·
CAS: 64-19-7	Acetic Acid	250 ppm

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

		(Contd. of page 4)
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	6,900 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	7200* ppm
CAS: 108-88-3		3700* ppm
	Sulfuric Acid 96 - 98%	160 mg/m³
	Potassium Bromide	610 mg/m³
CAS: 7487-94-7	Mercuric Chloride	38 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

PEL Long-term value: 260 mg/m³, 200 ppm

· Additional information about design of technical systems: No further data; see item 7.

Additional information about design of technical systems. 140 jurner data, see tiem 7.
· Control parameters
· Components with limit values that require monitoring at the workplace:
CAS: 64-19-7 Acetic Acid
PEL Long-term value: 25 mg/m³, 10 ppm
REL Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm
TLV Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm
CAS: 75-09-2 Dichloromethane (Methylene Chloride)
PEL Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL See Pocket Guide App. A
TLV Long-term value: 174 mg/m³, 50 ppm BEI
CAS: 67-56-1 Methanol (Methyl Alcohol)

(Contd. on page 6)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

TLV She Lo Ski CAS: 10 PEL Lo Ce *10 REL She Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	hort-term value: 325 mg/m³, 250 ppm ong-term value: 260 mg/m³, 200 ppm kin hort-term value: 328 mg/m³, 250 ppm ong-term value: 262 mg/m³, 200 ppm kin; BEI 08-88-3 Toluene ong-term value: 200 ppm Ceiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm
TLV She Lo Ski CAS: 10 PEL Lo Ce *10 REL She Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	kin hort-term value: 328 mg/m³, 250 ppm ong-term value: 262 mg/m³, 200 ppm kin; BEI 08-88-3 Toluene ong-term value: 200 ppm eiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm
REL She Lo BE Lo TLV Lo REL Lo TLV Lo REL Lo TLV Lo REL Lo TLV Lo *a.	ong-term value: 262 mg/m³, 200 ppm kin; BEI 08-88-3 Toluene ong-term value: 200 ppm Seiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm
REL She Lo REL Lo REL Lo REL Lo REL Lo CAS: 76	ong-term value: 262 mg/m³, 200 ppm kin; BEI 08-88-3 Toluene ong-term value: 200 ppm Seiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm
CAS: 10 PEL Lo Ce *10 REL Sh Lo TLV Lo BE CAS: 76 PEL Lo TLV Lo *a. CAS: 74	O8-88-3 Toluene ong-term value: 200 ppm Eviling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm
PEL Lo Ce *10 REL Sh Lo TLV Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	ong-term value: 200 ppm Ceiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm
REL Sha Lo TLV Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a.	Ceiling limit value: 300; 500* ppm 10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm EEI
REL Sh. Lo TLV Lo BE CAS: 76 PEL Lo TLV Lo *a. CAS: 74	10-min peak per 8-hr shift hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm EEI
REL She Lo TLV Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	hort-term value: 560 mg/m³, 150 ppm ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm EEI
TLV Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	ong-term value: 375 mg/m³, 100 ppm ong-term value: 75 mg/m³, 20 ppm EI
TLV Lo BE CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	ong-term value: 75 mg/m³, 20 ppm EI
CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	PEI
CAS: 76 PEL Lo REL Lo TLV Lo *a. CAS: 74	
PEL Lo REL Lo TLV Lo *a. CAS: 74	7664-93-9 Sulfuric Acid 96 - 98%
REL Lo TLV Lo *a. CAS: 74	·
TLV Lo. *a. CAS: 74	ong-term value: 1 mg/m³
*a. CAS: 74	ong-term value: 1 mg/m³
CAS: 74	ong-term value: 0.2* mg/m³
	as thoracic fraction
PFI Lo	1487-94-7 Mercuric Chloride
	ong-term value: 0.1 mg/m³
as	s Hg; see OSHA standard interpretation memo
	ong-term value: 0.05* mg/m³
	Ceiling limit value: 0.1 mg/m³
as	s Hg; *Vapor; Skin
TLV Lo	ong-term value: 0.025 mg/m³
as	s Hg; Skin; BEI
· Ingredie	ients with biological limit values:
CAS: 75	75-09-2 Dichloromethane (Methylene Chloride)
BEI 0.3	3 mg/L
LD	D50 Intraperitoneal: urine
	ime: end of shift
	D50: Dichloromethane (semi-quantitative)
	7-56-1 Methanol (Methyl Alcohol)
BEI 15	
	D50 Intraperitoneal: urine
	ime: end of shift
LD	D50: Methanol (background, nonspecific)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 6)

CAS: 108-88-3 Toluene

BEI 0.02 mg/L

LD50 Intraperitoneal: blood

Time: prior to last shift of workweek

LD50: Toluene

 $0.03 \, mg/L$

LD50 Intraperitoneal: urine

Time: end of shift LD50: Toluene

0.3 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: o-Cresol with hydrolysis (background)

CAS: 7487-94-7 Mercuric Chloride

BEI 35 μg/L

LD50 Intraperitoneal: urine

Time: prior to shift

LD50: Total inorganic mercury (background)

15 µg/L

LD50 Intraperitoneal: blood

Time: end of shift at end of workweek

LD50: Total inorganic mercury (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

 ${\it Keep \ away \ from \ foodstuffs, \ beverages \ and \ feed.}$

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 7)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Dynamic:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties
General Information	
Appearance: Form:	I :! I
r orm: Color:	Liquid Clear
· Odor:	Organic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	4 °C (39.2 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	4 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)
Density at 20 °C (68 °F):	1.03629 g/cm³ (8.64784 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

Not determined.

(Contd. on page 9)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number **Titration Solvent**

(Conta.	ΟI	page	8)

	(Col	itu. oi page o
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	98.7 %	
Water:	0.4 %	
VOC content:	83.14 %	
	861.6 g/l / 7.19 lb/gl	
Solids content:	0.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Acute toxicity:	oxicological effects	
LD/LC50 values	that are relevant for classij	fication:
ATE (Acute Toxi	icity Estimate)	
Oral	LD50	>511-524 mg/kg (rat)
Dermal	LD50	>1,382 mg/kg
Inhalative	LC50/4 h	1,238 mg/l (rat)
CAS: 64-19-7 Ac	etic Acid	
Oral	LD50	3,310 mg/kg (rat)
Dermal	LD50	1,060 mg/kg (rabbit)
CAS: 75-09-2 Di	chloromethane (Methylene	c Chloride)
Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	52,000 mg/l (rat)
Irritation of skin	Skin Corrosion/Irritation	(rabbit) (Draize)
Irritation of eyes	Eye damage/eye irritation	(rabbit)
CAS: 67-56-1 M	ethanol (Methyl Alcohol)	
Oral	LD50	>1,187-2,769 mg/kg (rat)
Dermal	LD50	17,100 mg/kg (rabbit)
Inhalative	LC50/4 h	128.2 mg/l (rat)
CAS: 108-88-3 T	oluene	
Oral	LD50	5,000 mg/kg (rat)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number **Titration Solvent**

		(Contd. of page 9)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)
CAS: 7487-94-7	Mercuric Chloride	
Oral	LD50	1 mg/kg (rat)
Dermal	LD50	41 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Internat	tional Agency for Research on Cancer)	
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	2A
CAS: 108-88-3	Toluene	3
CAS: 7664-93-9	9 Sulfuric Acid 96 - 98%	1
CAS: 7487-94-7	7 Mercuric Chloride	3
· NTP (National	Toxicology Program)	
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	R
CAS: 7664-93-9	9 Sulfuric Acid 96 - 98%	K
· OSHA-Ca (Occ	cupational Safety & Health Administration)	
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 11)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

(Contd. of page 10)

 $\cdot \textit{Other adverse effects} \ \textit{No further relevant information available}.$

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN2924
UN proper shipping name	
DOT	Flammable liquids, corrosive, n.o.s. (Acetic acid, glacial, Metha Toluene)
IMDG, IATA	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ACETIC AC
2,122	GLACIAL, METHANOL, TOLUENE)
Transport hazard class(es)	
DOT	
- •	
Framable Loud	
CORROSIVE	
· Class	2 Flammabla liquida
· Cass · Label	3 Flammable liquids 3, 8
IMDG	
V	
· Class · Label	3 Flammable liquids 3/8
	3/0
IATA	
3	
	3 Flammable liquids
Class Label	3 (8)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

	(Contd. of page	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler):	338	
EMS Number:	F- E , S - C	
Segregation groups	Acids	
Stowage Category	B	
Stowage Code	SW2 Clear of living quarters.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 1 L	
2	On cargo aircraft only: 5 L	
· IMDG		
Limited quantities (LQ)	1L	
Excepted quantities (\widetilde{EQ})	Code: E2	
(Z)	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
UN "Model Regulation":	UN 2924 FLAMMABLE LIQUIDS, CORROSIVE, N.O.S. (ACET	
<u> </u>	ACID, GLACIAL, METHANOL, TOLUENE), 3 (8), II	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):	
,	Sulfuric Acid 96 - 98%
CAS: 7487-94-7	Mercuric Chloride
· Section 313 (Spe	ccific toxic chemical listings):
CAS: 75-09-2	Dichloromethane (Methylene Chloride)
CAS: 67-56-1	Methanol (Methyl Alcohol)
CAS: 108-88-3	Toluene
CAS: 7664-93-9	Sulfuric Acid 96 - 98%
CAS: 7487-94-7	Mercuric Chloride
· TSCA (Toxic Su	bstances Control Act):
Acetic Acid	
Dichloromethane (Methylene Chloride)	
Methanol (Methyl Alcohol)	
Toluene	
Sulfuric Acid 96	- 98%
Potassium Brom	ide
Mercuric Chloric	de
	(Contd. on page 1)

(Contd. on page 13)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number Titration Solvent

Water

Proposition 65

Chemicals known to cause cancer:

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol (Methyl Alcohol)

CAS: 108-88-3 Toluene

· Carcinogenic categories

CAS: 7487-94-7 Mercuric Chloride

· EPA (Environmental Protection Agency)			
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	L	
CAS: 108-88-3	Toluene	II	
CAS: 7487-94-7	Mercuric Chloride	C	
· TLV (Threshold Limit Value established by ACGIH)			
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	A3	
CAS: 108-88-3	Toluene	A4	
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	A2	
CAS: 7487-94-7	Mercuric Chloride	A4	
· NIOSH-Ca (National Institute for Occupational Safety and Health)			
CAS: 75-09-2 D	ichloromethane (Methylene Chloride)		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02 GHS05

GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Acetic Acid

Dichloromethane (Methylene Chloride)

Methanol (Methyl Alcohol)

Toluene

Sulfuric Acid 96 - 98%

Mercuric Chloride

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed or in contact with skin.

Causes severe skin burns and eye damage.

May cause cancer.

Suspected of damaging fertility or the unborn child.

(Contd. on page 14)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number
Titration Solvent

(Contd. of page 13)

Causes damage to organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Immediately call a poison center/doctor.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

11-29-2017: review SDS for accuracy. STN

Creation date for SDS 01-08-2015. STN

11/29/2017 / -

(Contd. on page 15)

Printing date 11/29/2017 Reviewed on 11/29/2017

Trade name: Bromine Index Number
Titration Solvent

(Contd. of page 14)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Carc. 1A: Carcinogenicity - Category 1A

Repr. 2: Reproductive toxicity - Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

-US