US -

Safety Data Sheet acc. to OSHA HCS

Printing date 05/18/2023

Identification	
Product identifier Trade name: <u>Bromine Titration</u> <u>Solvent</u>	
	d cannot be distributed in commerce (as defined in TSCA section 3(5)) tion 3(13)) for consumer paint or coating removal.
Details of the supplier of the safet Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	y data sheet SOLUTIONS
Information department: Technical Coordinator Sherman Nelson shermann@aqua. Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	solutions.org
Harand(a) identification	
	mixture
Classification of the substance or	mixture H225 Highly flammable liquid and vapor.
Classification of the substance or GHS02 Flame	H225 Highly flammable liquid and vapor.
Classification of the substance or GHS02 Flame Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Classification of the substance or GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossl	H225 Highly flammable liquid and vapor.
Flammable Liquids 2 GHS06 Skull and crossl Acute Toxicity - Dermal 3	H225 Highly flammable liquid and vapor.
Classification of the substance or GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossl Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A	H225 Highly flammable liquid and vapor. pones H311 Toxic in contact with skin.
Classification of the substance or GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossl Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A	H225 Highly flammable liquid and vapor. Pones H311 Toxic in contact with skin. H350 May cause cancer. ingle Exposure 1 H370 Causes damage to the central nervous system and th
Classification of the substance or GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossl Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A Specific Target Organ Toxicity - S	H225 Highly flammable liquid and vapor. Pones H311 Toxic in contact with skin. H350 May cause cancer. ingle Exposure 1 H370 Causes damage to the central nervous system and th
Classification of the substance or GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossl Acute Toxicity - Dermal 3 GHS08 Health hazard Carcinogenicity 1A Specific Target Organ Toxicity - S GHS05 Corrosion	H225 Highly flammable liquid and vapor. Pones H311 Toxic in contact with skin. H350 May cause cancer. ingle Exposure 1 H370 Causes damage to the central nervous system and the visual organs.

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

(Contd. of page 1)

Acute Toxicity - Oral 4 H302 Harmful if swallowed. Sensitization - Skin 1 H317 May cause an allergic skin reaction. · Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS06 GHS07 GHS02 GHS05 GHS08 · Signal word Danger · Hazard-determining components of labeling: Acetic Acid, Glacial Methanol Dichloromethane (Methylene Chloride) Sulfuric Acid 96 - 98% · Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. *Causes damage to the central nervous system and the visual organs.* · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.* Keep container tightly closed. Ground/bond container and receiving equipment. *Use explosion-proof electrical/ventilating/lighting/equipment.* Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off immediately all contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool.

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration

Solvent

(Contd. of page 2)

Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

• Classification system: • NFPA ratings (scale 0 - 4)

30 H Fr

Health = 3Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE0Fire = 0REACTIVITY2Reactivity = 2

· Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 64-19-7	Acetic Acid, Glacial	71.156%		
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	16.867%		
CAS: 67-56-1	Methanol	10.038%		
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.517%		
• Table of Nonhaz	· Table of Nonhazardous Ingredients			
CAS: 7732-18-5	Water	1.423%		

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

• Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

US

Printing date 05/18/2023

Trade name: Bromine Titration Solvent

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

· Extinguishing media

- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Wear protective e	equipment. Keep unprotected persons away.	
· Environmental p		
	duct to reach sewage system or any water course.	
	e authorities in case of seepage into water course or sewage system.	
Dilute with plent		
	enter sewers/ surface or ground water.	
	terial for containment and cleaning up: id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing		
	nated material as waste according to section 13.	
Ensure adequate		
· Reference to oth		
See Section 7 for	information on safe handling.	
	information on personal protection equipment.	
	r disposal information.	
	n Criteria for Chemicals	
• PAC-1:		
CAS: 64-19-7	Acetic Acid, Glacial	5 ppm
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	200 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	0.20 mg/n
· PAC-2:		
CAS: 64-19-7	Acetic Acid, Glacial	35 ppm
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	560 ppm
CAS: 67-56-1	Methanol	2,100 pp
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	8.7 mg/m
· PAC-3:		· · ·
CAS: 64-19-7	Acetic Acid, Glacial	250 ppm
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	6,900 ppr
CAS: 67-56-1	Methanol	7200* pp
		(Contd. on page

(Contd. of page 3)

Reviewed on 05/18/2023

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

 $\frac{\text{(Contd. of page 4)}}{160 \text{ mg/m}^3}$

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities • Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- *Store in cool, dry conditions in well sealed receptacles.*
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
CAS.	: 64-19-7 Acetic Acid, Glacial
PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Short-term value: 37 mg/m ³ , 15 ppm
	Long-term value: 25 mg/m ³ , 10 ppm
TLV	Short-term value: 15 ppm Long-term value: 10 ppm
CAS	75-09-2 Dichloromethane (Methylene Chloride)
PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 50 ppm BEI, A3
CAS	: 67-56-1 Methanol
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
L	(Contd. on page 6)

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration

Solvent

	Sorrein
	(Contd. of page 5)
TLV	Short-term value: 250 ppm
	Long-term value: 200 ppm
	Skin; BEI
CAS	: 7664-93-9 Sulfuric Acid 96 - 98%
PEL	Long-term value: 1 mg/m ³
	Long-term value: 1 mg/m ³
TLV	Long-term value: 0.2* mg/m ³
	*as thoracic fraction, A2
· Ingr	edients with biological limit values:
CAS	: 75-09-2 Dichloromethane (Methylene Chloride)
BEI	0.3 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift LD50: Dichloromethane (semi-quantitative)
CAS	: 67-56-1 Methanol
	15 mg/L
DLI	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Methanol (background, nonspecific)
· Addi	<i>itional information:</i> The lists that were valid during the creation were used as basis.
	•
	osure controls onal protective equipment:
	eral protective equipment. eral protective and hygienic measures:
	p away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	e protective clothing separately.
Avoi	d contact with the eyes.
Avoi	d contact with the eyes and skin.
	thing equipment:
	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use
	iratory protective device that is independent of circulating air.
· Prot	ection of hands:
elli.	Protective gloves
	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the nical mixture.
chen	

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

US

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

(Contd. of page 6)

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Strong
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	4 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)
Density at 20 °C (68 °F):	1.05662 g/cm ³ (8.81749 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	98.1 %

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

		(Contd. of page 7)
Water: VOC content:	1.4 % 81.19 % 857.9 g/l / 7.16 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)			
	LD50	996 mg/kg	
Dermal	LD50	994 mg/kg	
Inhalative	LC50/4h	29.9 mg/l	

· Primary irritant effect:

• on the skin: Caustic effect on skin and mucous membranes.

 \cdot on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: *Toxic*

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	2A	
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	1	
· NTP (National 2	Toxicology Program)		
CAS: 75-09-2	Dichloromethane (Methylene Chloride)	R	
		(Contd. on page 9	

(Contd. of page 8)

K

Safety Data Sheet acc. to OSHA HCS

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration

Solvent

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· OSHA-Ca (Occupational Safety & Health Administration)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN2924
· UN proper shipping name	
DOT	Flammable liquids, corrosive, n.o.s. (Acetic Acid, Glacial , Methanol)
· IMDG, IATA	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Acetic Act
	Glacial
	, Methanol)

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

Printing date 05/18/2023

	(Contd. of pag
Transport hazard class(es)	
DOT	
CORROSIVE	
Class Label	3 Flammable liquids 3, 8
	5, 0
IMDG	
3 8	
Class	3 Flammable liquids
Label	3/8
IATA	
Class	3 Flammable liquids
Label	3 (8)
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler	
EMS Number:	F-E,S-C
Segregation groups	(SGG1) Acids
Stowage Category	B SW2 Clean of living quarters
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	
	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 5 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
	maximum net quantity per buter packaging. 500 mi

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

(Contd. of page 10)

· UN "Model Regulation":

UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ACETIC ACID, GLACIAL , METHANOL), 3 (8), II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· Section 313 (Specific toxic chemical listings):

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 67-56-1 Methanol

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· TSCA (Toxic Substances Control Act):

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

Sulfuric Acid 96 - 98%	ACTIVE
Water	ACTIVE
Methanol	ACTIVE
Dichloromethane (Methylene Chloride)	ACTIVE
Acetic Acid, Glacial	ACTIVE

· Hazardous Air Pollutants

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 67-56-1 Methanol

· Proposition 65

· Chemicals known to cause cancer:

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

· TLV (Threshold Limit Value)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 75-09-2 Dichloromethane (Methylene Chloride)

(Contd. on page 12)

L

AЗ

A2

⁻ US

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

(Contd. of page 11) • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS05 GHS06 GHS07 GHS02 GHS08 · Signal word Danger · Hazard-determining components of labeling: Acetic Acid, Glacial Methanol Dichloromethane (Methylene Chloride) Sulfuric Acid 96 - 98% · Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. Causes damage to the central nervous system and the visual organs. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. *Keep container tightly closed.* Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off immediately all contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 13)

US

• Additional classification according to Decree on Hazardous Materials:

Printing date 05/18/2023

Reviewed on 05/18/2023

Trade name: Bromine Titration Solvent

· National regulations:

(Contd. of page 12)

US

	Carcinogenic hazardous material group III (dangerous). • Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
	Exceptions can be made by the authorities in certain cases. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
*	16 Other information
	This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
	· Department issuing SDS: Environment protection department.
	· Contact:
	• Date of preparation / last revision
	Revision 1.0 05/18/2023 reviewed SDS for accuracy. S.T.N.
	Revision 1.0 01-10-2022, removed fluoride and sulfate from ingredients. STN
	Revision 0.1, revised CAS number for this raw material which was incorrect. STN
	05/18/2023
	· Abbreviations and acronyms:
	IMDG: International Maritime Code for Dangerous Goods
	DOT: US Department of Transportation
	IATA: International Air Transport Association
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	NFPA: National Fire Protection Association (USA) HMIS: Hagardous Materials Identification System (USA)
	HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	NIOSH: National Institute for Occupational Safety
	OSHA: Occupational Safety & Health
	TLV: Threshold Limit Value
	PEL: Permissible Exposure Limit REL: Recommended Exposure Limit
	BEI: Biological Exposure Limit
	Flammable Liquids 2: Flammable liquids – Category 2
	Acute Toxicity - Oral 4: Acute toxicity - Category 4
	Acute Toxicity - Dermal 3: Acute toxicity – Category 3
	Skin Corrosion 1B: Skin corrosion/irritation – Category 1B
	Eye Damage 1: Serious eye damage/eye irritation – Category 1
	Sensitization - Skin 1: Skin sensitisation – Category 1
	Carcinogenicity IA: Carcinogenicity – Category 1A Specific Target Organ Taxicity – Single Exposure 1: Specific target organ taxicity (single exposure) – Category 1
	Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1 • * Data compared to the previous version altered.
	· · Data comparea to the previous version atterea.