Printing date 11/29/2017

Reviewed on 11/29/2017

1 Identification

- · Product identifier
- Trade name: <u>Cyclohexanone/</u> <u>Methyl Ethyl Ketone 50/50</u>
- · Article number: LEI006
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

- Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org • Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapor.



Acute Tox. 4H312Harmful in contact with skin.Eye Irrit. 2AH319Causes serious eye irritation.STOT SE 3H336May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: Cyclohexanone 99.8% Methyl Ethyl Ketone
- Hazard statements Flammable liquid and vapor. Harmful in contact with skin. Causes serious eye irritation.

(Contd. on page 2)

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/ Methyl Ethyl Ketone 50/50

| , | (Contd. of page |
|-----------|---|
| | Aay cause drowsiness or dizziness. Precautionary statements |
| | leep away from heat/sparks/open flames/hot surfaces No smoking. |
| | Ground/bond container and receiving equipment. |
| | Ise explosion-proof electrical/ventilating/lighting/equipment. |
| | Ise only non-sparking tools. |
| | ake precautionary measures against static discharge. |
| | void breathing dust/fume/gas/mist/vapors/spray |
| | Vash thoroughly after handling. |
| | <i>Use only outdoors or in a well-ventilated area.</i> |
| | Vear protective gloves/protective clothing/eye protection/face protection. |
| | f on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| | F INHALED: Remove person to fresh air and keep comfortable for breathing. |
| | f in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to a |
| | Continue rinsing. |
| | Call a poison center/doctor if you feel unwell. |
| | pecific treatment (see on this label). |
| | f eye irritation persists: Get medical advice/attention. |
| | ake off contaminated clothing and wash it before reuse. |
| | n case of fire: Use for extinction: CO2, powder or water spray. |
| | tore in a well-ventilated place. Keep container tightly closed. |
| S | tore in a well-ventilated place. Keep cool. |
| S | tore locked up. |
| | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| | lassification system: |
| ٠N | IFPA ratings (scale 0 - 4) |
| | Health = 2 |
| | Fire = 2 |
| | 2 0 Reactivity = 0 |
| · F | IMIS-ratings (scale 0 - 4) |
| | |
| | |
| | FIRE 3 $Fire = 3$ |
| | REACTIVITY \bigcirc Reactivity = 0 |
| | Other hazards |
| | Results of PBT and vPvB assessment |
| | BT: Not applicable. |
| $\cdot v$ | PvB: Not applicable. |
| _ | |
| 3 (| Composition/information on ingredients |
| ~~~ | |

• Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|-------------------------|---------------------|-------|
| CAS: 108-94-1 | Cyclohexanone 99.8% | 54.1% |
| CAS: 78-93-3 | Methyl Ethyl Ketone | 45.9% |
| | | |

(Contd. on page 3)

US

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 50/50

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

• Protective Action Criteria for Chemicals

| CAS: 108-94-1 C | yclohexanone 99.8% | 60 ppm |
|-----------------|---|----------------------|
| CAS: 78-93-3 M | lethyl Ethyl Ketone | 200 ppn |
| | | |
| | | |
| <i>PAC-2:</i> | | |
| | <i>Syclohexanone 99.8%</i> | 830 ppm |
| CAS: 108-94-1 C | yclohexanone 99.8% Iethyl Ethyl Ketone | |
| CAS: 108-94-1 C | - | 830 ppm 2700* ppn |

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/ Methyl Ethyl Ketone 50/50

| (Con | |
|-----------------------------------|-----------|
| • PAC-3: | |
| CAS: 108-94-1 Cyclohexanone 99.8% | 5000* ppm |
| CAS: 78-93-3 Methyl Ethyl Ketone | 4000* ppm |
| | |

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

CAS: 108-94-1 Cyclohexanone 99.8%

- PEL Long-term value: 200 mg/m³, 50 ppm REL Long-term value: 100 mg/m³, 25 ppm Skin
- TLV Long-term value: 50 mg/m³, 20 ppm Skin

CAS: 78-93-3 Methyl Ethyl Ketone

PELLong-term value: 590 mg/m³, 200 ppmRELShort-term value: 885 mg/m³, 300 ppmLong-term value: 590 mg/m³, 200 ppmTLVShort-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm BEI

(Contd. on page 5)

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/ Methyl Ethyl Ketone 50/50

(Contd. of page 4)

• Ingredients with biological limit values: CAS: 108-94-1 Cyclohexanone 99.8%

BEI 80 mg/L

LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: 1.2-Cyclohexanediol with hydrolysis (nonspecific, semi-quantitative)

8 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Cyclohexanol with hydrolysis (nonspecific, semi-quantitative)

CAS: 78-93-3 Methyl Ethyl Ketone

BEI 2 mg/L

LD50 Intraperitoneal: urine Time: end of shift LD50: MEK

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 6)

US

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/ Methyl Ethyl Ketone 50/50

· Body protection: Protective work clothing

9 Physical and chemical properties

| Information on basic physical and chemical properties General Information | | | |
|--|--|--|--|
| · Appearance: | | | |
| Form: | Liquid | | |
| Color: | Colorless | | |
| · Odor: | Organic | | |
| · Odor threshold: | Not determined. | | |
| · pH-value: | Not determined. | | |
| · Change in condition | | | |
| Melting point/Melting range: | Undetermined. | | |
| Boiling point/Boiling range: | >34 °C (>93.2 °F) | | |
| · Flash point: | <40 °C (<104 °F) | | |
| · Flammability (solid, gaseous): | Not applicable. | | |
| · Ignition temperature: | 420 °C (788 °F) | | |
| · Decomposition temperature: | Not determined. | | |
| · Auto igniting: | Product is not selfigniting. | | |
| • Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. | | |
| · Explosion limits: | | | |
| Lower: | 1.3 Vol % | | |
| Upper: | 11.5 Vol % | | |
| · Vapor pressure at 20 °C (68 °F): | 105 hPa (78.8 mm Hg) | | |
| • Density at 20 °C (68 °F): | 0.878 g/cm ³ (7.32691 lbs/gal) | | |
| · Relative density | Not determined. | | |
| Vapor density Not determined. | | | |
| · Evaporation rate | Not determined. | | |
| · Solubility in / Miscibility with | | | |
| Water: | Not miscible or difficult to mix. | | |
| · Partition coefficient (n-octanol/water) | · Partition coefficient (n-octanol/water): Not determined. | | |
| · Viscosity: | | | |
| Dynamic: | Not determined. | | |
| | | | |

| Dynamic: Kinematic: | Not determined. Not determined. | |
|---|---|--|
| Solvent content: Organic solvents: VOC content: | 100.0 % 100.00 % 878.0 g/l / 7.33 lb/gl | |
| Solids content: | 0.0 % | |
| | | |

(Contd. on page 7)

US

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 50/50

• Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

| ATE (Acute Toxicity Estimate) | | | |
|-------------------------------|------|-------------------|--|
| Oral | LD50 | 2,034 mg/kg (rat) | |

Dermal LD50 1,509 mg/kg (rabbit)

CAS: 108-94-1 Cyclohexanone 99.8%

 Oral
 LD50
 1,535 mg/kg (rat)

 Dermal
 LD50
 948 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 8,000 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: Irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 108-94-1 Cyclohexanone 99.8%

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

3

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/ Methyl Ethyl Ketone 50/50

(Contd. of page 7)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- \cdot **Mobility in soil** No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| · UN-Number | |
|------------------------------|---|
| · DOT, IMDG, IATA | UN1993 |
| · UN proper shipping name | |
| ·DOT | Flammable liquids, n.o.s. (Ethyl methyl ketone, Cyclohexanone) |
| · IMDG, IATA | FLAMMABLE LIQUID, N.O.S. (Methyl Ethyl Ketone CYCLOHEXANONE) |
| · Transport hazard class(es) | |
| · DOT | |
| PLAMIANUE LOUD | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, IMDG, IATA | II |

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/ Methyl Ethyl Ketone 50/50

| | (Contd. of page |
|--|---|
| · Environmental hazards: | |
| • Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 30 |
| · EMS Number: | <i>F-E,S-E</i> |
| · Stowage Category | B |
| • Transport in bulk according to Annex | II of |
| MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| ·DOT | |
| • Quantity limitations | On passenger aircraft/rail: 60 L |
| | On cargo aircraft only: 220 L |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| \cdot Excepted quantities (EQ) | Code: El |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ETHYL METHY |
| - | KETONE, CYCLOHEXANONE), 3, II |

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 78-93-3 Methyl Ethyl Ketone

· TSCA (Toxic Substances Control Act):

Cyclohexanone 99.8%

Methyl Ethyl Ketone

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

US

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 50/50

(Contd. of page 9)

Ι

AЗ

| • | Carcinog | enic | categories |
|---|----------|------|------------|
|---|----------|------|------------|

· EPA (Environmental Protection Agency)

CAS: 78-93-3 Methyl Ethyl Ketone

· TLV (Threshold Limit Value established by ACGIH)

CAS: 108-94-1 Cyclohexanone 99.8%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

- Hazard-determining components of labeling: Cyclohexanone 99.8% Methyl Ethyl Ketone
- · Hazard statements Flammable liquid and vapor. Harmful in contact with skin. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 11) US

Printing date 11/29/2017

Reviewed on 11/29/2017

Trade name: Cyclohexanone/

Methyl Ethyl Ketone 50/50

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision 11-29-2017: review SDS for accuracy. STN Creation date for SDS 03-12-2014. STN 11/29/2017 / -· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3