Printing date 12/10/2021

Reviewed on 12/10/2021

1 7 1	, • /•	
	entific	ation
	chilyte	

- · Product identifier
- Trade name: <u>Nitrogen Standard</u> <u>2.0 ug/ml ( ppm ) in Toluene</u>
- · Article number: AM370
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier: Aqua Solutions, Inc.
  6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org
   Emergency telephone number: Chemtrec: 800-424-9300
- Canutec: 613-996-6666

## **2** *Hazard*(*s*) *identification*

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

*Repr.* 2 *H361 Suspected of damaging fertility or the unborn child.* 

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

• Hazard-determining components of labeling: Toluene

(Contd. on page 2)

US

Printing date 12/10/2021

Reviewed on 12/10/2021

## Trade name: Nitrogen Standard 2.0 ug/ml ( ppm ) in Toluene

	(Contd. of page 1)
· Hazard statements	
Highly flammable liquid and vapor. Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause drowsmess of alguness. May cause damage to organs through prolonged or repeated exposure.	
May cause admage to organs infolgin prolonged of repeated exposure. May be fatal if swallowed and enters airways.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool. Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	1.C
· Classification system:	<b>.</b>
· NFPA ratings (scale 0 - 4)	
$\begin{array}{c} Health = 1 \\ Fire = 3 \end{array}$	
T u e = 5	
$\frac{1}{0} Reactivity = 0$	
· HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 3 $Fire = 3$	
<b>REACTIVITY</b> Reactivity = 0	

- Other hazards
- Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

(Contd. on page 3)

US

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard

2.0 ug/ml ( ppm ) in Toluene

(Contd. of page 2)

99.997%

0.003%

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-88-3 Toluene

· Table of Nonhazardous Ingredients

CAS: 86-74-8 Carbazole, 96%

#### 4 First-aid measures

· Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

• *Reference to other sections* See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

US

Printing date 12/10/2021

Reviewed on 12/10/2021

#### Trade name: Nitrogen Standard 2.0 ug/ml ( ppm ) in Toluene

See Section 13	for disposal information.	(Contd. of page 3)
	on Criteria for Chemicals	
· PAC-1:		
CAS: 108-88-3	Toluene	67 ppm
CAS: 86-74-8	Carbazole, 96%	0.66 mg/m <sup>3</sup>
· PAC-2:		
CAS: 108-88-3	Toluene	560 ppm
CAS: 86-74-8	Carbazole, 96%	7.2 mg/m <sup>3</sup>
· PAC-3:		
CAS: 108-88-3	Toluene	3700* ppm
CAS: 86-74-8	Carbazole, 96%	43 mg/m <sup>3</sup>

## 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- $\cdot$  Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

   CAS: 108-88-3 Toluene

   PEL
   Long-term value: 200 ppm

   Ceiling limit value: 300; 500\* ppm

   \*10-min peak per 8-hr shift

   REL
   Short-term value: 560 mg/m³, 150 ppm

   Long-term value: 375 mg/m³, 100 ppm

   TLV
   Long-term value: 20 ppm

   BEI, OTO, A4

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 2.0 ug/ml ( ppm ) in Toluene

(Contd. of page 4)

Ingredients with biological limit values: CAS: 108-88-3 Toluene	
BEI 0.02 mg/L	
LD50 Intraperitoneal: blood	
Time: prior to last shift of workweek	
LD50: Toluene	
0.03 mg/L	
LD50 Intraperitoneal: urine	
Time: end of shift	
LD50: Toluene	
0.3 mg/g creatinine	
LD50 Intraperitoneal: urine	
Time: end of shift	
LD50: o-Cresol with hydrolysis (background)	
Additional information: The lists that were valid during the creation were used as b	asis.
· Exposure controls	
· Personal protective equipment:	
· General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing.	
Wash hands before breaks and at the end of work.	
Store protective clothing separately.	
Avoid contact with the skin.	
Avoid contact with the eyes and skin.	
Breathing equipment:	
In case of brief exposure or low pollution use respiratory filter device. In case of int	tensive or longer exposure us
respiratory protective device that is independent of circulating air.	
Protection of hands:	
1 <sup>11</sup> ? Protective gloves	
The glove material has to be impermeable and resistant to the product/ the substance	e/ the preparation
Due to missing tests no recommendation to the glove material can be given for the	
chemical mixture.	produces site proparations sit
Selection of the glove material on consideration of the penetration times, rates of diff	fusion and the degradation
• Material of gloves	
The selection of the suitable gloves does not only depend on the material, but also of	n further marks of auality and
varies from manufacturer to manufacturer. As the product is a preparation of severa	
the glove material can not be calculated in advance and has therefore to be checked	
• Penetration time of glove material	I I I I I I I I I I I I I I I I I I I
The exact break through time has to be found out by the manufacturer of the pro-	otective gloves and has to b
observed.	0
· Eye protection:	
Tightly sealed goggles	

(Contd. on page 6) US

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 2.0 ug/ml ( ppm ) in Toluene

· Body protection: Protective work clothing

Information on basic physical and o	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
· Odor: · Odor threshold:	Toluene Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	110 °C (230 °F)
Flash point:	4 °C (39.2 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	535 °C (995 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
• Vapor pressure at 20 •C (68 •F):	29 hPa (21.8 mm Hg)
Density at 20 °C (68 °F):	0.86683 g/cm <sup>3</sup> (7.2337 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 15 °C (59 °F):	0.5 g/l
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 % 866.8 g/l / 7.23 lb/gal
Solids content:	0.0%

(Contd. of page 5)

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard

2.0 ug/ml ( ppm ) in Toluene

(Contd. of page 6)

• Other information

No further relevant information available.

#### **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11 Toxicological information**

· Information on toxicological effects

- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

	· IARC (Internat	ional Agency for Research on Cancer)	
	CAS: 108-88-3	Toluene	3
	CAS: 86-74-8	Carbazole, 96%	2B
Γ	· NTP (National	Toxicology Program)	
	None of the ing	redients is listed.	

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### **12 Ecological information**

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

US

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard

2.0 ug/ml ( ppm ) in Toluene

(Contd. of page 7)

US

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

• Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· UN-Number · DOT, IMDG, IATA	UN1993	
· UN proper shipping name · DOT · IMDG, IATA	Flammable liquids, n.o.s. (Toluene) FLAMMABLE LIQUID, N.O.S. (Toluene)	
· Transport hazard class(es)		
·DOT		
· Class	3 Flammable liquids	
· Label	3	
· Class	3 Flammable liquids	
· Label	3	
· Packing group · DOT, IMDG, IATA	II	
· Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user · Hazard identification number (Kemle	Warning: Flammable liquids e <b>r code):</b> 33	
· EMS Number:	<i>F-E,<u>S-E</u></i>	
· Stowage Category	В	

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 2.0 ug/ml ( ppm ) in Toluene

	(Contd. of page
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE), 3, II

## **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

Sara Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
CAS: 108-88-3 Toluene	
TSCA (Toxic Substances Control Act):	
Toluene	ACTIV
Carbazole, 96%	ACTIV
Hazardous Air Pollutants	I
CAS: 108-88-3 Toluene	
Proposition 65	
Chemicals known to cause cancer:	
CAS: 86-74-8 Carbazole, 96%	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
CAS: 108-88-3 Toluene	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
CAS: 108-88-3 Toluene	
TLV (Threshold Limit Value)	
CAS: 108-88-3 Toluene	F
	(Contd. on page

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 2.0 ug/ml ( ppm ) in Toluene

(Contd. of page 9) · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed. • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: Toluene · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)

Printing date 12/10/2021

Reviewed on 12/10/2021

Trade name: Nitrogen Standard 2.0 ug/ml ( ppm ) in Toluene

(Contd. of page 10)

$T_{i}$	his information is based on our present knowledge. However, this shall not constitute a guarantee for
sp	pecific product features and shall not establish a legally valid contractual relationship.
D	Department issuing SDS: Environment protection department.
С	ontact:
D	Date of preparation / last revision
	evision 1.0, 11-16-2021: Updated product information. STN
	<i>Pevision 1.6, 11 16 2021: Optimized product information: 511</i> <i>Pevision 2.0, 01-12-2020: Updated sections 1, 2 and 15 to meet Fanns new requirements</i>
	2/10/2021 / -
	bbreviations and acronyms:
	MDG: International Maritime Code for Dangerous Goods
	OT: US Department of Transportation
	ATA: International Air Transport Association INECS: European Inventory of Existing Commercial Chemical Substances
	LINCS: European List of Notified Chemical Substances
	AS: Chemical Abstracts Service (division of the American Chemical Society)
	FPA: National Fire Protection Association (USA)
	MIS: Hazardous Materials Identification System (USA)
	OC: Volatile Organic Compounds (USA, EU)
PI	BT: Persistent, Bioaccumulative and Toxic
vŀ	PvB: very Persistent and very Bioaccumulative
	IOSH: National Institute for Occupational Safety
	SHA: Occupational Safety & Health
	LV: Threshold Limit Value
	EL: Permissible Exposure Limit
	EL: Recommended Exposure Limit
	EI: Biological Exposure Limit
	lam. Liq. 2: Flammable liquids – Category 2
	kin Irrit. 2: Skin corrosion/irritation – Category 2 epr. 2: Reproductive toxicity – Category 2
	TOT SE 3: Specific target organ toxicity (single exposure) – Category 3
	TOT RE 2: Specific target organ toxicity (single exposure) – Category 2