Printing date 05/24/2021

Reviewed on 05/24/2021

Product identifier		
Trade name: <u>n-Butyl</u>	Alcohol, HPLC Grade	
Article number: B8202	7	
CAS Number:		
71-36-3		
EC number:		
200-751-6 Index number:		
603-004-00-6		SOLUTIONS
Details of the supplier	of the safety data sheet	
Manufacturer/Supplie		
Aqua Solutions, Inc.		
6913 Highway 225 DEER PARK, TX 7753	26	
USA		
800-256-2586		
Information departme	ent:	
Technical Coordinator	~	
Sherman Nelson sherm	nann@aquasolutions.org	
Emergency telephone	number:	
<i>Emergency telephone</i> <i>Chemtrec:</i> 800-424-93	number: 200	
<i>Emergency telephone</i> <i>Chemtrec: 800-424-93</i> <i>Canutec: 613-996-666</i>	number: 200 66	
<i>Emergency telephone</i> <i>Chemtrec:</i> 800-424-93	number: 200 26 cation ubstance or mixture	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su	number: 200 26 cation ubstance or mixture ne	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam	number: 200 26 cation ubstance or mixture ne	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam	number: 200 26 20 20 20 20 20 20 20 20 20 20 20 20 20	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam Flam. Liq. 3 H226	number: 200 26 20 20 20 20 20 20 20 20 20 20 20 20 20	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam Flam. Liq. 3 H226	number: 200 26 20 20 20 20 20 20 20 20 20 20 20 20 20	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam Flam. Liq. 3 H226 Eye Dam. 1 H318	number: 200 26 20 20 20 20 20 20 20 20 20 20 20 20 20	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam Flam. Liq. 3 H226	number: 200 26 20 20 20 20 20 20 20 20 20 20 20 20 20	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam Flam. Liq. 3 H226 Eye Dam. 1 H318	number: 200 26 20 20 20 20 20 20 20 20 20 20 20 20 20	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Hazard(s) identific Classification of the su GHS02 Flam Flam. Liq. 3 H226 Eye Dam. 1 H318 GHS07	number: 200 26 cation ubstance or mixture ne Flammable liquid and vapor. rosion Causes serious eye damage.	
Emergency telephone Chemtrec: 800-424-93 Canutec: 613-996-666 Classification of the su GHS02 Flan Flam. Liq. 3 H226 Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315	number: 200 26 20 20 20 20 20 20 20 20 20 20 20 20 20	cause drowsiness or dizziness.

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: n-Butyl Alcohol, HPLC Grade

(Contd. of page 1)



- US

Printing date 05/24/2021

Reviewed on 05/24/2021

#### Trade name: n-Butyl Alcohol, HPLC Grade

(Contd. of page 2)

- Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description
- 71-36-3 n-Butyl Alcohol
- · Identification number(s)
- EC number: 200-751-6
- *Index number:* 603-004-00-6

### 4 First-aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

US

Printing date 05/24/2021

Reviewed on 05/24/2021

(Contd. of page 3)

#### Trade name: n-Butyl Alcohol, HPLC Grade

See Section 8 for information on personal protection equipment.

- See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

• **PAC-1:** 60 ppm

- **PAC-2:** 800 ppm
- **PAC-3:** 8000\*\* ppm

### 7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

### CAS: 71-36-3 n-Butyl Alcohol

PEL Long-term value: 300 mg/m<sup>3</sup>, 100 ppm

REL Ceiling limit value: 150 mg/m<sup>3</sup>, 50 ppm Skin

TLV Long-term value: 61 mg/m<sup>3</sup>, 20 ppm

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Printing date 05/24/2021

Reviewed on 05/24/2021

### Trade name: n-Butyl Alcohol, HPLC Grade

(Contd. of page 4)

- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves
- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• *Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.* 

• Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties
General Information	
Appearance: Form:	Linuid
Form: Color:	Liquid Colorless
· Odor:	Alcohol-like
• Odor threshold:	Not determined.
pH-value:	7
Change in condition	
Melting point/Melting range:	-89 °C (-128.2 °F)
Boiling point/Boiling range:	116-118 °C (240.8-244.4 °F)
Flash point:	35 °C (95 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	340 °C (644 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	9.4 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
Density at 20 °C (68 °F):	0.81 g/cm³ (6.75945 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water at 20 °C (68 °F):	77 g/l

Printing date 05/24/2021

Reviewed on 05/24/2021

(Contd. of page 5)

Trade name: n-Butyl Alcohol, HPLC Grade

 Viscosity: Dynamic at 20 °C (68 °F): Kinematic:

2.95 mPas Not determined.

· Other information

No further relevant information available.

## **10** Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot$  Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11** Toxicological information

· Information on toxicological effects

• Acute toxicity:

### · LD/LC50 values that are relevant for classification:

Oral LD50 500 mg/kg (ATE)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

## **12 Ecological information**

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

US

Printing date 05/24/2021

Reviewed on 05/24/2021

(Contd. of page 6)

Trade name: n-Butyl Alcohol, HPLC Grade

• Other adverse effects No further relevant information available.

## **13 Disposal considerations**

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1120	
UN proper shipping name		
DOT	Butanols	
IMDG, IATA	BUTANOLS	
Transport hazard class(es)		
DOT		
HAMMABLE LLOOP		
Class	3 Flammable liquids	
Label	3	
IMDG, IATA		
3		
Class	3 Flammable liquids	
Label	3	
Packing group	111	
DOT, IMDG, IATA	111	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Hazard identification number (Kemler code)		
EMS Number:	F-E,S-D	
Stowage Category	A	
Transport in bulk according to Annex II of		

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: n-Butyl Alcohol, HPLC Grade

	(Contd. of page 2
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
· Hazardous substance:	5000 lbs, 2270 kg
· IMDG	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities ( $\widetilde{E}Q$ )	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1120 BUTANOLS, 3, III

### **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

- Section 355 (extremely hazardous substances): Substance is not listed.
- Section 313 (Specific toxic chemical listings): Substance is listed.
- TSCA (Toxic Substances Control Act): ACTIVE
- · Hazardous Air Pollutants Substance is not listed.
- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency) D
- · TLV (Threshold Limit Value) Substance is not listed.
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- *GHS label elements* The substance is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



Signal word Danger
Hazard statements
Flammable liquid and vapor.
Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.

(Contd. on page 9)

US

Printing date 05/24/2021

Reviewed on 05/24/2021

#### Trade name: n-Butyl Alcohol, HPLC Grade

(Contd. of page 8) Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. *Continue rinsing.* Immediately call a poison center/doctor. Specific treatment (see on this label). Rinse mouth. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of preparation / last revision Revision 0.1, Reviewed SDS. STN Revision 1.0 05-07-2021: updated hazard information. STN 05/24/2021 / -
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

US