Printing date 01/03/2018 Reviewed on 01/03/2018

1 Identification

· Product identifier

· Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

· Article number: SPE908

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number:

Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT SE 2 H371 May cause damage to organs.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Isopropanol

Methanol (Methyl Alcohol)

· Hazard statements

Highly flammable liquid and vapor.

May cause damage to organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 1)

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 3

 \nearrow Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- $\cdot \textit{Description:} \ \textit{Mixture of the substances listed below with nonhazardous additions}.$

| · Dangerous components: | |
|--|----------|
| CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof | 90.0101% |
| CAS: 67-56-1 Methanol (Methyl Alcohol) | 5.015% |
| CAS: 67-63-0 Isopropanol | 4.973% |
| m II ay I I I I I | |

· Table of Nonhazardous Ingredients

CAS: 7757-82-6 Sodium Sulfate Anhydrous 0.0013%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| | • | |
|----------------|-----------------------------------|-----------------------|
| · PAC-1: | | |
| CAS: 64-17-5 | Ethyl Alcohol, Absolute 200 Proof | 1,800 ppm |
| CAS: 67-56-1 | Methanol (Methyl Alcohol) | 530 ppm |
| CAS: 67-63-0 | Isopropanol | 400 ppm |
| CAS: 7757-82-6 | Sodium Sulfate Anhydrous | 9.8 mg/m ³ |
| · PAC-2: | | |
| CAS: 64-17-5 | Ethyl Alcohol, Absolute 200 Proof | 3300* ppm |
| CAS: 67-56-1 | Methanol (Methyl Alcohol) | 2,100 ppm |
| CAS: 67-63-0 | Isopropanol | 2000* ppm |
| CAS: 7757-82-6 | Sodium Sulfate Anhydrous | 110 mg/m³ |
| · PAC-3: | | İ |
| CAS: 64-17-5 | Ethyl Alcohol, Absolute 200 Proof | 15000* ppm |
| CAS: 67-56-1 | Methanol (Methyl Alcohol) | 7200* ppm |
| CAS: 67-63-0 | Isopropanol | 12000** ppm |
| CAS: 7757-82-6 | Sodium Sulfate Anhydrous | 650 mg/m³ |
| | • | |

— US

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

| · Components with limit | values that require | monitoring at th | e workplace: |
|-------------------------|---------------------|------------------|--------------|
|-------------------------|---------------------|------------------|--------------|

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

- PEL Long-term value: 1900 mg/m³, 1000 ppm
- REL Long-term value: 1900 mg/m³, 1000 ppm
- TLV Short-term value: 1880 mg/m³, 1000 ppm

CAS: 67-56-1 Methanol (Methyl Alcohol)

- PEL Long-term value: 260 mg/m³, 200 ppm
- REL Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm

Skin

TLV Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm

Skin; BEI

CAS: 67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm

BEI

· Ingredients with biological limit values:

CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

(Contd. on page 5)

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 4)

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Clear

Odor: Alcohol

Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 64 °C (147.2 °F)

• Flash point: $11 \, ^{\circ}C \, (51.8 \, ^{\circ}F)$

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 425 °C (797 °F)

(Contd. on page 6)

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

| | (Contd. of page |
|---------------------------------------|---|
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vapo mixtures are possible. |
| Explosion limits: | |
| Lower: | 3.5 Vol % |
| Upper: | 19 Vol % |
| Vapor pressure at 20 °C (68 °F): | 59 hPa (44.3 mm Hg) |
| Density at 20 °C (68 °F): | 0.7897 g/cm³ (6.59005 lbs/gal) |
| Relative density | Not determined. |
| Vapor density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |
| Partition coefficient (n-octanol/wate | e r): Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | |
| Organic solvents: | 100.0 % |
| VOC content: | 100.00 % |
| | 789.7 g/l / 6.59 lb/gl |
| Solids content: | 90.0 % |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC50 values that are relevant for classification: | | |
|--|-------------|---------------------------|
| ATE (Acut | te Toxicity | Estimate) |
| Oral | LD50 | 23,667-55,210 mg/kg (rat) |
| Inhalative | LC50/4 h | 488 mg/l (rat) |

(Contd. on page 7)

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 6)

| CAS: 67-5 | 6-1 Metha | nol (Methyl Alcohol) |
|------------|-------------|----------------------|
| Oral | LD50 | 100 mg/kg (ATE) |
| Dermal | <i>LD50</i> | 300 mg/kg (ATE) |
| Inhalative | LC50/4 h | 3 mg/l (ATE) |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

| Caremogenic | cutegories | | | |
|---|--|---|--|--|
| · IARC (Interno | ntional Agency for Research on Cancer) | | | |
| CAS: 64-17-5 | Ethyl Alcohol, Absolute 200 Proof | 1 | | |
| CAS: 67-63-0 | Isopropanol | 3 | | |
| · NTP (National Toxicology Program) | | | | |
| None of the ingredients is listed. | | | | |
| · OSHA-Ca (Occupational Safety & Health Administration) | | | | |
| None of the in | gredients is listed. | | | |
| | | | | |

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

US

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 7)

| UN-Number | |
|---|--|
| DOT, IMDG, IATA | UN1993 |
| UN proper shipping name DOT IMDG, IATA | Flammable liquids, n.o.s. (Ethanol, Methanol, Isopropanol) FLAMMABLE LIQUID, N.O.S. (ETHANOL, METHANO Isopropanol) |
| Transport hazard class(es) | |
| DOT | |
| FLAMMIRE USUS Class | 3 Flammable liquids |
| Label | 3 |
| | 2 Element le l'entite |
| Class Label | 3 Flammable liquids 3 |
| | 3 |
| Packing group DOT, IMDG, IATA | II |
| Environmental hazards: | Not applicable. |
| Special precautions for user Danger code (Kemler): | Warning: Flammable liquids 33 |
| EMS Number: | F-E, <u>S-E</u> |
| Stowage Category | В |
| Transport in bulk according to Annex MARPOL73/78 and the IBC Code | II of Not applicable. |
| UN "Model Regulation": | UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ETHANO METHANOL, ISOPROPANOL), 3, II |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

| · Section 355 (extremely hazardous substances) | · Section 355 | (extremely | hazardo | ous sub | stances) | : |
|--|---------------|------------|---------|---------|----------|---|
|--|---------------|------------|---------|---------|----------|---|

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 67-56-1 Methanol (Methyl Alcohol)

CAS: 67-63-0 Isopropanol

(Contd. on page 9)

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 8)

· TSCA (Toxic Substances Control Act):

Ethyl Alcohol, Absolute 200 Proof

Methanol (Methyl Alcohol)

Isopropanol

Sodium Sulfate Anhydrous

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

CAS: 67-56-1 Methanol (Methyl Alcohol)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

| CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof | A3 |
|--|----|
| CAS: 67-63-0 Isopropanol | A4 |

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Isopropanol

Methanol (Methyl Alcohol)

· Hazard statements

Highly flammable liquid and vapor.

May cause damage to organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 10)

Printing date 01/03/2018 Reviewed on 01/03/2018

Trade name: Sulfate Std. 4.0 mg/kg

Soln., Prep to ASTM D 7318-07

(Contd. of page 9)

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing, Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

01-03-2018: review SDS for accuracy. STN

Revision 0.0, 10-07-2015: creation date for SDS. STN

01/03/2018 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2