Printing date 01/31/2018	Reviewed on 01/31/2018
1 Identification	
· Product identifier	
· Trade name: <u>Isopropanol / Water</u> <u>10:6 v/v</u>	
• Article number: UCT117	
• Details of the supplier of the safety data sheet • Manufacturer/Supplier:	
Aqua Solutions, Inc. 6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536	
USA 800-256-2586	
· Information department:	
Technical Coordinator	
Sherman Nelson sherman@aquasolutions.org	
• Emergency telephone number: Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
2 Hazard(s) identification	
· Classification of the substance or mixture	
GHS02 Flame	
GHS02 Flume	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
\mathbf{A}	
GHS07	
Eye Irrit. 2A H319 Causes serious eye irritation.	
STOT SE 3 H336 May cause drowsiness or dizziness.	
• Label elements • GHS label elements The product is classified and labeled a • Hazard pictograms	ccording to the Globally Harmonized System (GHS).
GHS02 GHS07	
· Signal word Danger	
• Hazard-determining components of labeling: Isopropanol	
· Hazard statements	
Highly flammable liquid and vapor. Causes serious eye irritation.	
May cause drowsiness or dizziness.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No Ground/bond container and receiving equipment.	smoking.
Groundsond container und receiving equipment.	(Contd. on page 2)

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water

10:6 v/v

(Contd. of page 1)
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification system:
· NFPA ratings (scale 0 - 4)
Health = 2
$\frac{3}{Fire = 3}$
$\frac{2}{Reactivity} = 0$
· HMIS-ratings (scale 0 - 4)
HEALTH 2 $Health = 2$
FIRE 3 Fire = 3
REACTIVITY Reactivity = 0
· Other hazards
· Results of PBT and vPvB assessment
• PBT: Not applicable.
· vPvB: Not applicable.
2 Composition linformation on increationts
3 Composition/information on ingredients
· Chemical characterization: Mixtures
• Description: Mixture of the substances listed below with nonhazardous additions.
· Dangerous components:
Ŭ I
CAS: 67-63-0 Isopropanol 56.679%
· Table of Nonhazardous Ingredients
CAS: 7732-18-5 Water 43.321%
4 First-aid measures

Description of first aid measures
 After inhalation: Supply fresh air; consult doctor in case of complaints.
 After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

US

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water

10:6 v/v

(Contd. of page 2)

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 67-63-0 Isopropanol	400 ppm
· PAC-2:	
CAS: 67-63-0 Isopropanol	2000* ppm
· PAC-3:	
CAS: 67-63-0 Isopropanol	12000** ppm

7 Handling and storage

· Handling:

· Precautions for safe handling No special precautions are necessary if used correctly.

- \cdot Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)

US

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water

10:6 v/v

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

 \cdot Components with limit values that require monitoring at the workplace:

CAS: 67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm

- REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
- TLV Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI

· Ingredients with biological limit values:

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
- Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

[–] US

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water 10:6 v/v

(Contd. of page 4)

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and a	chemical properties
General Information	
Appearance:	Limid
Form: Color:	Liquid Clear
Odor:	Alcohol
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C (179.6 °F)
Flash point:	13 °C (55.4 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo
	mixtures are possible.
Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
Density at 20 °C (68 °F):	0.86563 g/cm³ (7.22368 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	56.7 %

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water

10:6 v/v

	(Contd. of p	age 5)
Water: VOC content:	43.3 % 56.68 % 400.6 c // (4.00.1) /c1	
Solids content: • Other information	490.6 g/l / 4.09 lb/gl 0.0 % No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4 h 52.9 mg/l (rat)

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 67-63-0 Isopropanol

 \cdot NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 7)

3

⁻ ÚS

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water

10:6 v/v

(Contd. of page 6)

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • Results of PBT and vPvB assessment

· *PBT:* Not applicable.

· **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG, IATA	Flammable liquids, n.o.s. (Isopropanol) FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Transport hazard class(es)	
DOT	
RAMAREE LOUD	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	
Label	3 Flammable liquids 3
Packing group DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water 10:6 v/v

	(Contd. of page
Danger code (Kemler):	33
EMS Number:	F- E , S - E
Stowage Category	B
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
~ ·	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ISOPROPANOL), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 67-63-0 Isopropanol

· TSCA (Toxic Substances Control Act):

Isopropanol

Water

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

CAS: 67-63-0 Isopropanol

(Contd. on page 9)

A4

US

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water

10:6 v/v

(Contd. of page 8)

\cdot NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Isopropanol
Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

• Date of preparation / last revision

01-31-2018: review SDS for accuracy. STN Creation date for SDS 02-25-2015. STN 01/31/2018 / -

(Contd. on page 10)

[–] US

Printing date 01/31/2018

Reviewed on 01/31/2018

Trade name: Isopropanol / Water 10:6 v/v

	(Contd. of page 9
Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concer	rning the Internationa
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flam. Liq. 2: Flammable liquids – Category 2	
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	