

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

1 Identification

- **Product identifier**
- **Trade name:** Acrylic Acid 99.5%
- **Article number:** A1837
- **CAS Number:**
79-10-7
- **EC number:**
201-177-9
- **Index number:**
607-061-00-8
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

- **Label elements**

- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard statements**

Flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use foam to extinguish.

Collect spillage.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to landfill

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
79-10-7 Acrylic Acid
- **Identification number(s)**
- **EC number:** 201-177-9
- **Index number:** 607-061-00-8

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 3)

- Use neutralizing agent.
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**
- **PAC-1:** 1.5 ppm
- **PAC-2:** 46 ppm
- **PAC-3:** 180 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

CAS: 79-10-7 Acrylic Acid

REL	Long-term value: 6 mg/m ³ , 2 ppm Skin
TLV	Long-term value: 5.9 mg/m ³ , 2 ppm Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- **Breathing equipment:**
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 4)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Fluid
Color:	Colorless
Odor:	Pungent
Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range:	13 °C (55 °F)
Boiling point/Boiling range:	141 °C (286 °F)

· **Flash point:** 54 °C (129 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 374 °C (705 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Not determined.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	5.3 Vol %
Upper:	26 Vol %

· **Vapor pressure at 20 °C (68 °F):** 4.3 hPa (3 mm Hg)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 5)

- | | |
|------------------------------------|--|
| · Density at 20 °C (68 °F): | 1.0511 g/cm ³ (8.771 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |

- | | |
|--|-----------------|
| · Solubility in / Miscibility with Water: | Fully miscible. |
|--|-----------------|

- | | |
|---|-----------------|
| · Partition coefficient (n-octanol/water): | Not determined. |
|---|-----------------|

- | | |
|----------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

Oral	LD50	250 mg/kg (rat)
Dermal	LD50	280 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)** 3
- **NTP (National Toxicology Program)** Substance is not listed.
- **OSHA-Ca (Occupational Safety & Health Administration)** Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%





(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Assessment by list): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*
- **Recommended cleansing agent:** *Water, if necessary with cleansing agents.*

14 Transport information

- | | |
|---|--------------------------|
| UN-Number | UN2218 |
| DOT, IMDG, IATA | |
| UN proper shipping name | Acrylic acid, stabilized |
| DOT | ACRYLIC ACID, STABILIZED |
| IMDG, IATA | |
| Transport hazard class(es) | |
| DOT | |
|   | |
| Class | 8 Corrosive substances |
| Label | 8, 3 |
| <hr style="border-top: 1px dashed #ccc;"/> | |
| IMDG | |
|   | |
| Class | 8 Corrosive substances |

(Contd. on page 8)

Safety Data Sheet


acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 7)

· Label	8/3
· IATA	
	
· Class	8 Corrosive substances
· Label	8 (3)
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Environmentally hazardous substance, liquid
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	839
· EMS Number:	F-E,S-C
· Segregation groups	Acids
· Stowage Category	E
· Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· Hazardous substance:	5000 lbs, 2270 kg
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2218 ACRYLIC ACID, STABILIZED, 8 (3), II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):** Substance is not listed.
- **Section 313 (Specific toxic chemical listings):** Substance is listed.
- **TSCA (Toxic Substances Control Act):** Substance is listed.
- **Proposition 65**
- **Chemicals known to cause cancer:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for females:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for males:** Substance is not listed.
- **Chemicals known to cause developmental toxicity:** Substance is not listed.
- **Carcinogenic categories**
- **EPA (Environmental Protection Agency)** Substance is not listed.

(Contd. on page 9)

-US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 8)

- **TLV (Threshold Limit Value established by ACGIH) A4**
- **NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.**
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS05 GHS07

- **Signal word** *Danger*
- **Hazard statements**
 - Flammable liquid and vapor.*
 - Harmful if swallowed, in contact with skin or if inhaled.*
 - Causes severe skin burns and eye damage.*
- **Precautionary statements**
 - Keep away from heat/sparks/open flames/hot surfaces. No smoking.*
 - Ground/bond container and receiving equipment.*
 - Use explosion-proof electrical/ventilating/lighting/equipment.*
 - Use only non-sparking tools.*
 - Take precautionary measures against static discharge.*
 - Avoid breathing dust/fume/gas/mist/vapors/spray*
 - Wash thoroughly after handling.*
 - Do not eat, drink or smoke when using this product.*
 - Use only outdoors or in a well-ventilated area.*
 - Avoid release to the environment.*
 - Wear protective gloves/protective clothing/eye protection/face protection.*
 - IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.*
 - If swallowed: Rinse mouth. Do NOT induce vomiting.*
 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.*
 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
 - Immediately call a POISON CENTER/doctor.*
 - Specific treatment (see on this label).*
 - Wash contaminated clothing before reuse.*
 - In case of fire: Usefoam to extinguish.*
 - Collect spillage.*
 - Store in a well-ventilated place. Keep container tightly closed.*
 - Store in a well-ventilated place. Keep cool.*
 - Store locked up.*
 - Dispose of contents/container to landfill*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** *Environment protection department.*
- **Contact:**
- **Date of preparation / last revision**
 - 09-29-2017: review SDS for accuracy. STN*
 - Creation date for SDS 10-07-2014. STN*

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/29/2017

Reviewed on 09/29/2017

Trade name: Acrylic Acid 99.5%

(Contd. of page 9)

09/29/2017 / -

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

US