Printing date 07/01/2024

*

Reviewed on 07/01/2024

Product identifier Trade name: <u>Dibutylamine / Methanol</u>	
<u>1:9 V/V</u> Article number: BAS301	
Details of the supplier of the safety data sheet Manufacturer/Supplier:	
Aqua Solutions, Inc.	
6913 Highway 225 DEER PARK, TX 77536	SOLUTIONS
USA	
800-256-2586	
· Information department:	
Technical Coordinator Sherman Nelson shermann@aquasolutions.org	
· Emergency telephone number:	
Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
P Hazard(s) identification	
· Classification of the substance or mixture	
GHS02 Flame	
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
GHS06 Skull and crossbones	
Acute Toxicity - Oral 3	H301 Toxic if swallowed.
Acute Toxicity - Dermal 3	H311 Toxic in contact with skin.
Acute Toxicity - Inhalation 3	H331 Toxic if inhaled.
\mathbf{A}	
GHS08 Health hazard	
Specific Target Organ Toxicity - Single Exposure 1	H370 Causes damage to the central nervous system and th visual organs.
∧	· · · · · · · · · · · · · · · · · · ·
GHS05 Corrosion	
	H214 Causes severe skin hume and me damage
Skin Corrosion 1A	H314 Causes severe skin burns and eve damage.
\checkmark	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

(Contd. of page 1)



Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

(Contd. of page 2)

90.36%

9.64%

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 67-56-1 Methanol

CAS: 111-92-2 Dibutylamine

4 First-aid measures

· Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.
- Remove breathing apparatus only after contaminated clothing have been completely removed.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation:
- Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; immediately call for medical help.

- Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.*

(Contd. on page 4)

US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol	
1:9 V/V	

 Methods and m Absorb with liq Use neutralizing Dispose contam Ensure adequat Reference to ot See Section 7 for See Section 8 for See Section 13 j 	inated material as waste according to section 13. e ventilation.	(Contd. of page 3)
CAS: 67-56-1	Methanol	530 ppm
CAS: 111-92-2	Dibutylamine	0.45 ppm
· PAC-2:		
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 111-92-2	Dibutylamine	5 ppm
· PAC-3:		
CAS: 67-56-1	Methanol	7200* ppm
CAS: 111-92-2	Dibutylamine	21 ppm

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

	(Contd. of page 4
· Contro	ol parameters
· Compo	onents with limit values that require monitoring at the workplace:
CAS: 6	67-56-1 Methanol
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEIc
CAS:	111-92-2 Dibutylamine
WEEL	Ceiling limit value: 5 ppm Skin
· Ingred	lients with biological limit values:
-	67-56-1 Methanol
	5 mg/L
	D50 Intraperitoneal: urine
	ime: end of shift
	D50: Methanol (background, nonspecific)
	onal information: The lists that were valid during the creation were used as basis.
• Person • Genero Keep a	ure controls al protective equipment: al protective and hygienic measures: way from foodstuffs, beverages and feed. liately remove all soiled and contaminated clothing.
Wash l Store p	hands before breaks and at the end of work. protective clothing separately. contact with the eyes.
	contact with the eyes and skin.
• Breath In case respire	ting equipment: e of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use atory protective device that is independent of circulating air. tion of hands:
	Protective gloves
Due to	ove material has to be impermeable and resistant to the product/ the substance/ the preparation. missing tests no recommendation to the glove material can be given for the product/ the preparation/ the cal mixture.
• Materi	on of the glove material on consideration of the penetration times, rates of diffusion and the degradation ial of gloves
varies _. the glo	lection of the suitable gloves does not only depend on the material, but also on further marks of quality and from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of we material can not be calculated in advance and has therefore to be checked prior to the application. Fation time of glove material
	act break through time has to be found out by the manufacturer of the protective gloves and has to be
	(Contd. on page 6

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

(Contd. of page 5)

• Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and of a second secon	chemical properties
General Information	
Appearance: Form:	Liquid
Color:	Clear
Odor:	Strong
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	260 °C (500 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F):	0.78835 g/cm ³ (6.57878 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol	
1:9 V/V	

		(Contd. of page 6
· Solvent content:		
Organic solvents:	90.4 %	
VOC content:	90.36 %	
	712.3 g/l / 5.94 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)OralLD50108 mg/kgDermalLD50300 mg/kgInhalativeLC50/4h2.02 mg/l

· Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

• on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

- Corrosive
- Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

 · IARC (International Agency for Research on Cancer)

 None of the ingredients is listed.

 · NTP (National Toxicology Program)

 None of the ingredients is listed.

(Contd. on page 8)

US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

DOT, IMDG, IATA	UN2924
· UN proper shipping name · DOT · IMDG, IATA	Flammable liquids, corrosive, n.o.s. (Methanol, Dibutylamine) FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methano Dibutylamine)
• Transport hazard class(es)	
DOT	
TRAMABLE LOUD 3 8	
· Class	3 Flammable liquids
	(Contd. on page

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

	(Contd. of page
Label	3, 8
IMDG	
Class	3 Flammable liquids
Label	3/8
IATA	
Class	3 Flammable liquids
Label	3 (8)
Packing group DOT, IMDG, IATA	Ш
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	338
EMS Number:	F-E,S-C
Stowage Category	
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 5 L
IMDG	17
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per unter packaging: 50 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O. (METHANOL, DIBUTYLAMINE), 3 (8), II

15 Regulatory information

*

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 10)

US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

a tion 355 (extremely hazardous substances): ne of the ingredients is listed. tion 313 (Specific toxic chemical listings): S: 67-56-1 Methanol	
ne of the ingredients is listed. tion 313 (Specific toxic chemical listings):	
tion 313 (Specific toxic chemical listings):	
CA (Toxic Substances Control Act):	
thanol	ACTIVE
putylamine	ACTIVE
zardous Air Pollutants	
S: 67-56-1 Methanol	
position 65	
emicals known to cause cancer:	
ne of the ingredients is listed.	
emicals known to cause reproductive toxicity for females:	
ne of the ingredients is listed.	
emicals known to cause reproductive toxicity for males:	
ne of the ingredients is listed.	
emicals known to cause developmental toxicity:	
S: 67-56-1 Methanol	
rcinogenic categories	
A (Environmental Protection Agency)	
ne of the ingredients is listed.	

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Methanol Dibutylamine
Hazard statements Highly flammable liquid and vapor. Toxic if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage. Causes damage to the central nervous system and the visual organs.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.

(Contd. on page 11)

[–] US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

(Contd. of page 10) Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed: Call a POISON CENTER or doctor/physician. Call a poison center/doctor if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: • Date of preparation / last revision Revision 1.2 07/01/2024: Reviewed SDS for accuracy. MH/STN Creation date for SDS 10-17-2016. STN 07/01/2024 / 1.0 • Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit

(Contd. on page 12)

US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Dibutylamine / Methanol 1:9 V/V

(Contd. of page 11)

US

Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Oral 3: Acute toxicity – Category 3 Skin Corrosion 1A: Skin corrosion/irritation – Category 1A Eye Damage 1: Serious eye damage/eye irritation – Category 1 Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1 • * Data compared to the previous version altered.