Printing date 07/01/2024

Reviewed on 07/01/2024

• Trade name: <u>Low Water IPA - Toluene</u> 50:50 v/v Mix	
• Article number: BAS310	
• Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	AQUA SOLUTIONS
• Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org • Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	
P Hazard(s) identification	
GHS02 Flame Flammable Liquids 2	H225 Highly flammable liquid and vapor.
GHS08 Health hazard	
GHS08 Health hazard	
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure.
Toxic to Reproduction 2	
Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to organs through prolonged or repeated exposure.
Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1	H373 May cause damage to organs through prolonged or repeated exposure.
Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07	H373 May cause damage to organs through prolonged or repeated exposure.H304 May be fatal if swallowed and enters airways.
Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07 Skin Irritation 2	 H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.

GHS02 GHS07 GHS08

(Contd. on page 2)

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name:	Low	Water IPA	- Toluene
	50:5	0 v/v Mix	

Signal word Danger	(Contd. of page 1)
Hazard-determining components of labeling:	
Toluene	
Isopropanol	
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present an	id easy to do.
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 2	
$\frac{3}{Fire = 3}$	
$\frac{2}{Reactivity} = 0$	
HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 3 Fire = 3	
REACTIVITY 0 Reactivity = 0	
()	Contd. on page 3)

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

0	*	
CAS: 108-88-3	Toluene	52.477%
CAS: 67-63-0	Isopropanol	47.523%

4 First-aid measures

· Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.*
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

Ensure adequat Reference to oth See Section 7 fo See Section 8 fo See Section 13 f		(Contd. of page 3)	
· PAC-1:			
CAS: 108-88-3	Toluene	67 ppm	
CAS: 67-63-0	Isopropanol	400 ppm	
· PAC-2:			
CAS: 108-88-3	Toluene	560 ppm	
CAS: 67-63-0	Isopropanol	2000* ppm	
· PAC-3:			
CAS: 108-88-3	Toluene	3700* ppm	
CAS: 67-63-0	Isopropanol	12000** ppm	

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 108-88-3 Toluene

PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift

(Contd. on page 5)

US -

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name:	Low	Water IPA	- Toluene
	50:5	0 v/v Mix	

REL Short-erm value: 500 mg/m², 100 ppm Long-term value: 375 mg/m², 100 ppm BEL OTO, A4 CAS: 67-630 bspropanol PEL Long-term value: 200 ppm BEL Short-term value: 1225 mg/m², 400 ppm Long-term value: 200 mg/m², 400 ppm Long-term value: 400 ppm Long-term value: 400 ppm Long-term value: 200 ppm BEL OtoT-term value: 400 ppm Long-term value: 200 ppm BEL OtoT-term value: 200 ppm BEL OtoZ mg/L LD50 D10 Intraperitoneal: blood Time: end of shift LD50: Toluene 0.03 mg/L LD50: Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/L creatinine LD50: Toluene D40 mg/L LD50: Intraperitoneal: ur		(Contd. of page 4)
TLV Long-term value: 20 ppm BEI, OTO, A4 CAS: 67-30-Dspropanol PEL Long-term value: 1225 mg/m ² , 400 ppm Long-term value: 1225 mg/m ² , 500 ppm Long-term value: 200 ppm BEI, A4 • Ingredients with biological limit values: CAS: 108-88-3 Tolenee BEI (0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50 Intraperitoneal: urine Time: prior to last shift of workweek LD50 Intraperitoneal: urine Time: prior to last shift of workweek LD50: Toluene 0.3 mg/L LD50: or Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI Additional information: The lists that were valid during the creation were used as basis. Exposure controls • Personal protective equipment: • General protective and skift. • Statist show ex and skift. • Statist show ex and skift. • Statist show ex and skift. • Time: and of skift show ex and skift. • Time: and of skift show exet was and end of workweek LD50: Acetone (background, nonspecific)	REL	Short-term value: 560 mg/m ³ , 150 ppm
BEL OTO, A4 CAS: 67-63-0 Isopropanol FEL Long-term value: 980 mg/m ² , 400 ppm Long-term value: 980 mg/m ² , 400 ppm Long-term value: 200 ppm BEL, A4 • Ingredients with biological limit values: CAS: 108-88-3 Toluene BEL D50 Intraperioneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperioneal: urine Time: prior to last shift of workweek LD50: Toluene 0.3 mg/L LD50 Intraperioneal: urine Time: end of shift LD50: or Could and the operation of the and operation of the analytic operation opera		
PEL Long-term value: 1225 mg/m², 400 ppm REL Short-term value: 280 mg/m², 400 ppm Long-term value: 800 mg/m², 400 ppm DER_term value: 200 ppm BEL A4 • Ingredients with biological limit values: CAS: 108-88-3 Toluene BEL 0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50. Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50. Toluene 0.3 mg/c creatinine LD50 Intraperitoneal: urine Time: end of shift LD50. Toluene 0.3 mg/c preatinine LD50 Intraperitoneal: urine Time: end of shift LD50. Intraperitoneal: urine Time: end of shift LD50. Intraperitoneal: urine Time: end of shift at end of workweek LD50. Intraperitoneal: urine Time: end of shift at end of workweek LD50. Intraperitoneal: urine Time: end of shift at end of workweek LD50. Intraperitoneal: urine Time: end of shift end vorkweek LD50. Intraperitoneal: urine<	TLV	
REL Short-term value: 1225 mg/m², 400 ppm Long-term value: 200 ppm Long-term value: 400 ppm TIV Short-term value: 200 ppm BEI, A4 - Ingredients with biological limit values: CAS: 108-88-3 Toluene BEI 0.02 mg/L LD50 Intraperitoneal: blood Time; prior to last shift of workweek LD50: Toluene 0.03 mg/L D.03 Intraperitoneal: urine Time; end of shift LD50: Toluene 0.3 mg/g creatinine LD50: Toluene 0.3 mg/L O.3 mg/L D50: Toluene 0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/b creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Orceresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Aceteon (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls Personal protective and hygienic measures: * eeg away from foodstiffs, beverages and feed. <t< td=""><td>CAS</td><td>: 67-63-0 Isopropanol</td></t<>	CAS	: 67-63-0 Isopropanol
Long-term value: 980 mg/m ³ , 400 ppm TUV Short-term value: 200 ppm BEI. A4 • Ingredients with biological limit values: CAS: 108-88-3 Toluene BEI (0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/L creatinine LD50: Intraperitoneal: urine Time: end of shift LD50: acterone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • Concertive clothing separately. • Avoid contact with the eyes and skin. • Breathing equipment In case of birde sposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Protective gloves	PEL	Long-term value: 980 mg/m ³ , 400 ppm
Long-term value: 980 mg/m ³ , 400 ppm TUV Short-term value: 200 ppm BEI. A4 • Ingredients with biological limit values: CAS: 108-88-3 Toluene BEI (0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/L creatinine LD50: Intraperitoneal: urine Time: end of shift LD50: acterone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • Concertive clothing separately. • Avoid contact with the eyes and skin. • Breathing equipment In case of birde sposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Protective gloves	REL	Short-term value: 1225 mg/m ³ , 500 ppm
Long-term value: 200 ppm BEL A4 • Ingredients with biological limit values: CAS: 108-88-3 Toluene BEI 0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/L creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50. Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipme		
BEI, A4 Ingredients with biological limit values: CAS: 108-88-3 Toluene BEI 0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L DD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/L 0.3 mg/L rescalation 0.3 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50 intraperitoneal: urine Time: end of shift LD50 i. o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 i. accresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 i. accresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 i. Accresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 i. Accresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 i. Accresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 i. Accresol with reperitoneal: urine	TLV	Short-term value: 400 ppm
 Ingredients with biological limit values: CAS: 108-88-3 Toluene BEI 0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/g creatinine LD50: Toluene 0.3 mg/g creatinine LD50: or-Cressol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50: Intraperitoneal: urine Time: end of shift at end of workweek LD50: or-Cressol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50: Action (background, nonspecific) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective and hyginic measures: Keep away from foodstuff, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective colhing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: 		
CAS: 108-88-3 Toluene BEI 0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/g creatinine LD50: Toluene 0.3 mg/g creatinine LD50: Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI BEI Vang/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Accetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.		BEI, A4
BEI 0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/g creatinine LD50: Intraperitoneal: urine Time: end of shift LD50: top retainine LD50: top retaine D50: top retaine D50: top retaine LD50: top retaine LD50: top retaine LD50: top retaine LD50: hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Actional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective end hygienic measures: Keep away from foodstuffs, beverages and feed. <td>-</td> <td>÷</td>	-	÷
LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50. Toluene 0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: no-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acctone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protective gloves		
Time: prior to last shift of workweek LD50: Toluene 0.03 mg/L LD50: Toluene 0.3 mg/L LD50: Toluene 0.3 mg/g creatinine LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breads and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.	BEI	•
LD50: Toluene 0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50. Toluene 0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50. Acteone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective end hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: <i>Protective gloves</i>		
 0.03 mg/L LD50 Intraperioneal: wine Time: end of shift LD50: Toluene 0.3 mg/g creatinine LD50 Intraperioneal: wine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperioneal: wine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protective gloves 		
LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: · General protective equipment: · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Frotective gloves		
Time: end of shift LDS0: Toluene 0.3 mg/g creatinine LDS0 Intraperitoneal: urine Time: end of shift LDS0: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LDS0 Intraperitoneal: urine Time: end of shift at end of workweek LDS0: Acctone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Work Protective gloves		0.03 mg/L
LD50: Toluene 0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: -Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Wrote clour of planes:		
0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: c-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acctone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and containiated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Wroterion of hands:		
LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: \mathcal{V}		LD30: Toluene
LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: \mathcal{V}		0.3 mg/g creatinine
LD50: o-Cresol with hydrolysis (background) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Work Protective gloves		
CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acctone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: View Protective gloves		
 BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Wrotective gloves 		
LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Wrotective gloves		
Time: end of shift at end of workweek LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: • Protective gloves	BEI	
LD50: Acetone (background, nonspecific) • Additional information: The lists that were valid during the creation were used as basis. • Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Wrotective gloves		
 Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves 		
 Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves 	· Addi	
 Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves 		
 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves	-	
Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves		
 Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: 	Keep	away from foodstuffs, beverages and feed.
 Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves 		
 Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves 		
 Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves 		
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands: Protective gloves		
Protective gloves		
Protective gloves		
	· Prote	ection of hands:
	ſ	ή
	- Ini.	Protective gloves
(Contra on poor 6)		
(Conta. on page 6)		(Contd. on page 6)

US US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	chemical properties
General Information Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Organic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C (179.6 °F)
Flash point:	4 °C (39.2 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	12 Vol %
Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
Density at 20 °C (68 °F):	0.82591 g/cm ³ (6.89222 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

		(Contd. of page 6
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	825.9 g/l / 6.89 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

All components have the value 3.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 8)

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT	Flammable liquids, n.o.s. (Toluene, Isopropanol
IMDG, IATA) FLAMMABLE LIQUID, N.O.S. (Toluene, Isopropanol)
Transport hazard class(es)	
DOT	
RAMMARE LOOD	
Class	3 Flammable liquids

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

	(Contd. of page
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code) EMS Number:	: 33 F-E,S-E
Stowage Category	B
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUEN)
	ISOPROPANOL
), 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
Toluene	ACTIVE
Isopropanol	ACTIVE
(Conto	l. on page 10)

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

(Contd. of page 9)

II

· Hazardous Air Pollutants

CAS: 108-88-3 Toluene

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 108-88-3 Toluene

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 108-88-3 Toluene

· TLV (Threshold Limit Value)

All components have the value A4.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Toluene Isopropanol · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 11)

⁻ US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

(Contd. of page 10)

Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. *Call a poison center/doctor if you feel unwell.* Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2 07/01/2024: Reviewed SDS for accuracy. MH/STN

Creation date for SDS 10-17-2016. STN 07/01/2024 / 1.0 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 12)

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Low Water IPA - Toluene 50:50 v/v Mix

(Contd. of page 11)

US

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 Aspiration Hazard 1: Aspiration hazard – Category 1 • * Data compared to the previous version altered.