

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

1 Identification

- **Product identifier**
- **Trade name:** Chloroacetic Acid, 99% flake
- **Article number:** C3595
- **CAS Number:**
79-11-8
- **EC number:**
201-178-4
- **Index number:**
607-003-00-1
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS06 Skull and crossbones

Acute Toxicity - Oral 3 H301 Toxic if swallowed.
 Acute Toxicity - Dermal 3 H311 Toxic in contact with skin.
 Acute Toxicity - Inhalation 1 H330 Fatal if inhaled.



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.
 Eye Damage 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS06

- **Signal word** *Danger*
- **Hazard statements**
Toxic if swallowed or in contact with skin.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 1)

Fatal if inhaled.

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Immediately call a poison center/doctor.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Wash contaminated clothing before reuse.

Collect spillage.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3

Fire = 1

Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

* 3 Composition/information on ingredients

· Chemical characterization: Substances

· CAS No. Description

CAS: 79-11-8 Chloroacetic Acid 99%

· Identification number(s)

· EC number: 201-178-4

· Index number: 607-003-00-1

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 2)

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: *Immediately wash with water and soap and rinse thoroughly.*

· After eye contact: *Rinse opened eye for several minutes under running water. Then consult a doctor.*

· After swallowing:

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed *No further relevant information available.*

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: *Use fire fighting measures that suit the environment.*

· Special hazards arising from the substance or mixture *No further relevant information available.*

· Advice for firefighters

· Protective equipment: *Mouth respiratory protective device.*

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: *Do not allow to enter sewers/ surface or ground water.*

· Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1: *1.5 ppm*

· PAC-2: *6.6 ppm*

· PAC-3: *15 ppm*

7 Handling and storage

· Handling:

· Precautions for safe handling

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires: *Keep respiratory protective device available.*

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

CAS: 79-11-8 Chloroacetic Acid 99%

TLV	Long-term value: 0.5* ppm Skin;*as inhalable fraction and vapor, A4
WEEL	Long-term value: 0.5 ppm Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Crystalline
· Color:	White
· Odor:	Pungent
· Odor threshold:	Not determined.

· pH-value: <1

· Change in condition

· Melting point/Melting range:	62 °C (143.6 °F)
· Boiling point/Boiling range:	189 °C (372.2 °F)

· Flash point: 126 °C (258.8 °F)

· Flammability (solid, gaseous): Product is not flammable.

· Auto igniting: 470 °C (878 °F)

· Decomposition temperature: Not determined.

· Ignition temperature: Not determined.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

· Lower:	8 Vol %
· Upper:	Not determined.

· Vapor pressure at 20 °C (68 °F): 0.2 hPa

· Vapor pressure at 50 °C (122 °F): 2 hPa (1.5 mm Hg)

· Density at 20 °C (68 °F): 1.58 g/cm³ (13.1851 lbs/gal)

· Bulk density:	1 kg/m ³
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.

· Solubility in / Miscibility with

Water at 20 °C (68 °F): 4210 g/l

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

· Dynamic:	Not applicable.
· Kinematic:	Not applicable.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 5)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4h	0.005 mg/l (ATE)

· **Primary irritant effect:**

· **on the skin:** Caustic effect on skin and mucous membranes.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)** Substance is not listed.

· **NTP (National Toxicology Program)** Substance is not listed.

· **OSHA-Ca (Occupational Safety & Health Administration)** Substance is not listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Assessment by list): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 6)

Danger to drinking water if even extremely small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN1751

· **UN proper shipping name**

· **DOT**

Chloroacetic acid, solid

· **IMDG, IATA**

CHLOROACETIC ACID, SOLID

· **Transport hazard class(es)**

· **DOT**



· **Class**

6.1 Toxic substances

· **Label**

6.1, 8

· **IMDG**



· **Class**

6.1 Toxic substances

· **Label**

6.1/8

· **IATA**



· **Class**

6.1 Toxic substances

· **Label**

6.1 (8)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 7)

· Packing group · DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	Environmentally hazardous substance, solid No Symbol (fish and tree)
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Segregation groups · Stowage Category · Stowage Code · Segregation Code	Warning: Toxic substances 68 F-A,S-B (SGG1) Acids C SW2 Clear of living quarters. SG36 Stow "separated from" SGG18-alkalis. SG49 Stow "separated from" SGG6-cyanides
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations · Hazardous substance: · Remarks:	 On passenger aircraft/rail: 15 kg On cargo aircraft only: 50 kg 100 lbs, 45.4 kg flüssig: UN 1750
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · Remarks:	500 g Code: E4 Maximum net quantity per inner packaging: 1 g Maximum net quantity per outer packaging: 500 g flüssig: UN 1750
· UN "Model Regulation":	UN 1751 CHLOROACETIC ACID, SOLID, 6.1 (8), II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**
- **Section 355 (extremely hazardous substances):** Substance is listed.
- **Section 313 (Specific toxic chemical listings):** Substance is listed.
- **TSCA (Toxic Substances Control Act):** ACTIVE
- **Hazardous Air Pollutants** Substance is listed.
- **Proposition 65**
- **Chemicals known to cause cancer:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for females:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for males:** Substance is not listed.
- **Chemicals known to cause developmental toxicity:** Substance is not listed.
- **Carcinogenic categories**
- **EPA (Environmental Protection Agency)** Substance is not listed.
- **TLV (Threshold Limit Value) A4**
- **NIOSH-Ca (National Institute for Occupational Safety and Health)** Substance is not listed.
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 8)

· **Hazard pictograms**



GHS05 GHS06

· **Signal word** *Danger*

· **Hazard statements**

Toxic if swallowed or in contact with skin.

Fatal if inhaled.

Causes severe skin burns and eye damage.

· **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Immediately call a poison center/doctor.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Wash contaminated clothing before reuse.

Collect spillage.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** *Environment protection department.*

· **Contact:**

Date of Preparation / Last Revision:

· **Date of preparation / last revision**

Revision 1.2 07/03/2024: Reviewed SDS for accuracy. MH/STN

07/03/2024 / 1.0

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/03/2024

Reviewed on 07/03/2024

Trade name: Chloroacetic Acid, 99% flake

(Contd. of page 9)

*OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Acute Toxicity - Oral 3: Acute toxicity – Category 3**Acute Toxicity - Inhalation 1: Acute toxicity – Category 1**Skin Corrosion 1B: Skin corrosion/irritation – Category 1B**Eye Damage 1: Serious eye damage/eye irritation – Category 1***· * Data compared to the previous version altered.**

US