Printing date 01/06/2025 Reviewed on 01/06/2025

#### 1 Identification

· Product identifier

· Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

· Article number: E2438

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.

Toxic to Reproduction 1A H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 2 H371 May cause damage to the central nervous system and the visual organs.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

n-Heptane

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

Methanol

· Hazard statements

Highly flammable liquid and vapor.

Suspected of causing cancer.

(Contd. on page 2)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 1)

May damage fertility or the unborn child.

May cause damage to the central nervous system and the visual organs.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 3Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous con	ponents:	
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	92.904%
CAS: 67-56-1	Methanol	4.05%
CAS: 141-78-6	Ethyl Acetate	1.151%
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	1.025%
CAS: 142-82-5	n-Heptane	0.87%

-US

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 2)

#### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

2 . 0 . 0	ion erneruifor enemicuns	
· PAC-1:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 141-78-0	5 Ethyl Acetate	1,200 ppm
CAS: 108-10-	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	75 ppm
CAS: 142-82-	5 n-Heptane	500 ppm
	·	(Contd. on page 4)

US

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

<i>PAC-2:</i>		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 141-78-6	Ethyl Acetate	1,700 ppm
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	500 ppm
CAS: 142-82-5	n-Heptane	830 ppm
<i>PAC-3:</i>		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 141-78-6	Ethyl Acetate	10000** ppn
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	3000* ppm
CAS: 142-82-5	n-Heptane	5000* ppm

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

Colon of parameters
· Components with limit values that require monitoring at the workplace:
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof
PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1000 ppm A3

(Contd. on page 5)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

CAS	(Contd. of page : 67-56-1 Methanol
	Long-term value: 260 mg/m³, 200 ppm
	•
KEL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm
	Skin
TIV	Short-term value: 250 ppm
ILV	Long-term value: 200 ppm
	Skin; BEIc
CAS:	: 141-78-6 Ethyl Acetate
PEL	Long-term value: 1400 mg/m³, 400 ppm
REL	Long-term value: 1400 mg/m³, 400 ppm
	Long-term value: 400 ppm
	: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
	Long-term value: 410 mg/m³, 100 ppm
	Short-term value: 300 mg/m³, 75 ppm
	Long-term value: 205 mg/m³, 50 ppm
TLV	Short-term value: 75 ppm
	Long-term value: 20 ppm
	BEI, A3
CAS:	: 142-82-5 n-Heptane
PEL	Long-term value: 2000 mg/m³, 500 ppm
REL	Long-term value: 350 mg/m³, 85 ppm
	Ceiling limit value: 1800* mg/m³, 440* ppm
	*15-min
TLV	Short-term value: 500 ppm
	Long-term value: 400 ppm
_	edients with biological limit values:
	: 67-56-1 Methanol
	15 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Methanol (background, nonspecific)
	: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
	1 mg/L LD50 Intraperitoneal: urine
	LD30 Intrapertioneal: urine Time: end of shift
	LD50: MIBK
	tional information: The lists that were valid during the creation were used as basis.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 6)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 5)

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

#### 9 Physical and chemical properties

· 11	nformat	ion on	basic pi	hysical	and c	hemical	l properi	ties
------	---------	--------	----------	---------	-------	---------	-----------	------

· General Information

· Appearance:

· pH-value:

· Auto igniting:

Form: Liquid
Color: Clear
Odor: Acidic

· Odor threshold: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:78 °C (172.4 °F)

• Flash point: 13 °C (55.4 °F)

· Flammability: Highly flammable.

· Decomposition temperature: Not determined.

• Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Not determined.

425 °C (797 °F)

(Contd. on page 7)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

		(Contd. of pag
· Explosion limits:		
Lower:	3.5 Vol %	
Upper:	19 Vol %	
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)	
· Density at 20 °C (68 °F):	0.78166 g/cm³ (6.52295 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e <b>r</b> ): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	781.7 g/l / 6.52 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

### ATE (Acute Toxicity Estimate)

Oral	LD50	2,469 mg/kg
Dermal		7,407 mg/kg
Inhalative		

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 8)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 7)

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (Internat	tional Agency for Research on Cancer)	
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	2B
· NTP (National	Toxicology Program)	
None of the ing	redients is listed.	
· OSHA-Ca (Occ	cupational Safety & Health Administration)	
None of the ing	redients is listed.	

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
· UN-Number · DOT, IMDG, IATA	UN1170
· UN proper shipping name	
$\cdot DOT$	Ethanol solutions
$\cdot$ IMDG	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
$\cdot$ IATA	ETHANOL SOLUTION

(Contd. on page 9)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 8)

· Transport hazard class(es)

 $\cdot DOT$ 



· Class 3 Flammable liquids

· Label

· IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group

· DOT, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-D

· Stowage Category A

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot DOT$ 

• Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

 $\cdot$  *IMDG* 

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per inner packaging: 50 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL

SOLUTION), 3, II

#### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 10)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 9) · Section 313 (Specific toxic chemical listings): CAS: 67-56-1 Methanol CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) · TSCA (Toxic Substances Control Act): Ethyl Alcohol, Absolute 200 Proof **ACTIVE** Methanol **ACTIVE** Ethyl Acetate **ACTIVE** Methyl Isobutyl Ketone (4-Methyl-2-pentanone) **ACTIVE ACTIVE** n-Heptane · Hazardous Air Pollutants CAS: 67-56-1 Methanol CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) · Proposition 65 · Chemicals known to cause cancer: CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof CAS: 67-56-1 Methanol CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) · Carcinogenic categories · EPA (Environmental Protection Agency) CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone) CAS: 142-82-5 n-Heptane D· TLV (Threshold Limit Value) CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof A3· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: n-Heptane Methyl Isobutyl Ketone (4-Methyl-2-pentanone) Methanol

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 10)

#### · Hazard statements

Highly flammable liquid and vapor.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause damage to the central nervous system and the visual organs.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.1, 01-06-2025: Reviewed SDS for accuracy. STN 01/06/2025 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50. Lethal consentent on 50 money

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

(Contd. on page 12)

Printing date 01/06/2025 Reviewed on 01/06/2025

Trade name: Ethyl Alcohol, Denatured

Anhydrous Govt. Formula III, Lab Grade

(Contd. of page 11)

 $Flammable\ Liquids\ 2:\ Flammable\ liquids\ -\ Category\ 2$ 

Carcinogenicity 2: Carcinogenicity – Category 2

Toxic to Reproduction 1A: Reproductive toxicity – Category 1A

Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) – Category 2

\* \* Data compared to the previous version altered.