

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

1 Identification

- **Product identifier**
- **Trade name:** Adherent Insolubles
Solvent ASTM D6468
- **Article number:** ERL257
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Dermal 3

H311 Toxic in contact with skin.

Acute Toxicity - Inhalation 3

H331 Toxic if inhaled.



GHS08 Health hazard

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 1

H370 Causes damage to the central nervous system and the visual organs.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Acute Toxicity - Oral 4

H302 Harmful if swallowed.

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 1)

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

Methanol

Toluene

Acetone

- **Hazard statements**

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system and the visual organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Rinse mouth.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 2)

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 108-88-3	Toluene	35.383%
CAS: 67-56-1	Methanol	32.339%
CAS: 67-64-1	Acetone	32.278%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
 During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

CAS: 108-88-3	Toluene	67 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 67-64-1	Acetone	200 ppm

- **PAC-2:**

CAS: 108-88-3	Toluene	560 ppm
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 67-64-1	Acetone	3200* ppm

- **PAC-3:**

CAS: 108-88-3	Toluene	3700* ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 67-64-1	Acetone	5700* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 4)

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: *Store in a cool location.*

· Information about storage in one common storage facility: *Not required.*

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) *No further relevant information available.*

8 Exposure controls/personal protection

· Additional information about design of technical systems: *No further data; see section 7.*

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 108-88-3 Toluene

PEL Long-term value: 200 ppm
 Ceiling limit value: 300; 500* ppm
 *10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
 BEI, OTO, A4

CAS: 67-56-1 Methanol

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm
 Long-term value: 260 mg/m³, 200 ppm
 Skin

TLV Short-term value: 250 ppm
 Long-term value: 200 ppm
 Skin; BEIc

CAS: 67-64-1 Acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 500 ppm
 Long-term value: 250 ppm
 A4, BEI

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 5)

· Ingredients with biological limit values:

CAS: 108-88-3 Toluene

BEI	0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene
	0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene
	0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background)

CAS: 67-56-1 Methanol

BEI	15 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)
-----	--

CAS: 67-64-1 Acetone

BEI	25 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Acetone (nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 6)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Organic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C (131 °F)

- **Flash point:** -17 °C (1.4 °F)

- **Flammability (solid, gaseous):** Highly flammable.

- **Auto igniting:** 455 °C (851 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	1.2 Vol %
Upper:	44 Vol %

- **Vapor pressure at 20 °C (68 °F):** 233 hPa (174.8 mm Hg)

- **Density at 20 °C (68 °F):** 0.81502 g/cm³ (6.80134 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 7)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	67.72 % 551.9 g/l / 4.61 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)		
Oral	LD50	309 mg/kg
Dermal	LD50	928 mg/kg
Inhalative	LC50/4h	9.28 mg/l

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Toxic
Harmful
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 108-88-3	Toluene	3
---------------	---------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 8)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | <p>UN1993</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA | <p>Flammable liquids, n.o.s. (Acetone, Methanol, Toluene)
 FLAMMABLE LIQUID, N.O.S. (Acetone, Methanol, Toluene)</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | |
| <div style="display: flex; align-items: center; gap: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label | <p>3 Flammable liquids
3</p> |

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 9)

· **IMDG, IATA**

· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**
 · **DOT, IMDG, IATA** II

· **Environmental hazards:**
 · **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids
 · **Hazard identification number (Kemler code):** 33
 · **EMS Number:** F-E, S-E
 · **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **IMDG**
 · **Limited quantities (LQ)** 1L
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, METHANOL, TOLUENE), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 No further relevant information available.

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 108-88-3 | Toluene

CAS: 67-56-1 | Methanol

· **TSCA (Toxic Substances Control Act):**

Toluene

ACTIVE

Methanol

ACTIVE

Acetone

ACTIVE

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 10)

· **Hazardous Air Pollutants**

CAS: 108-88-3 Toluene

CAS: 67-56-1 Methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 108-88-3 Toluene

CAS: 67-56-1 Methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 108-88-3 Toluene

II

CAS: 67-64-1 Acetone

I

· **TLV (Threshold Limit Value)**

CAS: 108-88-3 Toluene

A4

CAS: 67-64-1 Acetone

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS06 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Methanol

Toluene

Acetone

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system and the visual organs.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 11)

· **Precautionary statements**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If swallowed: Immediately call a poison center/doctor.
- Specific treatment (see on this label).
- Do NOT induce vomiting.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- Get medical advice/attention if you feel unwell.
- Rinse mouth.
- Take off immediately all contaminated clothing and wash it before reuse.
- If skin irritation occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- In case of fire: Use CO₂, powder or water spray to extinguish.
- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
Date of Preparation / Last Revision:
- **Date of preparation / last revision**
Revision 1.2, 08-15-2024: Reviewed SDS for accuracy. STN/GW
08/15/2024 / 1.1
- **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 08/15/2024

Reviewed on 08/15/2024

Trade name: Adherent Insolubles
Solvent ASTM D6468

(Contd. of page 12)

*PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Acute Toxicity - Oral 4: Acute toxicity – Category 4**Acute Toxicity - Dermal 3: Acute toxicity – Category 3**Skin Irritation 2: Skin corrosion/irritation – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Toxic to Reproduction 2: Reproductive toxicity – Category 2**Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1**Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2**Aspiration Hazard 1: Aspiration hazard – Category 1**** Data compared to the previous version altered.**

US