Printing date 06/14/2024

Reviewed on 06/14/2024

1 Identification

- · Product identifier
- · Trade name: Hydranal® Solvent
- · Article number: H3428
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc.
- 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586
- Information department: Technical Coordinator
 Sherman Nelson shermann@aquasolutions.org
 Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 2

H225 Highly flammable liquid and vapor.

GHS06 Skull and crossbones

Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3

H301 Toxic if swallowed.H311 Toxic in contact with skin.H331 Toxic if inhaled.

GHS08 Health hazard

Toxic to Reproduction 1BH360 May damage fertility or the unborn child.Specific Target Organ Toxicity - Single Exposure 1H370 Causes damage to the central nervous system and the
visual organs.

GHS05 Corrosion

Skin Corrosion 1B Eye Damage 1 H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.

· Label elements

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

(Contd. of page 1)

US



(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 67-56-1	Methanol	80.0%
CAS: 288-32-4	Imidazole, Certified	13.0%
CAS: 7446-09-5	Sulfur Dioxide	7.0%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

- Remove breathing apparatus only after contaminated clothing have been completely removed.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation:
- Supply fresh air or oxygen; call for doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:
- Do not induce vomiting; immediately call for medical help.
- Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

us –

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

	tions, protective equipment and emergency procedures <i>ry protective device.</i>	
1	equipment. Keep unprotected persons away.	
· Environmental		
Dilute with plent		
	enter sewers/ surface or ground water.	
	tterial for containment and cleaning up:	
	id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing		
	nated material as waste according to section 13.	
Ensure adequate	8	
· Reference to oth		
	information on safe handling.	
	information on personal protection equipment.	
	or disposal information.	
	r Criteria for Chemicals	
· PAC-1:		
CAS: 67-56-1	Methanol	530 ppm
CAS: 288-32-4	Imidazole, Certified	0.66 mg/m ³
CAS: 7446-09-5	Sulfur Dioxide	0.20 ppm
· PAC-2:		
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 288-32-4	Imidazole, Certified	7.3 mg/m ³
CAS: 7446-09-5	Sulfur Dioxide	0.75 ppm
· PAC-3:		
CAS: 67-56-1	Methanol	7200* ppm
CAS: 288-32-4	Imidazole, Certified	44 mg/m ³
CAS: 7446-09-5	Sulfur Dioxide	30 ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

US

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

(Contd. of page 4)

- *Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.*
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
- At this time, the remaining constituent has no known exposure limits.

CAS	: 67-56-1 Methanol
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm
	Long-term value: 260 mg/m ³ , 200 ppm
	Skin
TLV	Short-term value: 250 ppm
	Long-term value: 200 ppm
	Skin; BEIc
CAS	: 7446-09-5 Sulfur Dioxide
PEL	Long-term value: 13 mg/m ³ , 5 ppm
REL	Short-term value: 13 mg/m ³ , 5 ppm
	Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 0.25 ppm
	A4
·Ingr	edients with biological limit values:
CAS	: 67-56-1 Methanol
BEI	15 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Methanol (background, nonspecific)
· Addi	tional information: The lists that were valid during the creation were used as basis.
· Expa	osure controls
	onal protective equipment:
	eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	e protective clothing separately.
	d contact with the eyes.
	d contact with the eyes and skin.
	thing equipment:
	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use iratory protective device that is independent of circulating air.
respi	(Contd. on page 6)
	US

US –

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

· Information on basic physical and	chemical properties
· General Information	
· Appearance: Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. -10 °C (14 °F)
· Flash point:	11 °C (51.8 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	455 °C (851 °F)
• Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

	(Cont	d. of page (
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)	
• Density at 20 °C (68 °F):	0.89 g/cm ³ (7.42705 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	80.0 %	
VOC content:	80.00 %	
	712.0 g/l / 5.94 lb/gal	
Solids content:	13.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

• Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

ATE (Acute Toxicity Estimate)OralLD50121 mg/kg

		101-10
Dermal	LD50	375 mg/kg
Inhalative	LC50/4h	3.75 mg/l

· Primary irritant effect:

• on the skin: Caustic effect on skin and mucous membranes.

 \cdot on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

(Contd. on page 8)

(Contd. of page 7)

3

Safety Data Sheet acc. to OSHA HCS

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 7446-09-5 Sulfur Dioxide

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- \cdot Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN2924
· UN proper shipping name	
-DOT	Flammable liquids, corrosive, n.o.s. (Methanol, Sulfur Dioxid
	Imidazole)

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydi	ranal® Solvent
------------------	----------------

	(Contd. of page
IMDG	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methanol, Sulfu
IATA	Dioxide, Imidazole) FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methanol/Sulfu Dioxide/Imidazole solution)
Transport hazard class(es)	
DOT	
RAMMARE LODOR 3 3	
Class	3 Flammable liquids
Label	3, 8
IMDG	
Class	3 Flammable liquids
Label	3/8
IATA	
Class Label	3 Flammable liquids 3 (8)
Packing group	
DOT, IMDG, IATA	Ι
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code).	: 338
EMS Number:	F-E,S-C
Segregation groups	(SGG18) Alkalis
Stowage Category Stowage Code	E SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	11
DOT Overtity limitations	On passangar giveraft/rail. 0.5 I
Quantity limitations	On passenger aircraft/rail: 0.5 L On cargo aircraft only: 2.5 L
IMDG	
Limited quantities (LQ)	0
	-
	Code: EU
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

(Contd. of page 9)

· UN "Model Regulation":

UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (METHANOL, SULFUR DIOXIDE, IMIDAZOLE), 3 (8), I

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• Sara

Suru		
· Section 355 (ext	remely hazardous substances):	
CAS: 7446-09-5	Sulfur Dioxide	
· Section 313 (Spe	ecific toxic chemical listings):	
CAS: 67-56-1 M	lethanol	
· TSCA (Toxic Su	bstances Control Act):	
Methanol		ACTIVE
Imidazole, Certif	fied	ACTIVE
Sulfur Dioxide		ACTIVE
· Hazardous Air P	Pollutants	
CAS: 67-56-1 M	lethanol	
· Proposition 65		
· Chemicals know	on to cause cancer:	
None of the ingredients is listed.		
· Chemicals know	n to cause reproductive toxicity for females:	
None of the ingredients is listed.		
· Chemicals know	n to cause reproductive toxicity for males:	
None of the ingre	edients is listed.	
· Chemicals know	n to cause developmental toxicity:	
CAS: 67-56-1	Methanol	
CAS: 7446-09-5	Sulfur Dioxide	
· Carcinogenic ca	tegories	

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

CAS: 7446-09-5 Sulfur Dioxide

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 11)

A4

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

	(Contd. of page 10)
· Hazard-determining components of labeling:	
Methanol	
Imidazole, Certified	
Sulfur Dioxide	
· Hazard statements	
Highly flammable liquid and vapor.	
Toxic if swallowed, in contact with skin or if inhaled.	
Causes severe skin burns and eye damage.	
May damage fertility or the unborn child.	
Causes damage to the central nervous system and the visual organs.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dusts or mists.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
If swallowed: Rinse mouth. Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/showed	r.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen	t and easy to do.
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Take off immediately all contaminated clothing and wash it before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	ns.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of Preparation / Last Revision:
- Date of preparation / last revision Revision 0.1, 06/14/2024: Reviewed SDS for accuracy. MH/STN 06/14/2024 / 1.0
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 12)

Printing date 06/14/2024

Reviewed on 06/14/2024

Trade name: Hydranal® Solvent

	(Contd. of page 11)
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 2: Flammable liquids – Category 2	
Acute Toxicity - Oral 3: Acute toxicity – Category 3	
Skin Corrosion 1B: Skin corrosion/irritation – Category 1B	
Eye Damage 1: Serious eye damage/eye irritation – Category 1	
Toxic to Reproduction 1B: Reproductive toxicity – Category 1B	
Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1	
* Data compared to the previous version altered.	
	US