

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

1 Identification

- **Product identifier**
- **Trade name:** Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v
- **Article number:** LEI012
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Dermal 3

H311 Toxic in contact with skin.



GHS07

Acute Toxicity - Oral 4

H302 Harmful if swallowed.

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS06



GHS07

- **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Cyclohexanone 99.8%
Methyl Ethyl Ketone

· **Hazard statements**

Flammable liquid and vapor.
Harmful if swallowed or if inhaled.
Toxic in contact with skin.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
Rinse mouth.
Specific treatment (see on this label).
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off immediately all contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 2
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 108-94-1	Cyclohexanone 99.8%	73.335%
CAS: 78-93-3	Methyl Ethyl Ketone	26.665%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

**Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v**

(Contd. of page 3)

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 108-94-1	Cyclohexanone 99.8%	60 ppm
CAS: 78-93-3	Methyl Ethyl Ketone	200 ppm

· **PAC-2:**

CAS: 108-94-1	Cyclohexanone 99.8%	830 ppm
CAS: 78-93-3	Methyl Ethyl Ketone	2700* ppm

· **PAC-3:**

CAS: 108-94-1	Cyclohexanone 99.8%	5000* ppm
CAS: 78-93-3	Methyl Ethyl Ketone	4000* ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 108-94-1 Cyclohexanone 99.8%	
PEL	Long-term value: 200 mg/m ³ , 50 ppm
REL	Long-term value: 100 mg/m ³ , 25 ppm Skin
TLV	Short-term value: 50 ppm Long-term value: 20 ppm Skin, BEI, A3

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

**Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v**

(Contd. of page 4)

CAS: 78-93-3 Methyl Ethyl Ketone

<i>PEL</i>	<i>Long-term value: 590 mg/m³, 200 ppm</i>
<i>REL</i>	<i>Short-term value: 885 mg/m³, 300 ppm</i> <i>Long-term value: 590 mg/m³, 200 ppm</i>
<i>TLV</i>	<i>Short-term value: NIC-150 (300) ppm</i> <i>Long-term value: NIC-75 (200) ppm</i> <i>BEI, NIC-Skin</i>

· Ingredients with biological limit values:**CAS: 108-94-1 Cyclohexanone 99.8%**

<i>BEI</i>	<i>80 mg/L</i> <i>LD50 Intraperitoneal: urine</i> <i>Time: end of shift at end of workweek</i> <i>LD50: 1.2-Cyclohexanediol (with hydrolysis, nonspecific, nonquantitative)</i>
<i>8 mg/L</i>	<i>LD50 Intraperitoneal: urine</i> <i>Time: end of shift</i> <i>LD50: Cyclohexanol (with hydrolysis, nonspecific, nonquantitative)</i>

CAS: 78-93-3 Methyl Ethyl Ketone

<i>BEI</i>	<i>2 mg/L</i> <i>LD50 Intraperitoneal: urine</i> <i>Time: end of shift</i> <i>LD50: Methyl ethyl ketone (nonspecific)</i>
------------	--

· **Additional information:** *The lists that were valid during the creation were used as basis.*

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Colorless
Odor:	Organic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>34 °C (>93.2 °F)

· **Flash point:** <40 °C (<104 °F)

· **Flammability (solid, gaseous):** Flammable.

· **Auto igniting:** 420 °C (788 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	1.3 Vol %
Upper:	11.5 Vol %

· **Vapor pressure at 20 °C (68 °F):** 105 hPa (78.8 mm Hg)

· **Density at 20 °C (68 °F):** 0.9068 g/cm³ (7.56725 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 6)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 % 906.8 g/l / 7.57 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)		
Oral	LD50	682 mg/kg
Dermal	LD50	409 mg/kg
Inhalative	LC50/4h	15 mg/l

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Toxic
Harmful
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 108-94-1 | Cyclohexanone 99.8%

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 7)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | UN1993 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT | Flammable liquids, n.o.s. (Methyl Ethyl Ketone
, Cyclohexanone) |
| <ul style="list-style-type: none"> · IMDG, IATA | FLAMMABLE LIQUID, N.O.S. (Methyl Ethyl Ketone
, Cyclohexanone) |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | |
| <div style="text-align: center;">  </div> | |
| <ul style="list-style-type: none"> · Class | 3 Flammable liquids |

(Contd. on page 9)

Safety Data Sheet


acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v

(Contd. of page 8)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	II
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL ETHYL KETONE , CYCLOHEXANONE), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

Cyclohexanone 99.8%

ACTIVE

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

**Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v**

(Contd. of page 9)

Methyl Ethyl Ketone

ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 78-93-3 Methyl Ethyl Ketone

I

· **TLV (Threshold Limit Value)**

CAS: 108-94-1 Cyclohexanone 99.8%

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS06

GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Cyclohexanone 99.8%

Methyl Ethyl Ketone

· **Hazard statements**

Flammable liquid and vapor.

Harmful if swallowed or if inhaled.

Toxic in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

**Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v**

(Contd. of page 10)

Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
Rinse mouth.
Specific treatment (see on this label).
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off immediately all contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
Date of Preparation / Last Revision:
- **Date of preparation / last revision**
Revision 1.2, 05/15/2024: Reviewed SDS for accuracy. MH/STN
05/15/2024
- **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 3: Flammable liquids – Category 3
Acute Toxicity - Oral 4: Acute toxicity – Category 4
Acute Toxicity - Dermal 3: Acute toxicity – Category 3
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/15/2024

Reviewed on 05/15/2024

**Trade name: Cyclohexanone/
Methyl Ethyl Ketone 70/30 v/v**

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**

(Contd. of page 11)

Creation date 03/12/14 LS

US