Printing date 05/22/2024

Reviewed on 05/22/2024


## **1** Identification

- · Product identifier
- Trade name: <u>Benzene Standard</u> 50 ug/ml (ppm) in Hexane
- · Article number: MOT151
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier: Aqua Solutions, Inc.
  6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

# 2 Hazard(s) identification



Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name:	Benzene Standard 50 ug/ml (ppm) in Hexane

	(Contd. of page 1)
Signal word Danger	
Hazard-determining components of labeling:	
Hexane	
Benzene	
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation.	e
Classification system:	).
NFPA ratings (scale 0 - 4)	
IVE FA raings (scale 0 - 4)	
Health = 1	
Fire = $3$	
1  0  Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
$\begin{array}{c c} \text{HEALTH} & 1 \\ \end{array} Health = 1 \end{array}$	
FIRE 3 Fire = 3	
<b>REACTIVITY</b> $0$ <i>Reactivity</i> = 0	
Other hazards	
Results of PBT and vPvB assessment	
<b>PBT:</b> Not applicable.	
<b>1 D1</b> , 107 approable.	(Contd. on page 3)

US

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

(Contd. of page 2)

99.995%

0.005%

· vPvB: Not applicable.

### 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 110-54-3 Hexane

#### · Table of Nonhazardous Ingredients

CAS: 71-43-2 Benzene

### 4 First-aid measures

· Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available. • Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## **6** Accidental release measures

Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

<sup>-</sup> US

Printing date 05/22/2024

Reviewed on 05/22/2024

## Trade name: Benzene Standard

#### 50 ug/ml (ppm) in Hexane

Absorb with liqu Dispose contam Ensure adequat • <b>Reference to ot</b> See Section 7 fo See Section 8 fo See Section 13 f		(Contd. of page 3)
· PAC-1:		
CAS: 110-54-3	Hexane	260 ppm
CAS: 71-43-2	Benzene	52 ppm
· PAC-2:		
CAS: 110-54-3	Hexane	2900* ppm
CAS: 71-43-2	Benzene	800 ppm
· PAC-3:		
CAS: 110-54-3	Hexane	8600** ppm
CAS: 71-43-2	Benzene	4000* ppm

# 7 Handling and storage

#### · Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

## · Components with limit values that require monitoring at the workplace:

# CAS: 110-54-3 Hexane

PEL Long-term value: 1800 mg/m<sup>3</sup>, 500 ppm

(Contd. on page 5)

US

Printing date 05/22/2024

Reviewed on 05/22/2024

## Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

(Contd. of page 4)

REL	Long-term value: 180 mg/m <sup>3</sup> , 50 ppm
TLV	Long-term value: 50 ppm
	Skin; BEI

### · Ingredients with biological limit values:

CAS: 110-54-3 Hexane

BEI 0.5 mg/L

LD50 Intraperitoneal: urine Time: end of shift LD50: 2.5-Hexanedione without hydrolysis

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

· Personal protective equipment:

#### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  **Material of gloves** 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

• **Body protection:** Protective work clothing

(Contd. on page 6)

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

(Contd. of page 5)

· Information on basic physical and cl	hemical properties
· General Information	
· Appearance: Form:	Liquid
Color:	Clear water white
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	69 °C (156.2 °F)
· Flash point:	-26 °C (-14.8 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	240 °C (464 °F)
• Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.7 Vol %
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
· Vapor pressure at 50 °C (08 °F):	540 hPa (405 mm Hg)
· Density at 20 °C (68 °F):	0.66 g/cm <sup>3</sup> (5.5077 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	0.1 g/l
· Partition coefficient (n-octanol/water	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 %
	660.0 g/l / 5.51 lb/gal
Solids content:	0.0 %
• Other information	No further relevant information available.

(Contd. on page 7)

US

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

(Contd. of page 6)

1

Κ

## **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11** Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 71-43-2 Benzene

· NTP (National Toxicology Program)

CAS: 71-43-2 Benzene

· OSHA-Ca (Occupational Safety & Health Administration)

CAS: 71-43-2 Benzene

### **12 Ecological information**

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

- Water hazard class 2 (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

• **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

(Contd. of page 7)

# **13 Disposal considerations**

## · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG IATA	Flammable liquids, n.o.s. (Hexane) FLAMMABLE LIQUID, N.O.S. (Hexane), MARINE POLLUTAN FLAMMABLE LIQUID, N.O.S. (Hexane)
Transport hazard class(es)	
DOT	
RAMAREE LOCO	
Class	3 Flammable liquids
Label	3
Class Label	3 Flammable liquids 3
IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances: Hexan Yes Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids

US ·

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

	(Contd. of page
· EMS Number:	F-E,S-E
· Stowage Category	B
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
• Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
·IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (HEXANE), 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

•	Sara
---	------

~		
· Section 355 (ex	tremely hazardous substances):	
None of the ing	redients is listed.	
· Section 313 (Sp	pecific toxic chemical listings):	
All ingredients	are listed.	
· TSCA (Toxic S	ubstances Control Act):	
Hexane		ACTIVE
Benzene		ACTIVE
· Hazardous Air	Pollutants	
All ingredients	are listed.	
· Proposition 65		
· Chemicals know	wn to cause cancer:	
CAS: 71-43-2	Benzene	
· Chemicals know	wn to cause reproductive toxicity for females:	
None of the ing	redients is listed.	
· Chemicals know	wn to cause reproductive toxicity for males:	
All ingredients	are listed.	
· Chemicals know	wn to cause developmental toxicity:	
CAS: 71-43-2	Benzene	
· Carcinogenic c	ategories	
	nental Protection Agency)	
CAS: 110-54-3	Hexane	II
CAS: 71-43-2	Benzene	A, K/L
		(Contd. on page 10)
		U

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

(Contd. of page 9)

A1

• TLV (Threshold Limit Value) CAS: 71-43-2 Benzene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 71-43-2 Benzene

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: Hexane Benzene · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

Printing date 05/22/2024

Reviewed on 05/22/2024

Trade name: Benzene Standard

50 ug/ml (ppm) in Hexane

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 10)

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2, 05/22/2024: Reviewed SDS for accuracy. MH/STN 05/22/2024 · Abbreviations and acronyms:
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety
- **OSHA:** Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- **REL:** Recommended Exposure Limit
- BEI: Biological Exposure Limit
- Flammable Liquids 2: Flammable liquids Category 2
- Skin Irritation 2: Skin corrosion/irritation Category 2
- Toxic to Reproduction 2: Reproductive toxicity Category 2
- Specific Target Organ Toxicity Single Exposure 3: Specific target organ toxicity (single exposure) Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2
- Aspiration Hazard 1: Aspiration hazard Category 1
- $\cdot$  \* Data compared to the previous version altered.