Printing date 05/23/2024

Reviewed on 05/23/2024

Product identifier Trade name: <u>Nital Etch Solution</u> <u>15% v/v Nitric Acid in Methanol</u>	
Article number: ND178	
Details of the supplier of the safety data sheet Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	AQUA SOLUTIONS
Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	
Hazard(s) identification	
114,414(5) Wennigreation	
Classification of the substance or mixture GHS02 Flame	
Classification of the substance or mixture	H225 Highly flammable liquid and vapor.
Classification of the substance or mixture GHS02 Flame	H225 Highly flammable liquid and vapor.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2	H225 Highly flammable liquid and vapor. H301 Toxic if swallowed.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones	
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Oral 3	H301 Toxic if swallowed.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3	H301 Toxic if swallowed. H311 Toxic in contact with skin.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3 GHS08 Health hazard	H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled. H370 Causes damage to the central nervous system and
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3 GHS08 Health hazard	H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled.
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3 GHS08 Health hazard	H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled. H370 Causes damage to the central nervous system and
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3 GHS08 Health hazard Specific Target Organ Toxicity - Single Exposure 1	H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled. H370 Causes damage to the central nervous system and
Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 GHS06 Skull and crossbones Acute Toxicity - Oral 3 Acute Toxicity - Dermal 3 Acute Toxicity - Inhalation 3 GHS08 Health hazard Specific Target Organ Toxicity - Single Exposure 1 GHS05 Corrosion	H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled. H370 Causes damage to the central nervous system and visual organs.

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol



Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

(Contd. of page 2)

74.901%

25.1%

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 67-56-1	Methanol
0110.07 50 1	munun

CAS: 7697-37-2 Nitric Acid

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

- Remove breathing apparatus only after contaminated clothing have been completely removed.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation:
- Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; immediately call for medical help.

- Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.*

(Contd. on page 4)

US

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

		(Contd. of page 3)
• Environmental p	recautions: Do not allow to enter sewers/ surface or ground water.	(conta: of page 5)
	terial for containment and cleaning up:	
Absorb with liqu	id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing		
Dispose contami	nated material as waste according to section 13.	
Ensure adequate		
· Reference to oth		
	information on safe handling.	
v	information on personal protection equipment.	
	r disposal information.	
	ı Criteria for Chemicals	
· PAC-1:		
CAS: 67-56-1	Methanol	530 ppm
CAS: 7697-37-2	Nitric Acid	0.16 ppm
· PAC-2:		
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 7697-37-2	Nitric Acid	24 ppm
· PAC-3:		
CAS: 67-56-1	Methanol	7200* ppm
CAS: 7697-37-2	Nitric Acid	92 ppm

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- *Store in cool, dry conditions in well sealed receptacles.*
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

US

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

C	(Contd. of page
	rol parameters ponents with limit values that require monitoring at the workplace:
	: 67-56-1 Methanol
	Long-term value: 260 mg/m ³ , 200 ppm
	Short-term value: 325 mg/m ³ , 250 ppm
KEL	Long-term value: 260 mg/m ³ , 200 ppm
	Skin
TLV	Short-term value: 250 ppm
12,	Long-term value: 200 ppm
	Skin; BEI
CAS	: 7697-37-2 Nitric Acid
PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm
	Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: (4) NIC-0.025* ppm
	Long-term value: (2) ppm
	*inh. fraction + vapor, NIC-A4
Ingr	edients with biological limit values:
CAS	: 67-56-1 Methanol
	15 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Methanol (background, nonspecific)
Addi	tional information: The lists that were valid during the creation were used as basis.
Expo	osure controls
Perso	onal protective equipment:
	eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	e protective clothing separately.
	d contact with the eyes. d contact with the eyes and skin.
	thing equipment:
	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure i
	iratory protective device that is independent of circulating air.
	ection of hands:
1	
1110	Protective gloves
	1 Tolective gloves
The g	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ t
	nical mixture.
	ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	erial of gloves
	selection of the suitable gloves does not only depend on the material, but also on further marks of quality a
	es from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance love material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

US

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

(Contd. of page 5)

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor: Odor threshold:	Methanol Not determined.
<i>pH-value at 20 °C (68 °F):</i>	<2
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F):	0.89823 g/cm ³ (7.49573 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e r): Not determined.
Viscosity:	
Dynamic:	Not determined.

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

		(Contd. of page 6)
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	74.9 %	
VOC content:	74.90 %	
	672.8 g/l / 5.61 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)OralLD50134 mg/kgDermalLD50401 mg/kgInhalativeLC50/4h3 mg/l

· Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

 \cdot on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 8)

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution

15% v/v Nitric Acid in Methanol

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN2924
UN proper shipping name	
DOT	Flammable liquids, corrosive, n.o.s. (Methanol, Nitric Acid)
IMDG, IATA	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methanol, Nitri
,	Acid)

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name:	Nital Etch Solution
	15% v/v Nitric Acid in Methanol

	(Con	td. of pag
Transport hazard class(es)		
DOT		
3 8		
Class	3 Flammable liquids	
Label	3, 8	
IMDG		
	2 Elammahla liquida	
Class Label	3 Flammable liquids 3/8	
IATA		
Class	3 Flammable liquids	
Label	3 (8)	
Packing group		
DOT, IMDG, IATA	II	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Flammable liquids	
Hazard identification number (Kemler code):		
EMS Number: Segregation groups	F-E,S-C (SGG1a) Strong acids	
Stowage Category	B	
Stowage Code	SW2 Clear of living quarters.	
Transport in bulk according to Annex II of		
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 1 L	
	On cargo aircraft only: 5 L	
IMDG		
Limited quantities (LQ)	1L	
Excepted quantities (\widetilde{EQ})	Code: E2	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
	(Contd	. on page

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

(Contd. of page 9)

· UN "Model Regulation":

UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (METHANOL, NITRIC ACID), 3 (8), II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):	
CAS: 7697-37-2 Nitric Acid	
· Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
Methanol	ACTIVE
Nitric Acid	ACTIVE
· Hazardous Air Pollutants	
CAS: 67-56-1 Methanol	

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 11)

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

	(Contd. of page 10)
Hazard-determining components of labeling:	
Methanol	
Nitric Acid	
Hazard statements	
Highly flammable liquid and vapor.	
Toxic if swallowed, in contact with skin or if inhaled.	
Causes severe skin burns and eye damage.	
Causes damage to the central nervous system and the visual organs.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dusts or mists.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
If swallowed: Rinse mouth. Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/show	ver.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if prese	ent and easy to do
Continue rinsing.	
IF exposed: Call a POISON CENTER or doctor/physician.	
Call a poison center/doctor if you feel unwell.	
Take off immediately all contaminated clothing and wash it before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulati	ions.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

- Date of Preparation / Last Revision:
- · Date of preparation / last revision

Revision 1.2, 05/22/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 01-07-2016: creation date for SDS. STN 05/23/2024 • Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Nital Etch Solution 15% v/v Nitric Acid in Methanol

	(Contd. of page 11)
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 2: Flammable liquids – Category 2	
Acute Toxicity - Oral 3: Acute toxicity – Category 3	
Skin Corrosion 1A: Skin corrosion/irritation – Category 1A	
Eye Damage 1: Serious eye damage/eye irritation – Category 1	
Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1	
• * Data compared to the previous version altered.	