

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

1 Identification

- **Product identifier**
- **Trade name:** Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution
- **Article number:** ND482
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS07

Acute Toxicity - Oral 4 H302 Harmful if swallowed.

Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Ethylene Glycol

- **Hazard statements**

Highly flammable liquid and vapor.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution**

(Contd. of page 1)

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Call a poison center/doctor if you feel unwell.
 Rinse mouth.
 Specific treatment (see on this label).
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 107-21-1	Ethylene Glycol	69.533%
CAS: 67-63-0	Isopropanol	11.915%

· **Table of Nonhazardous Ingredients**

CAS: 7732-18-5	Water	18.552%
----------------	-------	---------

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

CAS: 107-21-1	Ethylene Glycol	30 ppm
CAS: 67-63-0	Isopropanol	400 ppm

- **PAC-2:**

CAS: 107-21-1	Ethylene Glycol	150 ppm
CAS: 67-63-0	Isopropanol	2000* ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution**

(Contd. of page 3)

· **PAC-3:**

CAS: 107-21-1	Ethylene Glycol	900 ppm
CAS: 67-63-0	Isopropanol	12000** ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:****CAS: 107-21-1 Ethylene Glycol**

TLV Short-term value: 10** mg/m³, 50* ppm
Long-term value: 25* ppm
*vapor fraction: **inh. fraction, aerosol only, A4
WEEL I (2)

CAS: 67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm
REL Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm
TLV Short-term value: 400 ppm
Long-term value: 200 ppm
BEI, A4

· **Ingredients with biological limit values:****CAS: 67-63-0 Isopropanol**

BEI 40 mg/L
LD50 Intraperitoneal: urine
Time: end of shift at end of workweek
LD50: Acetone (background, nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution

(Contd. of page 4)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	de l'alcool

- **Odor threshold:** l
Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C (179.6 °F)

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution

(Contd. of page 5)

· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	410 °C (770 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2 Vol %
Upper:	53 Vol %
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
· Density at 20 °C (68 °F):	1.0376 g/cm ³ (8.65877 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	11.9 %
Water:	18.6 %
VOC content:	11.92 %
	123.6 g/l / 1.03 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	719 mg/kg
------	------	-----------

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 67-63-0	Isopropanol	3
--------------	-------------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024



Reviewed on 05/23/2024

Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	UN1993
· DOT, IMDG, IATA	
· UN proper shipping name	Flammable liquids, n.o.s. (Isopropanol)
· DOT	
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Isopropanol)
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution

(Contd. of page 8)

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 107-21-1 Ethylene Glycol

CAS: 67-63-0 Isopropanol

· **TSCA (Toxic Substances Control Act):**

Ethylene Glycol

ACTIVE

Water

ACTIVE

Isopropanol

ACTIVE

· **Hazardous Air Pollutants**

CAS: 107-21-1 Ethylene Glycol

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 107-21-1 Ethylene Glycol

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

CAS: 107-21-1 Ethylene Glycol

A4

CAS: 67-63-0 Isopropanol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Danger· **Hazard-determining components of labeling:**

Ethylene Glycol

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution**

(Contd. of page 9)

· **Precautionary statements**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
- Keep container tightly closed.*
- Ground/bond container and receiving equipment.*
- Use explosion-proof electrical/ventilating/lighting/equipment.*
- Use only non-sparking tools.*
- Take precautionary measures against static discharge.*
- Wash thoroughly after handling.*
- Do not eat, drink or smoke when using this product.*
- Wear protective gloves/protective clothing/eye protection/face protection.*
- If swallowed: Call a poison center/doctor if you feel unwell.*
- Rinse mouth.*
- Specific treatment (see on this label).*
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- Take off contaminated clothing and wash it before reuse.*
- If skin irritation occurs: Get medical advice/attention.*
- If eye irritation persists: Get medical advice/attention.*
- In case of fire: Use CO₂, powder or water spray to extinguish.*
- Store in a well-ventilated place. Keep cool.*
- Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
- Date of Preparation / Last Revision:*
- **Date of preparation / last revision**
- Revision 1.2, 05/23/2024: Reviewed SDS for accuracy. MH/STN*
- Revision 0.0. 08-04-2016: creation date for SDS. STN*
- 05/23/2024*
- **Abbreviations and acronyms:**
- IMDG: International Maritime Code for Dangerous Goods*
- DOT: US Department of Transportation*
- IATA: International Air Transport Association*
- EINECS: European Inventory of Existing Commercial Chemical Substances*
- ELINCS: European List of Notified Chemical Substances*
- CAS: Chemical Abstracts Service (division of the American Chemical Society)*
- NFPA: National Fire Protection Association (USA)*
- HMIS: Hazardous Materials Identification System (USA)*
- VOC: Volatile Organic Compounds (USA, EU)*
- LC50: Lethal concentration, 50 percent*
- LD50: Lethal dose, 50 percent*
- PBT: Persistent, Bioaccumulative and Toxic*
- vPvB: very Persistent and very Bioaccumulative*
- NIOSH: National Institute for Occupational Safety*
- OSHA: Occupational Safety & Health*
- TLV: Threshold Limit Value*
- PEL: Permissible Exposure Limit*
- REL: Recommended Exposure Limit*
- BEI: Biological Exposure Limit*
- Flammable Liquids 2: Flammable liquids – Category 2*

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/23/2024

Reviewed on 05/23/2024

**Trade name: Ethylene Glycol 65% v/v
Water-Isopropanol 35% v/v Solution**

(Contd. of page 10)

*Acute Toxicity - Oral 4: Acute toxicity – Category 4**Skin Irritation 2: Skin corrosion/irritation – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**· * Data compared to the previous version altered.*

US