Printing date 05/29/2024 Reviewed on 05/29/2024

1 Identification

· Product identifier

· Trade name: Acetic Acid / Chloroform

60/40 v/v Solution

· Article number: SPE305

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Toxicity - Inhalation 3

H331 Toxic if inhaled.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to the central nervous system, the kidneys, the liver and the respiratory system

through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



H302 Harmful if swallowed. Acute Toxicity - Oral 4

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 1)

· Hazard pictograms









GHS05

GHS06

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Chloroform

Acetic Acid, Glacial

· Hazard statements

Harmful if swallowed.

Toxic if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

(Contd. on page 3)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous co	mponents:	
CAS: 64-19-7	Acetic Acid, Glacial	51.557%
CAS: 67-66-3	Chloroform	48.443%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
CAS: 64-19-7 Acetic Acid, Glacial	5 ppm
CAS: 67-66-3 Chloroform	2 ppm
· PAC-2:	
CAS: 64-19-7 Acetic Acid, Glacial	35 ppm
CAS: 67-66-3 Chloroform	64 ppm
· PAC-3:	
CAS: 64-19-7 Acetic Acid, Glacial	250 ppm
CAS: 67-66-3 Chloroform	3,200 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 4)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 64-19-7 Acetic Acid, Glacial

PEL Long-term value: 25 mg/m³, 10 ppm REL Short-term value: 37 mg/m³, 15 ppm

TLV Short-term value: 15 ppm Long-term value: 10 ppm

CAS: 67-66-3 Chloroform

PEL Ceiling limit value: 240 mg/m³, 50 ppm

Long-term value: 25 mg/m³, 10 ppm

REL Short-term value: 9.78* mg/m³, 2* ppm *60-min; See Pocket Guide App. A

TLV Long-term value: 10 ppm

A3

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties	
General Information		
Appearance:	**	
Form:	Liquid	
Color: Odor:	Clear Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	118 °C (244.4 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	485 °C (905 °F)	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	4 Vol %	
Upper:	17 Vol %	
Vapor pressure at 20 °C (68 °F):	210 hPa (157.5 mm Hg)	
Density at 20 °C (68 °F):	1.25979 g/cm³ (10.51295 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	51.6 %	

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

	(Contd. of page 6)
VOC content:	51.56 % 649.5 g/l / 5.42 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:		
ATE (Acut	ATE (Acute Toxicity Estimate)		
Oral	LD50	1,032 mg/kg	
Dermal	LD50	2,056 mg/kg (rabbit)	
Inhalative	LC50/4h	6.19 mg/l	

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: **Toxic**

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Interi	national Agency for Research on Cancer)	
CAS: 67-66	Chloroform	28
· NTP (Nation	al Toxicology Program)	
CAS: 67-66-3	R Chloroform	R
		(Contd. on page 8)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1 4 5	. .		•	r	
129	Trans	nort	ากา	orm	สนากท
	T COLUD		$\omega_{\rm L}\omega_{\rm L}$		

· UN-Number · DOT, IMDG, IATA	UN2922
· UN proper shipping name	

· **DOT**Corrosive liquids, toxic, n.o.s. (Acetic Acid, Glacial , Chloroform)

· IMDG, IATA CORROSIVE LIQUID, TOXIC, N.O.S. (Acetic Acid, Glacial , Chloroform)

(Contd. on page 9)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

	(Contd. of pag
Transport hazard class(es)	
DOT	
CORROSIVE	
8 6	
Class	8 Corrosive substances
Label	8, 6.1
IMDG	
TWDG	
8/	
Class	8 Corrosive substances
Label	8/6.1
IATA	
6	
Class Label	8 Corrosive substances 8 (6.1)
	0 (0.1)
Packing group DOT, IMDG, IATA	II
	П
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler of EMS Number:	F-A,S-B
Segregation groups	(SGG1) Acids
Stowage Category	B
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex I	I of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
~ ,	On cargo aircraft only: 30 L
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 9)

· UN "Model Regulation": UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (ACETIC ACID,

GLACIAL

, CHLOROFORM), 8 (6.1), II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

CAS: 67-66-3 Chloroform

· Section 313 (Specific toxic chemical listings):

CAS: 67-66-3 Chloroform

· TSCA (Toxic Substances Control Act):

Acetic Acid, Glacial ACTIVE
Chloroform ACTIVE

· Hazardous Air Pollutants

CAS: 67-66-3 Chloroform

- · Proposition 65
- · Chemicals known to cause cancer:

CAS: 67-66-3 Chloroform

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-66-3 Chloroform

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

CAS: 67-66-3 Chloroform

B2, L, NL

· TLV (Threshold Limit Value)

CAS: 67-66-3 Chloroform

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 67-66-3 Chloroform

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS05 GHS06

6 GHS07

GHS08

· Signal word Danger

(Contd. on page 11)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 10)

· Hazard-determining components of labeling:

Chloroform

Acetic Acid, Glacial

· Hazard statements

Harmful if swallowed.

Toxic if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

 $\cdot \textit{Chemical safety assessment:} \ A \ \textit{Chemical Safety Assessment has not been carried out.}$

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 05/29/2024: Reviewed SDS for accuracy. MH/STN 05/29/2024

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Printing date 05/29/2024 Reviewed on 05/29/2024

Trade name: Acetic Acid / Chloroform 60/40 v/v Solution

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Acute Toxicity - Oral 4: Acute toxicity - Category 4 Acute Toxicity - Inhalation 3: Acute toxicity - Category 3 Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Eye Damage 1: Serious eye damage/eye irritation - Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1 Carcinogenicity 2: Carcinogenicity - Category 2

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

* * Data compared to the previous version altered.

-US