

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

1 Identification

- **Product identifier**
- **Trade name:** Sulfur-Dioxide In pyridine
400 gm/gal
- **Article number:** UCS023F
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Product safety department
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS05



GHS06

- **Signal word** Danger

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Pyridine
Sulfur Dioxide

· **Hazard statements**

Extremely flammable liquid and vapor.
Harmful if swallowed or in contact with skin.
Toxic if inhaled.
Causes severe skin burns and eye damage.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dusts or mists.
Wear protective gloves / eye protection / face protection.
Wear protective gloves / protective clothing.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
If swallowed: Call a poison center/doctor if you feel unwell.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Wash contaminated clothing before reuse.
If swallowed: Rinse mouth. Do NOT induce vomiting.
In case of fire: Use for extinction: CO₂, powder or water spray.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 4
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 3
Fire = 4
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
· **vPvB:** Not applicable.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 110-86-1	Pyridine	90.0%
CAS: 7446-09-5	Sulfur Dioxide	10.0%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

See Section 13 for disposal information.

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

110-86-1 Pyridine

PEL Long-term value: 15 mg/m³, 5 ppm

REL Long-term value: 15 mg/m³, 5 ppm

TLV Long-term value: 3.1 mg/m³, 1 ppm

7446-09-5 Sulfur Dioxide

PEL Long-term value: 13 mg/m³, 5 ppm

REL Short-term value: 13 mg/m³, 5 ppm
Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 0.65 mg/m³, 0.25 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

(Contd. on page 5)

-US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· Form:	Liquid
· Color:	Clear
· Odor:	Characteristic
· Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	-10 °C (14 °F)

- **Flash point:** 17 °C (63 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 550 °C (1022 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

· Lower:	1.7 Vol %
· Upper:	10.6 Vol %

- **Vapor pressure at 20 °C (68 °F):** 20 hPa (15 mm Hg)

- **Density at 20 °C (68 °F):** 1.0174 g/cm³ (8.49 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Fully miscible.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 5)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 0.0 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	990 mg/kg (rat)
Dermal	LD50	1246 mg/kg (rabbit)
Inhalative	LC50/4 h	8.68 mg/l

110-86-1 Pyridine

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	1121 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

7446-09-5 Sulfur Dioxide

Inhalative	LC50/4 h	3 mg/l (ATE)
------------	----------	--------------

- **Primary irritant effect:**
 - **on the skin:** Caustic effect on skin and mucous membranes.
 - **on the eye:** Strong caustic effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

110-86-1	Pyridine	3
7446-09-5	Sulfur Dioxide	3

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 6)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|--|
| · UN-Number | UN3286 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Flammable liquid, toxic, corrosive, n.o.s. (Pyridine, Sulfur dioxide) |
| · DOT | |
| · IMDG, IATA | FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (PYRIDINE, SULPHUR DIOXIDE) |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |

(Contd. on page 8)

Safety Data Sheet



acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 7)

· Label	3, 6.1, 8
· IMDG	
	
· Class	3 Flammable liquids
· Label	3/6.1/8
· IATA	
	
· Class	3 Flammable liquids
· Label	3 (6.1, 8)
· Packing group	
· DOT, IMDG, IATA	I
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	368
· EMS Number:	F-E,S-C
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: Forbidden On cargo aircraft only: 2.5 L
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN3286, Flammable liquid, toxic, corrosive, n.o.s. (Pyridine, Sulfur dioxide), 3 (6.1+8), I

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

7446-09-5	Sulfur Dioxide
-----------	----------------

· **Section 313 (Specific toxic chemical listings):**

110-86-1	Pyridine
----------	----------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 8)

· **Proposition 65**

· **Chemicals known to cause cancer:**

110-86-1	Pyridine
----------	----------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

7446-09-5	Sulfur Dioxide
-----------	----------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

110-86-1	Pyridine	A3
7446-09-5	Sulfur Dioxide	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS06

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Pyridine
Sulfur Dioxide

· **Hazard statements**

Extremely flammable liquid and vapor.
Harmful if swallowed or in contact with skin.
Toxic if inhaled.
Causes severe skin burns and eye damage.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dusts or mists.
Wear protective gloves / eye protection / face protection.
Wear protective gloves / protective clothing.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/29/2015

Reviewed on 06/29/2015

Trade name: Sulfur-Dioxide In pyridine
400 gm/gal

(Contd. of page 9)

Specific treatment (see on this label).

If swallowed: Call a poison center/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

If swallowed: Rinse mouth. Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Mr. Nelson

· **Date of preparation / last revision**

Revision 0.1, 06-29-2015: added additional information.as Density. STN
 06/29/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Acute Tox. 4: Acute toxicity, Hazard Category 4

Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1