Printing date 05/29/2019 Reviewed on 05/29/2019

#### 1 Identification

· Product identifier

· Trade name: ASTM D6591 Modified Cal Std

Method Aromatics by HPLC - C

· Article number: HOU067

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number:

Chemtrec: 800-424-9300 Canutec: 613-996-6666



### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

 $n ext{-}Heptane$ 

Cyclohexane

(Contd. on page 2)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

(Contd. of page 1)

#### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1

Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 142-82-5 n-Heptane

70.382%

(Contd. on page 3)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

	(Cor	ntd. of page 2)
CAS: 95-47-6	o-Xylene	13.905%
CAS: 110-82-7	Cyclohexane	13.905%
CAS: 90-12-0	1-methylnaphthalene	1.391%
	Phenanthrene, 98%	0.417%

### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- $\cdot \textit{For safety reasons unsuitable extinguishing agents: } Water \textit{ with full jet}$
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1 / 0/00/1/0 / 10//	in Citicitation Chemicals	
· PAC-1:		
CAS: 142-82-5	n-Heptane	500 ppm
CAS: 110-82-7	Cyclohexane	300 ppm
CAS: 90-12-0	1-methylnaphthalene	20 mg/m³
	Phenanthrene, 98%	5.4 mg/m³
	(Co	ntd. on page 4)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

PAC-2:		(Contd. of page 2
CAS: 142-82-5	n-Heptane	830 ppm
CAS: 110-82-7	Cyclohexane	1700* ppm
CAS: 90-12-0	1-methylnaphthalene	61 mg/m³
	Phenanthrene, 98%	59 mg/m³
· PAC-3:		
CAS: 142-82-5	n-Heptane	5000* ppm
CAS: 110-82-7	Cyclohexane	10000** ppm
CAS: 90-12-0	1-methylnaphthalene	$360  mg/m^3$
	Phenanthrene, 98%	360 mg/m³

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· *Specific end use*(s) *No further relevant information available.* 

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Conti	· Control parameters		
· Comp	· Components with limit values that require monitoring at the workplace:		
CAS: 142-82-5 n-Heptane			
PEL	PEL Long-term value: 2000 mg/m³, 500 ppm		
REL	Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min		
TLV	Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm		
CAS: 95-47-6 o-Xylene			
PEL	PEL   Long-term value: 435 mg/m³, 100 ppm		

(Contd. on page 5)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

(Contd. of page 4)			
Short-term value: 655 mg/m³, 150 ppm			
Long-term value: 435 mg/m³, 100 ppm			
Short-term value: 651 mg/m³, 150 ppm			
Long-term value: 434 mg/m³, 100 ppm			
BEI			
: 110-82-7 Cyclohexane			
Long-term value: 1050 mg/m³, 300 ppm			
Long-term value: 1050 mg/m³, 300 ppm			
Long-term value: 344 mg/m³, 100 ppm			
CAS: 90-12-0 1-methylnaphthalene			
Long-term value: 3 mg/m³, 0.5 ppm			
Skin			
nanthrene, 98%			
Short-term value: 0.2 mg/m³			
edients with biological limit values:			
: 95-47-6 o-Xylene			
1.5 g/g creatinine			
LD50 Intraperitoneal: urine			
Time: end of shift			
LD50: Methylhippuric acids  itional information: The lists that were valid during the creation were used as basis			

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Gasoline-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	81 °C (177.8 °F)
Flash point:	-18 °C (-0.4 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	215 °C (419 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	8.3 Vol %
Vapor pressure at 20 °C (68 °F):	104 hPa (78 mm Hg)
Density at 20 °C (68 °F):	0.72762 g/cm³ (6.07199 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e <b>r</b> ): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

		(Contd. of page 6
· Solvent content:		
Organic solvents:	98.2 %	
VOC content:	98.19 %	
	714.5 g/l / 5.96 lb/gal	
Solids content:	0.4 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)			
Oral	LD50	132,327 mg/kg (rat)	
Dermal	LD50	7,911 mg/kg	
Inhalative	LC50/4h	79.1 mg/l	
CAS, 05 47 6 a Vulgue			

CAS: 95-47-6 o-Xylene				
		1,100 mg/kg (ATE)		
Inhalative	LC50/4h	11 mg/l (ATE)		

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 95-47-6	o-Xylene	3
	Phenanthrene, 98%	3
· NTP (Nationa	al Toxicology Program)	
Phenanthrene	2, 98%	R
		(Contd. on page 8)

— II

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

 ranspor	UI IIIUU	uviu

· UN-Number · DOT, IMDG, IATA	UN1993
· UN proper shipping name · DOT · IMDG · IATA	Flammable liquids, n.o.s. (Heptanes, Cyclohexane, Xylenes) FLAMMABLE LIQUID, N.O.S. (HEPTANES, CYCLOHEXANE, XYLENES), MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (HEPTANES, CYCLOHEXANE, XYLENES)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

(Contd. on page 9)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

	(Contd. of page
· Label	3
· IMDG	
<b>*</b>	
· Class	3 Flammable liquids
· Label	3
· IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: n-Heptan Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	<i>F-E,<u>S-E</u></i>
· Stowage Category	В
· Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot DOT$	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities $(\widetilde{EQ})$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (HEPTANE CYCLOHEXANE, XYLENES), 3, II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 10)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

(Contd. of page 9) · Section 313 (Specific toxic chemical listings): CAS: 95-47-6 o-Xylene CAS: 110-82-7 Cyclohexane Phenanthrene, 98% · TSCA (Toxic Substances Control Act): n-Heptane **ACTIVE** o-Xylene **ACTIVE** Cyclohexane **ACTIVE** 1-methylnaphthalene **ACTIVE** Phenanthrene, 98% **ACTIVE** · Hazardous Air Pollutants CAS: 95-47-6 o-Xylene Phenanthrene, 98% · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Carcinogenic categories · EPA (Environmental Protection Agency) CAS: 142-82-5 n-Heptane D CAS: 95-47-6 o-Xylene CAS: 110-82-7 Cyclohexane Phenanthrene, 98% D · TLV (Threshold Limit Value established by ACGIH) CAS: 95-47-6 o-Xylene A4CAS: 90-12-0 1-methylnaphthalene *A4* 

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





None of the ingredients is listed.



· NIOSH-Ca (National Institute for Occupational Safety and Health)

GHS02

- GHS07
- GHS08
- · Signal word Danger
- · Hazard-determining components of labeling: n-Heptane

(Contd. on page 11)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

(Contd. of page 10)

Cyclohexane

#### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revsion 0.0, 05-29-2019: Creation date for SDS, STN 05/29/2019 / -

#### · Abbreviations and acronyms:

 ${\it IMDG: International\ Maritime\ Code\ for\ Dangerous\ Goods}$ 

DOT: US Department of Transportation

 ${\it IATA: International Air Transport Association}$ 

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 12)

Printing date 05/29/2019 Reviewed on 05/29/2019

Trade name: ASTM D6591 Modified Cal Std Method Aromatics by HPLC - C

(Contd. of page 11)

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1