Printing date 10/30/2024

*

Reviewed on 10/30/2024

Identification	
· Product identifier	
• Trade name: Lead Standard Solution 1.0 Prepared to ASTM D3237-	
• Article number: SPX771	
• Details of the supplier of the safety data .	shaat
· Manufacturer/Supplier:	
Aqua Solutions, Inc.	
6913 Highway 225 DEER PARK, TX 77536	SOECHONS
USA	
800-256-2586	
• Information department: Technical Coordinator	
Sherman Nelson shermann@aquasolution	ns.org
• Emergency telephone number: Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
2 Hazard(s) identification	
· Classification of the substance or mixtur	
Clussification of the substance of mixtur	e e
GHS02 Flame	
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
GHS08 Health hazard	
Carcinogenicity 2	H351 Suspected of causing cancer.
GHS05 Corrosion	
\checkmark	
Eye Damage 1	H318 Causes serious eye damage.
GHS07	
Acute Toxicity - Inhalation 4	H332 Harmful if inhaled.
-	xposure 3 H336 May cause drowsiness or dizziness.
· Label elements	· · · · · · · · · · · · · · · · · · ·
	ified and labeled according to the Globally Harmonized System (GHS).
$\land \land \land \land$	
<u>\@</u> >(+*)(!)(&)>	
GHS02 GHS05 GHS07 GHS08	
	(Contd. on page
	(Contd. on page

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name:	Lead Standard Solution 1.0g Pb/gal
	Prepared to ASTM D3237-17

· Signal word Danger	(Contd. of page 1)
· Hazard-determining components of labeling:	
Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	
methyltrioctylammonium chloride	
· Hazard statements	
Highly flammable liquid and vapor.	
Harmful if inhaled.	
Causes serious eye damage.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/sho	ower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pre	sent and easy to do.
Continue rinsing.	
Immediately call a poison center/doctor.	
IF exposed or concerned: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regula	ations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 3	
Fire = 3	
3 0 Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
$\begin{array}{c} \text{HEALTH} \overset{*3}{} Health = *3 \end{array}$	
FIRE 3 $Fire = 3$	
REACTIVITY O Reactivity = 0	
• Other hazards	
Results of PBT and vPvB assessment	

• *PBT:* Not applicable. • *vPvB:* Not applicable.

(Contd. on page 3)

US

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	96.901%
CAS: 5137-55-3 methyltrioctylammonium chloride	3.063%
• Table of Nonhazardous Ingredients	
CAS: 7758-95-4 Lead Chloride	0.035%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- $\cdot \textit{For safety reasons unsuitable extinguishing agents: } Water with full jet$
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

US -

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

See Section 8 for See Section 13 fo	<i>er sections</i> information on safe handling. information on personal protection equipment. or disposal information. n Criteria for Chemicals	(Contd. of page 3)
· PAC-1:		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	75 ppm
CAS: 5137-55-3	methyltrioctylammonium chloride	$0.67 mg/m^3$
CAS: 7758-95-4	Lead Chloride	$0.2 mg/m^{3}$
· PAC-2:		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	500 ppm
CAS: 5137-55-3	methyltrioctylammonium chloride	7.4 mg/m ³
CAS: 7758-95-4	Lead Chloride	160 mg/m ³
· PAC-3:		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	3000* ppm
CAS: 5137-55-3	methyltrioctylammonium chloride	$44 mg/m^3$
CAS: 7758-95-4	Lead Chloride	940 mg/m ³

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

⁻ US

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

	(Contd. of page 4)
CAS	: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm
	Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 75 ppm
	Long-term value: 20 ppm
	BEI, A3
· Ingr	edients with biological limit values:
CAS	: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
BEI	1 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: MIBK
· Addi	tional information: The lists that were valid during the creation were used as basis.
. Erne	osure controls
	onal protective equipment:
	eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	e protective clothing separately.
Avoi	d contact with the eyes.
Avoi	d contact with the eyes and skin.
· Brea	thing equipment:
In ca	use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use
	iratory protective device that is independent of circulating air.
· Prot	ection of hands:
	Ω)
Phu .	Protective gloves
The	alove material has to be impermeable and resistant to the product/ the substance/ the preparation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

· Body protection: Protective work clothing

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Color: According to product specification · Odor: *Characteristic* Not determined. • Odor threshold: Not determined. · pH-value: · Change in condition -83.5 °C (-118.3 °F) Melting point/Melting range: 114 °C (237.2 °F) Boiling point/Boiling range: 14 °C (57.2 °F) · Flash point: · Flammability: Highly flammable. · Auto igniting: 460 °C (860 °F) · Decomposition temperature: Not determined. · Ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapor · Danger of explosion: mixtures are possible. · Explosion limits: 1.7 Vol % Lower: 9 Vol % Upper: · Vapor pressure at 20 °C (68 °F): 8 hPa (6 mm Hg) 1.00116 g/cm³ (8.35468 lbs/gal) • Density at 20 •C (68 •F): · Relative density Not determined. · Vapor density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with 19 g/l *Water at 20 •C (68 •F):* · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Not determined. Dynamic: Kinematic: Not determined. · Solvent content: 96.9 % Organic solvents: 96.90 % **VOC content:** 970.1 g/l / 8.10 lb/gal 0.0 % Solids content: (Contd. on page 7) US

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 6)

• Other information

No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 7,279 mg/kg (rat)

Inhalative LC50/4h 11.4 mg/l (ATE)

· Primary irritant effect:

• on the skin: No irritant effect.

- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	2B
CAS: 7758-95-4	Lead Chloride	2A
· NTP (National Toxicology Program)		
CAS: 7758-95-4	Lead Chloride	R
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingre	edients is listed.	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- *Persistence and degradability No further relevant information available.*
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)

US

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 7)

 \cdot Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

 $\cdot \textit{Other adverse effects}$ No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

*

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, IMDG, IATA	UN1992
\cdot UN proper shipping name	
$\cdot DOT$	Flammable liquids, toxic, n.o.s. (Methyl Isobutyl Ketone)
· IMDG	FLAMMABLE LIQUID, TOXIC, N.O.S. (Methyl Isobutyl Ketone MARINE POLLUTANT
·IATA	FLAMMABLE LIQUID, TOXIC, N.O.S. (Methyl Isobutyl Ketone)
· Transport hazard class(es)	
·DOT	
P.AMMABLE LOUD	
· Class	3 Flammable liquids
· Label	3, 6.1
· IMDG	
· Class	3 Flammable liquids
	3/6.1

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

	(Contd. of page
·IATA	
· Class	3 Flammable liquids
· Label	3 (6.1)
Packing group	
· DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	В
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
2	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E2
· · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (METHY
-	ISOBUTYL KETONE), 3 (6.1), II

*

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

CAS: 7758-95-4 Lead Chloride

· TSCA (Toxic Substances Control Act):

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

methyltrioctylammonium chloride

Lead Chloride

ACTIVE (Contd. on page 10)

ACTIVE

ACTIVE

US

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 9)

B2

AЗ

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

CAS: 7758-95-4 Lead Chloride

· Proposition 65

 \cdot Chemicals known to cause cancer:

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

CAS: 7758-95-4 Lead Chloride

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

CAS: 7758-95-4 Lead Chloride

· TLV (Threshold Limit Value)

CAS: 7758-95-4 Lead Chloride

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Methyl Isobutyl Ketone (4-Methyl-2-pentanone) methyltrioctylammonium chloride · Hazard statements Highly flammable liquid and vapor. Harmful if inhaled. Causes serious eve damage. Suspected of causing cancer. May cause drowsiness or dizziness. · Precautionary statements *Obtain special instructions before use.* Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

(Contd. on page 11)

Printing date 10/30/2024

Reviewed on 10/30/2024

Trade name: Lead Standard Solution 1.0g Pb/gal Prepared to ASTM D3237-17

(Contd. of page 10)

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* IF exposed or concerned: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: · Date of preparation / last revision Revision 0.0, 09-04-2024: Creation date for SDS. STN Revision 1.1, 10-30-2024: Updated DOT infomation.. STN 10/30/2024 / 1.1 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Inhalation 4: Acute toxicity - Category 4 Eye Damage 1: Serious eye damage/eye irritation - Category 1 Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

• * Data compared to the previous version altered.