Printing date 08/27/2019 Reviewed on 08/27/2019

### 1 Identification

· Product identifier

· Trade name: Bottle #2 - Level 2

· Article number: ARL002

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

2 GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Hexane

Methylcyclopentane 98%

(Contd. on page 2)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 1)

3-Methylpentane

Hexanes (From Petroleum)

Cyclohexane

#### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

· vPvB: Not applicable.

(Contd. of page 2)

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

	· Dangerous components:						
CAS: 110-54-3	Hexane	96.0%					
	3-Methylpentane	1.0%					
CAS: 107-83-5	Hexanes (From Petroleum)	1.0%					
	Methylcyclopentane 98%	1.0%					
CAS: 110-82-7	Cyclohexane	1.0%					

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 3)

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
CAS: 110-54-3	Hexane	260 ppm
CAS: 96-14-0	3-Methylpentane	1,000 ppr
CAS: 107-83-5	Hexanes (From Petroleum)	1,000 ррг
CAS: 96-37-7	Methylcyclopentane 98%	14 ppm
CAS: 110-82-7	Cyclohexane	300 ppm
PAC-2:		
CAS: 110-54-3	Hexane	2900* ppm
CAS: 96-14-0	3-Methylpentane	11000** ppi
CAS: 107-83-5	Hexanes (From Petroleum)	11000** pp.
CAS: 96-37-7	Methylcyclopentane 98%	160 ppm
CAS: 110-82-7	AS: 110-82-7 Cyclohexane	
<i>PAC-3:</i>		
CAS: 110-54-3	Hexane	8600** ppm
CAS: 96-14-0	3-Methylpentane	66000*** ppi
CAS: 107-83-5	Hexanes (From Petroleum)	66000*** ppi
CAS: 96-37-7	Methylcyclopentane 98%	940 ppm
CAS: 110-82-7	Cyclohexane	10000** ppm

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

US

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 4)

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

#### CAS: 110-54-3 Hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

REL Long-term value: 180 mg/m³, 50 ppm

TLV Long-term value: 176 mg/m³, 50 ppm Skin; BEI

CAS: 96-14-0 3-Methylpentane

REL Long-term value: 350 mg/m³, 100 ppm

Ceiling limit value: 1800\* mg/m³, 510\* ppm

\*15-min

TLV Short-term value: 3500 mg/m³, 1000 ppm Long-term value: 1760 mg/m³, 500 ppm

#### CAS: 107-83-5 Hexanes (From Petroleum)

REL Long-term value: 350 mg/m³, 100 ppm Ceiling limit value: 1800\* mg/m³, 510\* ppm \*15-min

TLV Short-term value: 3500 mg/m³, 1000 ppm Long-term value: 1760 mg/m³, 500 ppm

#### CAS: 96-37-7 Methylcyclopentane 98%

REL Long-term value: 350 mg/m³, 100 ppm

Ceiling limit value: 1800\* mg/m³, 510\* ppm

\*15-min

TLV Short-term value: 3500 mg/m³, 1000 ppm Long-term value: 1760 mg/m³, 500 ppm

#### CAS: 110-82-7 Cyclohexane

PEL Long-term value: 1050 mg/m³, 300 ppm

REL Long-term value: 1050 mg/m³, 300 ppm

TLV Long-term value: 344 mg/m<sup>3</sup>, 100 ppm

#### · Ingredients with biological limit values:

### CAS: 110-54-3 Hexane

#### BEI 0.4 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek LD50: 2.5-Hexanedione without hydrolysis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

(Contd. on page 6)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 5)

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

### 9 Physical and chemical properties

. 1	nf	formai	tion (	on .	basic	рl	hysi	cal	and	C	hem	ica	l pr	оре	erti	es
-----	----	--------	--------	------	-------	----	------	-----	-----	---	-----	-----	------	-----	------	----

· General Information

· Appearance:

12pp cur unice.	
Form:	Liquid
Color:	Colorless
· Odor:	Sweetish
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	69 °C (156.2 °F)
· Flash point:	-26 °C (-14.8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

(Contd. on page 7)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

	(Contd	l. of page
· Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7.4 Vol %	
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)	
· Density at 20 °C (68 °F):	0.66213 g/cm³ (5.52547 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	0.1 g/l	
· Partition coefficient (n-octanol/wate	e <b>r</b> ): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	97.0 %	
VOC content:	98.00 %	
	648.9 g/l / 5.42 lb/gal	
Solids content:	1.0 %	
· Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 50,000 mg/kg

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 8)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 7)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

- 1	 			
	nari	11711	ormat	• • • • • •
	u u u u	וטוט	UI IIIIII	uvu

· UN-Number · DOT, IMDG, IATA	UN1993
· UN proper shipping name · DOT · IMDG	Flammable liquids, n.o.s. (Hexanes) FLAMMABLE LIQUID, N.O.S. (HEXANES), MARINE POLLUTANT
· IATA	FLAMMABLE LIQUID, N.O.S. (HEXANES)

(Contd. on page 9)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 8) · Transport hazard class(es)  $\cdot DOT$ · Class 3 Flammable liquids · Label · IMDG · Class 3 Flammable liquids · Label  $\cdot$  IATA 3 Flammable liquids · Class · Label · Packing group · DOT, IMDG, IATA II Product contains environmentally hazardous substances: · Environmental hazards: Cyclohexane · Marine pollutant: Symbol (fish and tree) Warning: Flammable liquids · Special precautions for user · Danger code (Kemler): 33 · EMS Number: F-E,S-E· Stowage Category В · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:  $\cdot DOT$ On passenger aircraft/rail: 5 L · Quantity limitations On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1993 FLAMMABLE LIQUID, N.O.S. (HEXANES), 3, II · UN "Model Regulation":

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 9)

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section	355	(extremely	hazardous	substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 110-54-3 Hexane

CAS: 110-82-7 Cyclohexane

#### · TSCA (Toxic Substances Control Act):

,	
Hexane	ACTIVE
3-Methylpentane	ACTIVE
Hexanes (From Petroleum)	ACTIVE
Methylcyclopentane 98%	ACTIVE
Cyclohexane	ACTIVE

#### · Hazardous Air Pollutants

CAS: 110-54-3 Hexane

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

CAS: 110-54-3 Hexane

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA	(Environmental Protection Agency)
-------	-----------------------------------

CAS: 110-54-3   Hexane	II
CAS: 110-82-7 Cyclohexane	I

#### · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS07

GHS

- · Signal word Danger
- · Hazard-determining components of labeling: Hexane

(Contd. on page 11)

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

(Contd. of page 10)

Methylcyclopentane 98%

3-Methylpentane

Hexanes (From Petroleum)

Cyclohexane

#### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.* 

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revsion 0.0, 08-27-2019, Creation date for SDS. STN 08/27/2019 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 12)

(Contd. of page 11)

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/27/2019 Reviewed on 08/27/2019

Trade name: Bottle #2 - Level 2

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

HMIS: Hazardous Materials Identification System (U

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

US