Printing date 11/07/2019

Reviewed on 11/07/2019

I Identification	
· Product identifier	
• Trade name: <u>N-Propanol : Water</u> <u>2:1 Solution</u>	
• Article number: THE481	
\cdot Details of the supplier of the safety data sheet	
• <i>Manufacturer/Supplier:</i> Aqua Solutions, Inc.	AQUA
6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536 USA	
800-256-2586	
· Information department:	
Technical Coordinator Sherman Nelson sherman@aquasolutions.org	
· Emergency telephone number:	
Chemtrec: 800-424-9300 Canutec: 613-996-6666	
Canutec: 015-990-0000	
2 Hazard(s) identification	
\cdot Classification of the substance or mixture	
GHS02 Flame	
GIIS02 Frame	
Elam Lie 2 U225 Uichly flammahla liquid and yan on	
Fiam. Liq. 2 H223 Highly fiammable liquia and vapor.	
<i>Flam. Liq. 2 H225 Highly flammable liquid and vapor.</i>	
GHS05 Corrosion	
GHS05 Corrosion	
GHS05 Corrosion	
<i>GHS05 Corrosion</i> <i>Eye Dam. 1 H318 Causes serious eye damage.</i>	
<i>GHS05 Corrosion</i> <i>Eye Dam. 1 H318 Causes serious eye damage.</i>	
GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07	l according to the Globally Harmonized System (GHS,
<i>Eye Dam. 1 H318 Causes serious eye damage.</i> <i>Eye Dam. 1 H318 Causes serious eye damage.</i> <i>GHS07</i> <i>STOT SE 3 H336 May cause drowsiness or dizziness.</i> <i>Label elements</i> <i>GHS label elements The product is classified and labeled</i>	l according to the Globally Harmonized System (GHS,
<i>Eye Dam. 1 H318 Causes serious eye damage.</i> <i>Eye Dam. 1 H318 Causes serious eye damage.</i> <i>GHS07</i> <i>STOT SE 3 H336 May cause drowsiness or dizziness.</i> <i>Label elements</i> <i>GHS label elements The product is classified and labeled</i>	l according to the Globally Harmonized System (GHS
<i>Eye Dam. 1 H318 Causes serious eye damage.</i> <i>Eye Dam. 1 H318 Causes serious eye damage.</i> <i>GHS07</i> <i>STOT SE 3 H336 May cause drowsiness or dizziness.</i> <i>Label elements</i> <i>GHS label elements The product is classified and labeled</i> <i>Hazard pictograms</i>	l according to the Globally Harmonized System (GHS
 GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled. Hazard pictograms GHS02 GHS05 GHS07 Signal word Danger Hazard-determining components of labeling: 	according to the Globally Harmonized System (GHS,
 GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled. Hazard pictograms GHS02 GHS05 GHS07 Signal word Danger Hazard-determining components of labeling: n-propanol 	according to the Globally Harmonized System (GHS
 GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled. Hazard pictograms GHS02 GHS05 GHS07 Signal word Danger Hazard-determining components of labeling: 	according to the Globally Harmonized System (GHS,

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

	(Contd. of page 1)
May cause drowsiness or dizziness.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	74
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower IF INHALED: Remove person to fresh air and keep comfortable for breathing.	·
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present	t and easy to do
Continue rinsing.	i unu eusy io uo.
Immediately call a poison center/doctor.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	ns.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
$\begin{array}{c} 3 \\ 3 \\ 3 \\ 0 \end{array} \begin{array}{c} Health = 3 \\ Fire = 3 \\ Reactivity = 0 \end{array}$	
· HMIS-ratings (scale 0 - 4)	
HEALTH *3 Health = $*3$	
FIRE 3 $Fire = 3$	
REACTIVITY 0 Reactivity = 0	
• Other hazards	
• Results of PBT and vPvB assessment	
• PBT : Not applicable.	
• vPvB: Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Mixtures	
• Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
CAS: 71-23-8 n-propanol	61.571%
· Table of Nonhazardous Ingredients	
	20 (200)

CAS: 7732-18-5 Water

4 First-aid measures

· Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

38.429%

US

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

(Contd. of page 2)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

Wear protective equipment. Keep unprotected persons away.	
Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing agent.	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
PAC-1:	
CAS: 71-23-8 n-propanol	250 pp
PAC-2:	
CAS: 71-23-8 n-propanol	670 pp
РАС-3:	
CAS: 71-23-8 n-propanol	4000* pp

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

(Contd. on page 4)

US

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

(Contd. of page 3)

- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 71-23-8 n-propanol

PEL Long-term value: 500 mg/m³, 200 ppm

- REL Short-term value: 625 mg/m³, 250 ppm Long-term value: 500 mg/m³, 200 ppm Skin
- TLV Long-term value: 246 mg/m³, 100 ppm

• Additional information: The lists that were valid during the creation were used as basis.

• Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

[—] US

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

(Contd. of page 4)

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Mild
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	96.5-97.5 °C (205.7-207.5 °F)
Flash point:	22 °C (71.6 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	360 °C (680 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	13.5 Vol %
Vapor pressure at 20 $^{\circ}C$ (68 $^{\circ}F$):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	0.87901 g/cm ³ (7.33534 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wat	e r): Not determined.
Viscosity:	
Dynamic:	Not determined.

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

		(Contd. of page 5
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	61.6 %	
Water:	38.4 %	
VOC content:	61.57 %	
	541.2 g/l / 4.52 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- \cdot Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 3,037 mg/kg (rat)

CAS: 71-23-8 n-propanol

Oral LD50 500 mg/kg (ATE)

· Primary irritant effect:

• on the skin: No irritant effect.

- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

US

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number		
· DOT, IMDG, IATA	UN1274	
· UN proper shipping name		
· DOT, IMDG, IATA	n-Propanol solution	
• Transport hazard class(es)		
DOT		
RAMADE LODO		
J		
· Class	3 Flammable liquids	
· Label	3	

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

	(Contd. of page
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	F- E , S - D
Stowage Category	В
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
· · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1274 N-PROPANOL SOLUTION, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

– US

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water

2:1 Solution

(Contd. of page 8)

A4

• Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

CAS: 71-23-8 n-propanol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling:

n-propanol

• Hazard statements

Highly flammable liquid and vapor. Causes serious eve damage.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

Printing date 11/07/2019

Reviewed on 11/07/2019

Trade name: N-Propanol : Water 2:1 Solution

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision Revision 0.0, 11-07-2019: Creation date for SDS. STN 11/07/2019 / -· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3