Printing date 03/09/2020

Reviewed on 03/09/2020

1 Identification	
· Product identifier	
· Trade name: HBBLI	
Level 1	
• Article number: ARL008	
• Details of the supplier of the safety data sheet • Manufacturer/Supplier:	
Aqua Solutions, Inc.	
6913 Highway 225 DEER PARK, TX 77536	SOLUTIONS
USA	
800-256-2586	
· Information department:	
Technical Coordinator Sherman Nelson sherman@aquasolutions.org	
· Emergency telephone number:	
Chemtrec: 800-424-9300 Canutec: 613-996-6666	
2 Hazard(s) identification	
• Classification of the substance or mixture	
GHS02 Flame	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
GHS08 Health hazard	
Carc. 2 H351 Suspected of causing cancer.	
Repr. 2H361 Suspected of damaging fertility or the unSTOT RE 1H372 Causes damage to the hearing organs th	
Asp. Tox. 1 H304 May be fatal if swallowed and enters air	
GHS07	
\mathbf{V}	
Skin Irrit. 2 H315 Causes skin irritation.	
STOT SE 3 H336 May cause drowsiness or dizziness.	
· Label elements	
• GHS label elements The product is classified and labeled ac • Hazard pictograms	cording to the Globally Harmonized System (GHS).
$\land \land \land \land$	
GHS02 GHS07 GHS08	
· Signal word Danger	
0	(Contd. on page 2)

Printing date 03/09/2020

Trade name: HBBLI Level 1 Reviewed on 03/09/2020

(Contd. of page 1) · Hazard-determining components of labeling: Cyclohexane Hexane Styrene 99+% 4-Vinyl-1-Cyclohexene · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. *Causes damage to the hearing organs through prolonged or repeated exposure.* May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

(Contd. on page 3)

- U

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI

Level 1

(Contd. of page 2)

90.0%

4.0%

3.0%

3.0%

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 110-82-7	Cyclohexane
---------------	-------------

CAS: 110-54-3 Hexane

CAS: 100-40-3 4-Vinyl-1-Cyclohexene

CAS: 100-42-5 Styrene 99+%

4 First-aid measures

· Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

US

Printing date 03/09/2020

Trade name: HBBLI

Level 1

Reviewed on 03/09/2020

	Absorb with liq		(Contd. of page 3)	
	See Section 8 fo See Section 13	or information on safe handling. or information on personal protection equipment. for disposal information. on Criteria for Chemicals		
	· PAC-1:			
	CAS: 110-82-7	Cyclohexane	300 ppm	
	CAS: 110-54-3	Hexane	260 ppm	
	CAS: 100-40-3	4-Vinyl-1-Cyclohexene	0.3 ppm	
	CAS: 100-42-5	Styrene 99+%	20 ppm	
Ī	• PAC-2:			
	CAS: 110-82-7	Cyclohexane	1700* ppm	
	CAS: 110-54-3	Hexane	2900* ppm	
	CAS: 100-40-3	4-Vinyl-1-Cyclohexene	210 ppm	
	CAS: 100-42-5	Styrene 99+%	130 ppm	
Ī	· PAC-3:			
	CAS: 110-82-7	Cyclohexane	10000** ppm	
	CAS: 110-54-3	Hexane	8600** ppm	
	CAS: 100-40-3	4-Vinyl-1-Cyclohexene	340 ppm	
	CAS: 100-42-5	Styrene 99+%	1100* ppm	
. L			~ ~	

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- \cdot Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

(Contd. on page 5)

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI Level 1

(Contd. of page 4)

Additi	ional information about design of technical systems: No further data; see item 7.	
Contr	ol parameters	
Comp	onents with limit values that require monitoring at the workplace:	
CAS:	110-82-7 Cyclohexane	
PEL	Long-term value: 1050 mg/m ³ , 300 ppm	
REL	Long-term value: 1050 mg/m ³ , 300 ppm	
TLV	Long-term value: 344 mg/m ³ , 100 ppm	
CAS:	110-54-3 Hexane	
PEL	Long-term value: 1800 mg/m ³ , 500 ppm	
REL	Long-term value: 180 mg/m ³ , 50 ppm	
TLV	Long-term value: 176 mg/m³, 50 ppm Skin; BEI	
CAS:	100-40-3 4-Vinyl-1-Cyclohexene	
TLV	Long-term value: 0.44 mg/m ³ , 0.1 ppm	
WEEL	L Long-term value: 4.4 mg/m³, 1 ppm	
CAS:	100-42-5 Styrene 99+%	
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs	
REL	Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm	
TLV	Short-term value: (170) mg/m ³ , (40) NIC-20 ppm Long-term value: (85) mg/m ³ , (20) NIC-10 ppm BEI, NIC-A3, NIC-OTO	
Ingre	dients with biological limit values:	
-	110-54-3 Hexane	
1 7	0.4 mg/L LD50 Intraperitoneal: urine Fime: end of shift at end of workweek LD50: 2.5-Hexanedione without hydrolysis	
CAS:	100-42-5 Styrene 99+%	
1 7	000 mg/g creatinine D50 Intraperitoneal: urine Fime: end of shift D50: Mandelic acid plus phenylglyoxylic acid (nonspecific)	
1 7	0.2 mg/L D50 Intraperitoneal: venous blood Fime: end of shift	
	D50: Styrene (semi-quantitative) Conal information: The lists that were valid during the creation were used as basis.	

Printing date 03/09/2020

Reviewed on 03/09/2020


Trade name: HBBLI Level 1

(Contd. of page 5)

Exposure controls
Personal protective equipment:
General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Liquid	
Color:	Clear-Pale Yellow	
Odor:	Strong	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	81 °C (177.8 °F)	

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI

ume.	IIDDLI
	Level 1

	(Contd. of page 6)
· Flash point:	-18 °C (-64.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 8.3 Vol %
· Vapor pressure at 20 °C (68 °F):	104 hPa (78 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	0.78054 g/cm ³ (6.51361 lbs/gal) Not determined. Not determined. Not determined.
• Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
\cdot Partition coefficient (n-octanol/wate	pr): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
• Solvent content: Organic solvents: VOC content:	97.0 % 97.00 % 757.1 g/l / 6.32 lb/gal
Solids content: • Other information	0.0 % No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

US

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI

Level 1

(Contd. of page 7)

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 43,430 mg/kg (rat)

Inhalative LC50/4h 900 mg/l (mouse)

CAS: 100-42-5 Styrene 99+%

Inhalative LC50/4h 11 mg/l (ATE)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 100-40-3 4-Vinyl-1-Cyclohexene	2B
CAS: 100-42-5 Styrene 99+%	28
· NTP (National Toxicology Program)	
CAS: 100-42-5 Styrene 99+%	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 9)

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI Level 1

(Contd. of page 8)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

UN-Number	
DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Cyclohexane, Hexanes)
IMDG	FLAMMABLE LIQUID, N.O.S. (CYCLOHEXANE, HEXANE) MARINE POLLUTANT
IATA	FLAMMABLE LIQUID, N.O.S. (CYCLOHEXANE, HEXANES)
Transport hazard class(es)	
DOT	
3	
· Class	3 Flammable liquids
Label	3
IMDG	
Class	3 Flammable liquids
Label	3
IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substance Cyclohexane
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI Level 1

	(Contd. of page
· Danger code (Kemler):	33
· EMS Number:	F- E , S - D
· Stowage Category	В
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	5L
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (CYCLOHEXANE
0	HEXANES), 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixtur	e
· Sara	
Section 255 (automote har and and and and and and	

· Section 355 (ex	tremely hazardous substances):	
None of the ing	redients is listed.	
· Section 313 (Sp	ecific toxic chemical listings):	
CAS: 110-82-7 Cyclohexane		
CAS: 110-54-3	Hexane	
CAS: 100-42-5	Styrene 99+%	
· TSCA (Toxic Si	ubstances Control Act):	
Cyclohexane		ACTIVE
Hexane		ACTIVE
4-Vinyl-1-Cyclohexene		ACTIVE
Styrene 99+%		ACTIVE
· Hazardous Air	Pollutants	
CAS: 110-54-3	Hexane	
CAS: 100-42-5	Styrene 99+%	
· Proposition 65		
· Chemicals know	wn to cause cancer:	
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	
CAS: 100-42-5	Styrene 99+%	
· Chemicals know	wn to cause reproductive toxicity for females:	
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	
· Chemicals know	wn to cause reproductive toxicity for males:	
CAS: 110-54-3	Hexane	
		(Contd. on page 1

US

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI

Level 1

(Contd. of page 10)

I II

A3

A4

 \cdot Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 110-82-7 Cyclohexane

CAS: 110-54-3 Hexane

· TLV (Threshold Limit Value established by ACGIH)

CAS: 100-40-3 4-Vinyl-1-Cyclohexene

CAS: 100-42-5 Styrene 99+%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Cyclohexane Hexane Styrene 99+% 4-Vinyl-1-Cyclohexene · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. *Causes damage to the hearing organs through prolonged or repeated exposure.* May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eve protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting.

(Contd. on page 12)

Printing date 03/09/2020

Reviewed on 03/09/2020

Trade name: HBBLI Level 1

(Contd. of page 11)

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of preparation / last revision Revision 0.0, 03-06-2020: Creation date for SDS. STN 03/09/2020 / -
- · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Asp. Tox. 1: Aspiration hazard - Category 1

-US-