Printing date 03/31/2020

Reviewed on 06/13/2018

## **1** Identification

- · Product identifier
- · Trade name: Toluene, Reagent ACS Grade
- Article number: T7601-4L
- · CAS Number: 108-88-3
- · EC number: 203-625-9
- · Index number: 601-021-00-3
- Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586
- · Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org
- · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child. Repr. 2

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



*Printing date 03/31/2020* 

Reviewed on 06/13/2018

Trade name: Toluene, Reagent ACS Grade

Hazard pictograms	(Contd. of page 1
GHS02 GHS07 GHS08	
Signal word Danger	
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations	c
Classification system:	
NFPA ratings (scale 0 - 4)	
A A A A A A A A A A A A A A A A A A A	
Health = 1	
Fire = $3$	
1 $0$ Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
= 1euuu = 2	

HEALTH2Health = 2FIRE3Fire = 3REACTIVITY0Reactivity = 0

(Contd. on page 3)

Printing date 03/31/2020

Reviewed on 06/13/2018

#### Trade name: Toluene, Reagent ACS Grade

(Contd. of page 2)

- Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description
- 108-88-3 Toluene
- · Identification number(s)
- EC number: 203-625-9
- Index number: 601-021-00-3

### 4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

# No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

US

Printing date 03/31/2020

Reviewed on 06/13/2018

#### Trade name: Toluene, Reagent ACS Grade

(Contd. of page 3)

- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

• **PAC-1:** 67 ppm

- PAC-2: 560 ppm
- **PAC-3:** 3700\* ppm

### 7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- $\cdot$  Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 108-88-3 Toluene

- PEL Long-term value: 200 ppm Ceiling limit value: 300; 500\* ppm \*10-min peak per 8-hr shift
- REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm Long-term value: 375 mg/m<sup>3</sup>, 100 ppm
- TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm BEI

(Contd. on page 5)

*Printing date 03/31/2020* 

Reviewed on 06/13/2018

Trade name: Toluene, Reagent ACS Grade

(Contd. of page 4)

•	(Contd. of page 4
-	edients with biological limit values:
	: 108-88-3 Toluene
BEI	0.02 mg/L
	LD50 Intraperitoneal: blood
	Time: prior to last shift of workweek
	LD50: Toluene
	0.03 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Toluene
	0.3 mg/g creatinine
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: o-Cresol with hydrolysis (background)
Addi	tional information: The lists that were valid during the creation were used as basis.
Wash Store Avoi Avoi <b>Brea</b> In ca respi	ediately remove all soiled and contaminated clothing. a hands before breaks and at the end of work. p protective clothing separately. d contact with the skin. d contact with the eyes and skin. <b>thing equipment:</b> use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure us fratory protective device that is independent of circulating air. <b>ection of hands:</b>
un	Protective gloves
Due chen	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the ical mixture.
Mate	ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation <b>prial of gloves</b>
The s	selection of the suitable gloves does not only depend on the material, but also on further marks of quality an

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.





Tightly sealed goggles

(Contd. on page 6)

US –

(Contd. of page 5)

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2020

Reviewed on 06/13/2018

## Trade name: Toluene, Reagent ACS Grade

· Body protection: Protective work clothing

imixtures are possible.	9 Physical and chemical properties					
· Appearance: Liquid   Form: Liquid   Color: Colorless   · Odor: Aromatic   · Odor threshold: Not determined.   · pH-value: Not determined.   · Change in condition Metting point/Melting range:   · PH-value: Not determined.   · Change in condition -95 °C (-139 °F)   Boiling point/Boiling range: 110-111 °C (230-167.8 °F)   · Flash point: 4 °C (39.2 °F)   · Flash point: 535 °C (995 °F)   · Decomposition temperature: Not applicable.   · Ignition temperature: Not determined.   · Auto igniting: Not determined.   · Danger of explosion: Product is not explosive. However, formation of explosive air/va mixtures are possible.   · Explosion limits: 1.2 Vol %   · Upper: 7 Vol %   · Vapor pressure at 20 °C (68 *F): 29 hPa (21.8 mm Hg)   · Density at 20 °C (68 *F): 0.86683 g/cm² (7.2337 lbs/gal)   · Relative density Not determined.   · Vapor density Not determined.   · Vapor density Not determined.   · Solubility in / Miscibility with<						
Form:LiquidColor:ColorlessOdor:AromaticOdor threshold:Not determined.• pH-value:Not determined.• pH-value:Not determined.• Change in condition Melting point/Melting range: Boiling point/Boiling range:-95 °C (-139 °F) Boiling point/Boiling range:• Flash point:4 °C (39.2 °F)• Flash point:4 °C (39.2 °F)• Flammability (solid, gaseous):Not applicable.• Ignition temperature:535 °C (995 °F)• Decomposition temperature:Not determined.• Auto igniting:Not determined.• Danger of explosion:Product is not explosive. However, formation of explosive air/valmixtures are possible.• Explosion limits: Lower:1.2 Vol %Upper:7 Vol %• Vapor pressure at 20 °C (68 °F):29 hPa (21.8 mm Hg)• Density at 20 °C (68 °F):0.86683 g/cm³ (7.2337 lbs/gal)• Relative densityNot determined.• Vapor densityNot determined.• Solubility in / Miscibility with Water at 15 °C (97 °F):0.5 g/l• Partition coefficient (n-octanol/water): Not determined.						
Color:ColorlessOdor:AromaticOdor threshold:Not determined.• pH-value:Not determined.• Change in condition-95 °C (-139 °F)Boiling point/Melting range:110-111 °C (230-167.8 °F)• Flash point:4 °C (39.2 °F)• Flash point:4 °C (39.2 °F)• Flammability (solid, gaseous):Not applicable.• Ignition temperature:535 °C (995 °F)• Decomposition temperature:Not determined.• Auto igniting:Not determined.• Danger of explosion:Product is not explosive. However, formation of explosive air/va mixtures are possible.• Explosion limits: Lower:1.2 Vol % Vapor pressure at 20 °C (68 °F):29 hPa (21.8 mm Hg)Not determined.• Density at 20 °C (68 °F):29 hPa (21.8 mm Hg)• Density at 20 °C (68 °F):0.86683 g/cm³ (7.2337 lbs/gal)• Relative density Vapor densityNot determined.• Solubility in / Miscibility with Water at 15 °C (59 °F):0.5 g/l• Partition coefficient (n-octanol/water): Not determined.		Liquid				
• Odor: Aromatic   • Odor threshold: Not determined.   • pH-value: Not determined.   • Change in condition -95 °C (-139 °F)   Boiling point/Melting range: 110-111 °C (230-167.8 °F)   • Flash point: 4 °C (39.2 °F)   • Flash point: 4 °C (39.2 °F)   • Flammability (solid, gaseous): Not applicable.   • Ignition temperature: 535 °C (995 °F)   • Decomposition temperature: Not determined.   • Auto igniting: Not determined.   • Auto igniting: Not determined.   • Danger of explosion: Product is not explosive. However, formation of explosive air/va mixtures are possible.   • Explosion limits: 1.2 Vol %   Upper: 7 Vol %   • Vapor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   • Density at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Not determined.   • Solubility in / Miscibility with Not determined.   • Solubility in / Miscibility with Not determined.   • Solubility i		1				
· Odor threshold:Not determined.· pH-value:Not determined.· Change in condition Melting point/Melting range: Boiling point/Boiling range:-95 °C (-139 °F) 110-111 °C (230-167.8 °F)· Flash point:4 °C (39.2 °F)· Flammability (solid, gaseous):Not applicable.· Ignition temperature:535 °C (995 °F)· Decomposition temperature:Not determined.· Danger of explosion:Product is not explosive. However, formation of explosive air/valmixtures are possible.· Explosion limits: Lower: Upper:1.2 Vol %· Vapor pressure at 20 °C (68 °F):29 hPa (21.8 mm Hg)· Density at 20 °C (68 °F):0.86683 g/cm³ (7.2337 lbs/gal)· Relative density · Vapor densityNot determined.· Solubility in / Miscibility with Water at 15 °C (59 °F):0.5 g/l· Partition coefficient (n-octanol/water): Not determined5 g/l						
• pH-value: Not determined.   • Change in condition Melting point/Melting range: -95 °C (-139 °F) 110-111 °C (230-167.8 °F)   • Flash point: 4 °C (39.2 °F)   • Flammability (solid, gaseous): Not applicable.   • Ignition temperature: 535 °C (995 °F)   • Decomposition temperature: Not determined.   • Auto igniting: Not determined.   • Danger of explosion: Product is not explosive. However, formation of explosive air/va mixtures are possible.   • Explosion limits: 1.2 Vol %   Upper: 7 Vol %   • Vagor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   • Density at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Vapor density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Not determined.   • Solubility in / Miscibility with 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined. .5 g/l						
Melting point/Melting range: Boiling point/Boiling range:-95 °C (-139 °F) 110-111 °C (230-167.8 °F)· Flash point:4 °C (39.2 °F)· Flammability (solid, gaseous):Not applicable.· Ignition temperature:535 °C (995 °F)· Decomposition temperature:Not determined.· Auto igniting:Not determined.· Danger of explosion:Product is not explosive. However, formation of explosive air/va mixtures are possible.· Explosion limits: Lower: Upper:1.2 Vol % 7 Vol %· Vapor pressure at 20 °C (68 °F):29 hPa (21.8 mm Hg)· Density at 20 °C (68 °F):0.86683 g/cm³ (7.2337 lbs/gal)· Relative density 	· pH-value:					
Melting point/Melting range: Boiling point/Boiling range:-95 °C (-139 °F) 110-111 °C (230-167.8 °F)· Flash point:4 °C (39.2 °F)· Flammability (solid, gaseous):Not applicable.· Ignition temperature:535 °C (995 °F)· Decomposition temperature:Not determined.· Auto igniting:Not determined.· Danger of explosion:Product is not explosive. However, formation of explosive air/va mixtures are possible.· Explosion limits: Lower: Upper:1.2 Vol % 7 Vol %· Vapor pressure at 20 °C (68 °F):29 hPa (21.8 mm Hg)· Density at 20 °C (68 °F):0.86683 g/cm³ (7.2337 lbs/gal)· Relative density · Vapor densityNot determined.· Solubility in / Miscibility with Water at 15 °C (59 °F):0.5 g/l· Partition coefficient (n-octanol/water): Not determined5 g/l	· Change in condition					
Boiling point/Boiling range: 110-111 °C (230-167.8 °F)   • Flash point: 4 °C (39.2 °F)   • Flammability (solid, gaseous): Not applicable.   • Ignition temperature: 535 °C (995 °F)   • Decomposition temperature: Not determined.   • Auto igniting: Not determined.   • Danger of explosion: Product is not explosive. However, formation of explosive air/va mixtures are possible.   • Explosion limits: 1.2 Vol %   Lower: 1.2 Vol %   Upper: 7 Vol %   • Vapor pressure at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Wot determined.   • Solubility in / Miscibility with 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.		-95 °C (-139 °F)				
• Flash point: 4 °C (39.2 °F)   • Flammability (solid, gaseous): Not applicable.   • Ignition temperature: 535 °C (995 °F)   • Decomposition temperature: Not determined.   • Auto igniting: Not determined.   • Danger of explosion: Product is not explosive. However, formation of explosive air/va mixtures are possible.   • Explosion limits: 1.2 Vol %   Lower: 1.2 Vol %   Vpper: 7 Vol %   • Vapor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   • Density at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Water at 15 °C (59 °F):   • Solubility in / Miscibility with 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.						
• Flammability (solid, gaseous): Not applicable.   • Ignition temperature: 535 °C (995 °F)   • Decomposition temperature: Not determined.   • Auto igniting: Not determined.   • Danger of explosion: Product is not explosive. However, formation of explosive air/va mixtures are possible.   • Explosion limits: 1.2 Vol %   Lower: 1.2 Vol %   Upper: 7 Vol %   • Vapor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   • Density at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Not determined.   • Solubility in / Miscibility with 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.						
• Ignition temperature: 535 °C (995 °F)   • Decomposition temperature: Not determined.   • Auto igniting: Not determined.   • Danger of explosion: Product is not explosive. However, formation of explosive air/va mixtures are possible.   • Explosion limits: I.2 Vol %   Lower: 1.2 Vol %   Upper: 7 Vol %   • Vapor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   • Density at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Not determined.   • Solubility in / Miscibility with 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.	•					
· Auto igniting: Not determined.   · Danger of explosion: Product is not explosive. However, formation of explosive air/vaminixtures are possible.   · Explosion limits: I.2 Vol %   Lower: 1.2 Vol %   Upper: 7 Vol %   · Vapor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   · Density at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   · Relative density Not determined.   · Vapor density Not determined.   · Solubility in / Miscibility with Not determined.   · Solubility in / Miscibility with 0.5 g/l   · Partition coefficient (n-octanol/water): Not determined. Not determined.						
• Danger of explosion: Product is not explosive. However, formation of explosive air/vamixtures are possible.   • Explosion limits: I.2 Vol %   Lower: 1.2 Vol %   Upper: 7 Vol %   • Vapor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   • Density at 20 °C (68 °F): 0.86683 g/cm³ (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Water at 15 °C (59 °F): 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined. Not determined.	• Decomposition temperature:	Not determined.				
imixtures are possible.	· Auto igniting:	Not determined.				
Lower:1.2 Vol %Upper:7 Vol %Vapor pressure at 20 °C (68 °F):29 hPa (21.8 mm Hg)Density at 20 °C (68 °F):0.86683 g/cm³ (7.2337 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water at 15 °C (59 °F):0.5 g/lPartition coefficient (n-octanol/water): Not determined.	· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.				
Lower:1.2 Vol %Upper:7 Vol %Vapor pressure at 20 °C (68 °F):29 hPa (21.8 mm Hg)Density at 20 °C (68 °F):0.86683 g/cm³ (7.2337 lbs/gal)Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with Water at 15 °C (59 °F):0.5 g/lPartition coefficient (n-octanol/water): Not determined.	· Explosion limits:					
• Vapor pressure at 20 °C (68 °F): 29 hPa (21.8 mm Hg)   • Density at 20 °C (68 °F): 0.86683 g/cm <sup>3</sup> (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Vapor density Not determined.   • Solubility in / Miscibility with Not determined.   • Solubility in / Miscibility with 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.	-	1.2 Vol %				
• Density at 20 °C (68 °F): 0.86683 g/cm <sup>3</sup> (7.2337 lbs/gal)   • Relative density Not determined.   • Vapor density Not determined.   • Evaporation rate Not determined.   • Solubility in / Miscibility with Not determined.   • Vater at 15 °C (59 °F): 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.	Upper:	7 Vol %				
• Relative density Not determined.   • Vapor density Not determined.   • Evaporation rate Not determined.   • Solubility in / Miscibility with Water at 15 °C (59 °F):   • Vation coefficient (n-octanol/water): Not determined.	· Vapor pressure at 20 °C (68 °F):	29 hPa (21.8 mm Hg)				
• Vapor density Not determined.   • Evaporation rate Not determined.   • Solubility in / Miscibility with Use of the second seco	• Density at 20 •C (68 •F):	0.86683 g/cm <sup>3</sup> (7.2337 lbs/gal)				
• Evaporation rate Not determined.   • Solubility in / Miscibility with 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.	· Relative density	Not determined.				
· Solubility in / Miscibility with   Water at 15 °C (59 °F): 0.5 g/l   · Partition coefficient (n-octanol/water): Not determined.	· Vapor density	Not determined.				
Water at 15 °C (59 °F): 0.5 g/l   • Partition coefficient (n-octanol/water): Not determined.	· Evaporation rate	Not determined.				
		0.5 g/l				
	· Partition coefficient (n-octanol/wat	er): Not determined.				
· Viscosity·	· Viscosity:					
<b>Dynamic at 20 °C (68 °F):</b> $0.6 \text{ mPas}$		0.6 mPas				
Kinematic: Not determined.						
• Other information No further relevant information available.						

## **10 Stability and reactivity**

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)

US

(Contd. of page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2020

Reviewed on 06/13/2018

Trade name: Toluene, Reagent ACS Grade

- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

· Information on toxicological effects

- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) 3
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

### **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

· UN-Number		
· DOT, IMDG, IATA	UN1294	

Printing date 03/31/2020

Reviewed on 06/13/2018

Trade name: Toluene, Reagent ACS Grade

	(Contd. of page
· UN proper shipping name · DOT MDC LATA	Toluene TOLUENE
· IMDG, IATA	IOLUENE
• Transport hazard class(es)	
·DOT	
PRAMARE COOD	
· Class	3 Flammable liquids
·Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
• Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	В
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· DOI · Quantity limitations	On passenger aircraft/rail: 5 L
Zuanny unuunns	On cargo aircraft only: 60 L
· Hazardous substance:	1000 lbs, 454 kg
· IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities ( $\widetilde{EQ}$ )	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1294 TOLUENE, 3, II

## **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

• Section 355 (extremely hazardous substances): Substance is not listed.

(Contd. on page 9)

<sup>—</sup> US

Printing date 03/31/2020

Reviewed on 06/13/2018

Trade name: Toluene, Reagent ACS Grade

(Contd. of page 8)

• Section 313 (Specific toxic chemical listings): Substance is listed.

- · TSCA (Toxic Substances Control Act): ACTIVE
- · Hazardous Air Pollutants Substance is listed.
- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is listed.

· Carcinogenic categories

- · EPA (Environmental Protection Agency) II
- TLV (Threshold Limit Value established by ACGIH) A4
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- *GHS label elements* The substance is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Printing date 03/31/2020

Reviewed on 06/13/2018

Trade name: Toluene, Reagent ACS Grade

(Contd. of page 9)

Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of preparation / last revision Revision 0.1, Reviewed SDS. STN 03/31/2020 / -

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1