US

Safety Data Sheet acc. to OSHA HCS

Printing date 06/12/2024

Reviewed on 05/13/2024

1 Identification · Product identifier · Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity • Article number: THE478 · CAS Number: 110-54-3 · EC number: 203-777-6 · Index number: 601-037-00-0 • Details of the supplier of the safety data sheet · Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 · Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org · Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666 2 Hazard(s) identification · Classification of the substance or mixture GHS02 Flame Flammable Liquids 2 H225 Highly flammable liquid and vapor. GHS08 Health hazard Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways. GHS07 Skin Irritation 2 H315 Causes skin irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements

• GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity



(Contd. on page 3)

US

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity

(Contd. of page 2)

- Other hazards
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description
- CAS: 110-54-3 Hexane
- · Identification number(s)
- EC number: 203-777-6
- Index number: 601-037-00-0

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

US

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity

(Contd. of page 3)

- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals
- **PAC-1:** 260 ppm
- **PAC-2:** 2900* ppm • **PAC-3:** 8600** ppm
- **PAC-3:** 8000*** ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 110-54-3 Hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

- REL Long-term value: 180 mg/m³, 50 ppm
- TLV Long-term value: 50 ppm Skin; BEI

· Ingredients with biological limit values:

CAS: 110-54-3 Hexane

BEI 0.5 mg/L

LD50 Intraperitoneal: urine Time: end of shift LD50: 2.5-Hexanedione without hydrolysis

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 5)

US

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

 \cdot Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Sweetish
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	69 °C (156.2 °F)
Flash point:	-26 °C (-14.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity

	(Contd. of pag
Upper:	7.7 Vol %
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
· Vapor pressure at 50 °C (122 °F):	540 hPa (405 mm Hg)
· Density at 20 °C (68 °F):	0.659 g/cm ³ (5.49936 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	0.1 g/l
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
• Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 7)

US

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity

(Contd. of page 6)

- \cdot Additional ecological information:
- · General notes:

Water hazard class 3 (Assessment by list): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

4 Transport information		
· UN-Number		
· DOT, IMDG, IATA	UN1208	
· UN proper shipping name		
·DOT	Hexanes	
· IMDG · IATA	HEXANES, MARINE POLLUTANT HEXANES	
	HEXANES	
Transport hazard class(es)		
DOT		
RUMUREE LOUD		
Class	3 Flammable liquids	
Label	3	
IMDG		
Class	3 Flammable liquids	
Label	3	
IATA		
Class	3 Flammable liquids	
	(Contd. on	pag

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity

	(Contd. of pag
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Environmentally hazardous substance, liquid; Marine Pollutant
Marine pollutant:	No
-	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	Ε
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
Hazardous substance:	5000 lbs, 2270 kg
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1208 HEXANES, 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• Sara

- · Section 355 (extremely hazardous substances): Substance is not listed.
- · Section 313 (Specific toxic chemical listings): Substance is listed.
- TSCA (Toxic Substances Control Act): ACTIVE
- · Hazardous Air Pollutants Substance is listed.

· Proposition 65

- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.

· Carcinogenic categories

- · EPA (Environmental Protection Agency) II
- TLV (Threshold Limit Value) Substance is not listed.
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.

· GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity



16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- · Contact:
- Date of Preparation / Last Revision:
- Date of preparation / last revision
- Revision 1.2, 06/10/2024: Reviewed SDS for accuracy. MH/STN

(Contd. on page 10)

Printing date 06/12/2024

Reviewed on 05/13/2024

Trade name: n-Hexane (UV) (>95% n-Hexane), High Purity

	(Contd. of page 9)
Creation date for SDS 08-18-2016. STN	
06/12/2024 / -	
· Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLY: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 2: Flammable liquids – Category 2	
Skin Irritation 2: Skin corrosion/irritation – Category 2	
Toxic to Reproduction 2: Reproductive toxicity – Category 2	
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3	
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2	
Aspiration Hazard 1: Aspiration hazard – Category 1	
• * Data compared to the previous version altered.	
Dum compared to the previous reision durered.	