Printing date 07/27/2020 Reviewed on 07/27/2020

#### 1 Identification

· Product identifier

· Trade name: Alcohol, Reagent ACS Grade
Denatured Ethyl Alcohol

· Article number: A2700-4L

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Thermal Scientific Co. 4405 Westpark Ave. Beaumont TX (409) 724-2428

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapor.



GHS08 Health hazard

STOT SE 2 H371 May cause damage to the central nervous system and the visual organs.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Isopropanol

Methanol (Methyl Alcohol)

· Hazard statements

Extremely flammable liquid and vapor.

May cause damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

(Contd. on page 2)

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 1)

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 4Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:					
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	90.0%			
CAS: 67-56-1	Methanol (Methyl Alcohol)	5.0%			
CAS: 67-63-0	Isopropanol	5.0%			

#### 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	530 ppm
CAS: 67-63-0	Isopropanol	400 ppm
· PAC-2:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	2,100 ppm
CAS: 67-63-0	Isopropanol	2000* ppm
· PAC-3:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	7200* ppm
CAS: 67-63-0	Isopropanol	12000** ppm

US

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 3)

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

•		1		.1 .	•	•, •	1	1 1
· Components	with	umu	values	tnat	reauire	monitoring	at the	workplace:

#### CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm

#### CAS: 67-56-1 Methanol (Methyl Alcohol)

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm

Long-term value: 260 mg/m³, 200 ppm

Skir

TLV Short-term value: 328 mg/m³, 250 ppm

Long-term value: 262 mg/m³, 200 ppm

Skin; BEI

#### CAS: 67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm

Long-term value: 492 mg/m³, 200 ppm

BEI

(Contd. on page 5)

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 4)

#### · Ingredients with biological limit values:

#### CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

### CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

**-** U

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 5)

Information on basic physical and c	chemical properties
· General Information	
· Appearance:	*
Form: Color:	Liquid
· Odor:	Clear de l'alcool
ouor.	ue i uicooi
	l
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	Undetermined
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. <35 °C (<95 °F)
· Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	19 Vol %
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
Density at 20 °C (68 °F):	0.78923 g/cm³ (6.58612 lbs/gal)
· Relative density · Vapor density	Not determined. Not determined.
· vapor aensuy · Evaporation rate	Not determined. Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	M. J. J. J. J.
Dynamic: Kinematic:	Not determined.
	Not determined.
Solvent content: Organic solvents:	100.0 %
VOC content:	100.00 %
, oo comem.	789.2 g/l / 6.59 lb/gal
Solids content:	90.0 %

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 6)

· Other information

No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:					
ATE (Acut	ATE (Acute Toxicity Estimate)				
Oral	LD50	23,740-55,380 mg/kg (rat)			
Inhalative	LC50/4h	486 mg/l (rat)			
	, and the second				

#### CAS: 67-56-1 Methanol (Methyl Alcohol)

Oral	<i>LD50</i>	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4h	3 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· Carcinogenic	cuiegories				
· IARC (Intern	· IARC (International Agency for Research on Cancer)				
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1			
CAS: 67-63-0	Isopropanol	3			
· NTP (Nationa	· NTP (National Toxicology Program)				
None of the ingredients is listed.					
· OSHA-Ca (Occupational Safety & Health Administration)					

### 12 Ecological information

None of the ingredients is listed.

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 8)

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 7)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1 / 1		• ^ ,•
1/1 100	nanart	INTOVINATION
		information
	lup p u lu .	20, 01 1100000010

***		
I/N.	.Num	her

· DOT, IMDG, IATA

UN1987

· UN proper shipping name

 $\cdot DOT$ 

Alcohols, n.o.s. (Ethanol, Methanol, Isopropanol)

· IMDG, IATA ALCOHOLS, N.O.S. (ETHANOL, METHANOL, Isopropanol)

- · Transport hazard class(es)
- $\cdot DOT$



· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· Packing group

· DOT, IMDG, IATA

II

(Contd. on page 9)

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

	(Contd. of page
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	B
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
~ ,	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{EQ})$	Code: E2
(2)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1987 ALCOHOLS, N.O.S. (ETHANOL, METHANO
-	ISOPROPANOL), 3, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355 (extre	mely hazard	ous subst	ances):
----------------------	-------------	-----------	---------

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

CAS: 67-56-1 Methanol (Methyl Alcohol)

CAS: 67-63-0 Isopropanol

#### · TSCA (Toxic Substances Control Act):

Ethyl Alcohol, Absolute 200 Proof	ACTIVE
Methanol (Methyl Alcohol)	ACTIVE
Isopropanol	ACTIVE

#### · Hazardous Air Pollutants

CAS: 67-56-1 Methanol (Methyl Alcohol)

· Proposition 65

#### · Chemicals known to cause cancer:

None of the ingredients is listed.

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 10)

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 9)

#### · Chemicals known to cause developmental toxicity:

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

CAS: 67-56-1 Methanol (Methyl Alcohol)

#### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

None of the ingredients is listed.

#### TLV (Threshold Limit Value established by ACGIH)

12 (1.11 6316 14 21111 ) 41110 (3111 6311)		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	<i>A3</i>
CAS: 67-63-0	Isopropanol	A4

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Isopropanol

Methanol (Methyl Alcohol)

· Hazard statements

Extremely flammable liquid and vapor.

May cause damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

110

Printing date 07/27/2020 Reviewed on 07/27/2020

Trade name: Alcohol, Reagent ACS Grade Denatured Ethyl Alcohol

(Contd. of page 10)

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 1.1, 04-01-2020: Revised Hazard information per Fann. STN Revision 0.1, 06-11-2018 updated density results based on spreadsheet. STN 07/27/2020 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 1: Flammable liquids - Category 1

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2