Printing date 10/14/2020 Reviewed on 10/14/2020

1 Identification

· Product identifier

· Trade name: 1.0 mg/L 12 Component

Mixed Metal Working Solution

· Article number: SGS077

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number:

Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrochloric Acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

(Contd. on page 2)

Reviewed on 10/14/2020 Printing date 10/14/2020

Trade name: 1.0 mg/L 12 Component **Mixed Metal Working Solution**

(Contd. of page 1)

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*3 *Health* = *3 Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous compo		
CAS: 7647-01-0	Hydrochloric Acid	2.351%
· Table of Nonhaza	rdous Ingredients	
CAS: 7732-18-5	Water	96.996%
CAS: 12007-60-2	Lithium Tetraborate, Reagent	0.359%
CAS: 87-69-4	L-Tartaric Acid	0.249%
CAS: 7789-24-4	Lithium Fluoride	0.0399%
CAS: 7697-37-2	Nitric Acid	0.0025%
CAS: 7784-27-2	Aluminum Nitrate	0.000696%
CAS: 13446-18-9	Magnesium Nitrate	0.000528%
CAS: 7782-61-8	Ferric Nitrate	0.000362%
CAS: 16919-19-0	Ammonium hexafluorosilicate	0.000317%
CAS: 7631-99-4	Sodium Nitrate	0.000181%
CAS: 7722-76-1	Ammonium Phosphate Monobasic	0.000186%
CAS: 471-34-1	Calcium Carbonate	0.000121%
CAS: 7757-79-1	Potassium Nitrate	0.00013%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component
Mixed Metal Working Solution

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Dilute with plenty of water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 7647-01-0	Hydrochloric Acid	1.8 ppm
CAS: 12007-60-2	Lithium Tetraborate, Reagent	4.3 mg/m ³
CAS: 87-69-4	L-Tartaric Acid	1.6 mg/m^3
CAS: 7789-24-4	Lithium Fluoride	10 mg/m^3
CAS: 7697-37-2	Nitric Acid	0.16 ppm
CAS: 7784-27-2	Aluminum Nitrate	83 mg/m³
CAS: 13446-18-9	Magnesium Nitrate	16 mg/m³
CAS: 7782-61-8	Ferric Nitrate	22 mg/m³
CAS: 16919-19-0	Ammonium hexafluorosilicate	12 mg/m³
CAS: 7631-99-4	Sodium Nitrate	4.1 mg/m ³
CAS: 7722-76-1	Ammonium Phosphate Monobasic	17 mg/m³
CAS: 471-34-1	Calcium Carbonate	45 mg/m³
CAS: 7757-79-1	Potassium Nitrate	9 mg/m³
CAS: 1314-62-1	Vanadium Pentoxide Reagent	0.64 mg/n

(Contd. on page 4)

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component Mixed Metal Working Solution

CAS: 10099-74-8	Nickel Metal	0.24 mg/n 4.5 mg/n
	Zinc Metal	6 mg/m ³
• PAC-2:	Zine meta	o mg/m
	Hydrochloric Acid	22 ppm
	Lithium Tetraborate, Reagent	47 mg/n
CAS: 87-69-4	L-Tartaric Acid	17 mg/n
	Lithium Fluoride	110 mg/
	Nitric Acid	24 ppm
	Aluminum Nitrate	920 mg/
	Magnesium Nitrate	180 mg/
	Ferric Nitrate	110 mg
	Ammonium hexafluorosilicate	130 mg/
	Sodium Nitrate	45 mg/r
CAS: 7722-76-1	Ammonium Phosphate Monobasic	190 mg/
CAS: 471-34-1	Calcium Carbonate	210 mg
CAS: 7757-79-1	Potassium Nitrate	100 mg.
CAS: 1314-62-1	Vanadium Pentoxide Reagent	7 mg/m
CAS: 10099-74-8	Lead Nitrate	180 mg
CAS: 7440-02-0	Nickel Metal	50 mg/n
CAS: 7440-66-6	Zinc Metal	21 mg/r
PAC-3:		<u> </u>
CAS: 7647-01-0	Hydrochloric Acid	100 ppm
CAS: 12007-60-2	Lithium Tetraborate, Reagent	280 mg/m
CAS: 87-69-4	L-Tartaric Acid	100 mg/m
CAS: 7789-24-4	Lithium Fluoride	680 mg/m
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 7784-27-2	Aluminum Nitrate	5,500 mg/
	Magnesium Nitrate	1,100 mg/
CAS: 7782-61-8		640 mg/m
CAS: 16919-19-0	Ammonium hexafluorosilicate	780 mg/m
CAS: 7631-99-4	Sodium Nitrate	270 mg/m
	Ammonium Phosphate Monobasic	1,100 mg/
CAS: 471-34-1	Calcium Carbonate	1,300 mg/
CAS: 7757-79-1	Potassium Nitrate	600 mg/m
CAS: 1314-62-1	Vanadium Pentoxide Reagent	70 mg/m^3
CAS: 10099-74-8		1,100 mg/
CAS: 7440-02-0	Nickel Metal	99 mg/m^3

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component
Mixed Metal Working Solution

(Contd. of page 4)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:			
CAS: 7647-01-0 Hydrochloric Acid			
NIOSH RECOMENDED EXP LIMI	Ceiling limit value: 7.0 mg/m3 mg/m³		
PEL	Ceiling limit value: 7 mg/m³, 5 ppm		
REL	Ceiling limit value: 7 mg/m³, 5 ppm		
TLV	Ceiling limit value: 2.98 mg/m³, 2 ppm		

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component
Mixed Metal Working Solution

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



· Viscosity: Dynamic:

Kinematic:

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties	
· General Information		
· Appearance:		
Form:	Liquid	
Color:	Clear to pale green	
· Odor:	Odorless	
· Odor threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	<2	
· Change in condition		
Melting point/Melting range:	0 °C (32 °F)	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.00376 g/cm³ (8.37638 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	

Not determined.

Not determined.

(Contd. on page 7)

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component
Mixed Metal Working Solution

		(Contd. of page 6
· Solvent content:		
Water:	97.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.6 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 $The \ product \ shows \ the \ following \ dangers \ according \ to \ internally \ approved \ calculation \ methods \ for \ preparations:$

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Internation	nal Agency for Research on Cancer)	
CAS: 7789-24-4	Lithium Fluoride	3
CAS: 1314-62-1	Vanadium Pentoxide Reagent	2B
CAS: 10099-74-8	Lead Nitrate	2A
CAS: 7440-02-0	Nickel Metal	2B
· NTP (National To	oxicology Program)	
CAS: 10099-74-8	Lead Nitrate	R
CAS: 7440-02-0	Nickel Metal	R
· OSHA-Ca (Occup	national Safety & Health Administration)	
None of the ingred	lients is listed.	

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component
Mixed Metal Working Solution

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

Transport information		
· UN-Number · DOT, IMDG, IATA	Not regulated	
UN proper shipping name DOT, IMDG, IATA	Not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	Not regulated	
Packing group		
DOT, IMDG, IATA	Not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	II of Not applicable.	

(Contd. on page 9)

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component Mixed Metal Working Solution

(Contd. of page 8)

· UN ''Model Regulation'': Not regulated

	d environmental regulations/legislation specific for the sul	bstance or mixture
Sara		
,	emely hazardous substances):	
CAS: 7697-37-2		
CAS: 1314-62-1	Vanadium Pentoxide Reagent	
Section 313 (Spec	rific toxic chemical listings):	
CAS: 7697-37-2	Nitric Acid	
CAS: 7784-27-2	Aluminum Nitrate	
CAS: 13446-18-9	Magnesium Nitrate	
CAS: 7782-61-8	Ferric Nitrate	
CAS: 7757-79-1	Potassium Nitrate	
CAS: 1314-62-1	Vanadium Pentoxide Reagent	
CAS: 10099-74-8	Lead Nitrate	
CAS: 7440-02-0	Nickel Metal	
CAS: 7440-66-6	Zinc Metal	
TSCA (Toxic Sub	stances Control Act):	
Water		ACTI
Hydrochloric Aci	\overline{d}	ACTI
Lithium Tetrabor	ıte, Reagent	ACTI
L-Tartaric Acid		ACTI
Lithium Fluoride		ACTI
Nitric Acid		ACTI
Ammonium hexaf	uorosilicate	ACTI
Sodium Nitrate		ACTI
Ammonium Phosp	phate Monobasic	ACTI
Calcium Carbona	te	ACTI
Potassium Nitrate	1	ACTI
Vanadium Pentox	ide Reagent	ACTI
Lead Nitrate		ACTI
Nickel Metal		ACTI
Zinc Metal		ACTI
Hazardous Air Po	ollutants	
CAS: 7647-01-0	Hydrochloric Acid	
CAS: 10099-74-8	·	
Proposition 65	<u> </u>	
_	to cause cancer:	

A3

A5

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component
Mixed Metal Working Solution

	(Contd. of page 9
CAS: 10099-74-8 Lead Nitrate	
CAS: 7440-02-0 Nickel Metal	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
CAS: 12007-60-2 Lithium Tetraborate, Reagent	I (oral)
CAS: 10099-74-8 Lead Nitrate	B2
CAS: 7440-66-6 Zinc Metal	D, I, II
· TLV (Threshold Limit Value established by ACGIH)	
CAS: 7789-24-4 Lithium Fluoride	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Vanadium Pentoxide Reagent

CAS: 7440-02-0 Nickel Metal

CAS: 10099-74-8 Lead Nitrate

CAS: 7440-02-0 Nickel Metal

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms

CAS: 1314-62-1



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrochloric Acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

Printing date 10/14/2020 Reviewed on 10/14/2020

Trade name: 1.0 mg/L 12 Component
Mixed Metal Working Solution

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 0.0, 10-14-2020: Creation date for SDS. STN 10/14/2020 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

US